IPC - ASSOCIATION CONNECTION ELECTRONICS INDUSTRIE	© Copyright 2005. IPC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lowelevel parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No. Homogeneous Materi				ials and Mfg Information				
upplier Inforn	nation												
Company name*			Company unique ID			Unique ID Autho	ority		Response Date*				
nsemi									2024-04-17	2024-04-17			
Contact Name			Title - Contact			Phone - Contact*			Email - Contact*				
Product-Env-Stewards			Product Enviro Compliance			NA			Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative			Phone - Representative*			Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance			NA NA			Product-Env-Stewards@onsemi.com				
Request	er Item Number	Mfr Item Num	nber Mfr Item	Mfr Item Name		Effective Date	Version	Manufacturing Site	Weight*	UOM	Unit Type		
		NCP170AXV150T2G Ultra-Low IQ 150 mA CN Regulator, Act Discharge.				2024-04-17		MY1	2.79	mg	Each		
Ianufacturing	Process Information	on											
Terminal Plating / Grid Array Material Terminal Base Alloy			J-STD-020 M	ISL Rating	Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles								
Matte Tin (Sn) - annealed		CU All	CU Alloy 1			260	C	30	seconds 3				
omments													
vel 1 - maximum	time at peak temperature	e during solderin	ng is 10-30 seconds	5									
or more informat	ion regarding material co	omposition please	e refer to page 3										

RoHS Material Composition Declaration			Declaration Type *	Detail	ed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its uppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Itaalian agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions										
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the					

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.12	mg	Supplier	Silicon (Si)	7440-21-3		0.12	mg
Lead Frame	1.18	mg	В	Nickel (Ni)	7440-02-0		0.4283	mg
			Supplier	Iron (Fe)	7439-89-6		0.5924	mg
			Supplier	Copper (Cu)	7440-50-8		0.1593	mg
Mold Compound-Black	1.4	mg		Epoxy Phenol Resin	proprietary data		0.147	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		1.253	mg
Plating	0.06	mg	Supplier	Tin (Sn)	7440-31-5		0.06	mg
Wire Bond - Au	0.03	mg	Supplier	Gold (Au)	7440-57-5		0.03	mg