© Copyright 2005. IPC, Bann	CONVECTING CONVECTING CODVICE THES* MOUSTRES* MOUST				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.							
	IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribu			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information								
Supplier Information												
mpany name* Company unique ID				Unique ID Authority				Response Date*				
onsemi	emi							2024-04-25				
Contact Name	Title - Contact			Phone - Contact*				Email - Contact*				
Product-Env-Stewards	uct-Env-Stewards Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
uthorized Representative* Title - Representative				Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester Item Number Mfr	Item Number	Mfr Item Name		Effective	e Date	Version	Manufacturing Site		Weight*	UOM	Unit Type	
NCF	3233MNTXG	High Current Sync	chronous Buck Converte	r 2024-04-	-25		PH1	:	114.9	mg	Each	
Manufacturing Proccess Information				•			·					
Terminal Plating / Grid Array Material	l Terminal Base Alloy J		-STD-020 MSL Rating	Peal	Peak Process Body Tempe		ture Max Time at Peak Temp		ure Number	r of Reflow Cyc	les	
Matte Tin (Sn) - annealed CU Alloy 3			•	260		С	30	secon	ids 3			
Comments												
ATTENTION: MSL 3 Rated item requires Bake a	nd Dry Pack (afte	r electrical test)										
For more information regarding material composition	ion please refer to	o page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et	
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).		
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the
Supplier Digital Signature	astislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	15.66	mg	Supplier	Zinc (Zn)	7440-66-6		0.0188	mg
			Supplier	Iron (Fe)	7439-89-6		0.368	mg
			Supplier	Copper (Cu)	7440-50-8		15.2685	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0047	mg
Die	4.6	mg	Supplier	Silicon (Si)	7440-21-3		4.6	mg
Die Attach Solder	1.72	mg	Supplier	Silver (Ag)	7440-22-4		0.043	mg
			А	Lead (Pb)	7439-92-1	7a	1.591	mg
			Supplier	Tin (Sn)	7440-31-5		0.086	mg
Lead Frame	40.03	mg	Supplier	Silver (Ag)	7440-22-4		0.4003	mg
			Supplier	Tin (Sn)	7440-31-5		0.1001	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0881	mg
			Supplier	Chromium (Cr)	7440-47-3		0.1001	mg
			Supplier	Copper (Cu)	7440-50-8		39.3415	mg
Mold Compound-Black	51.07	mg		Epoxy resin	proprietary data		2.4003	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		5.107	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0511	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		41.1114	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		2.4003	mg
Plating	1.49	mg	Supplier	Tin (Sn)	7440-31-5		1.49	mg
Wire Bond	0.33	mg	Supplier	Palladium (Pd)	7440-05-3		0.0033	mg
			Supplier	Copper (Cu)	7440-50-8		0.3267	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).