ABSOCIATION CONNECTING ELECTRONICS INDUSTRIES® INCLUSTRES®	burn, Illinois. A	ll rights reserved un ntions.	nder both le	⁷ his docume evel parts, t	ent is a declaration e	on of the sub ncompasses	ostances v all lower	within the manufacture level materials for wh	er listed i hich the n	tem. Note: i nanufacturer	f the item is an as has engineering	sembly with lower responsibility.
1752-21.1 IPC Web Site for Information of http://www.ipc.org/IPC-175x	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute			Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia				als and Mfg Information				
Supplier Information												
mpany name* Company unique ID				Unique ID Authority				Response Date*				
onsemi	emi								2024-04-20			
Contact Name	e Title - Contact			Phone - Contact*				Email - Contact*				
bduct-Env-Stewards Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorized Representative* Title - Representative				Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product Enviro Compliance			NA					Produ		duct-Env-Stewards@onsemi.com		
Requester Item Number Mfr Ite	m Number	Mfr Item Name			Effective Date	Version	N	Manufacturing Site		Weight*	UOM	Unit Type
NCP52	12AMNTXG SYNC STEP DOWN		VN CONTROLL	ER	2024-04-20	PH1			37.78	mg	Each	
Manufacturing Proccess Information					•		ŀ					
Terminal Plating / Grid Array Material	1 Terminal Base Alloy		STD-020 MSL I	Rating	Peak Process Body		Femperature Max Time at Peak		Tempera	ture Numb	er of Reflow Cyd	cles
Matte Tin (Sn) - annealed CU Alloy 1				260		С	30	secon	nds 3			
Comments												
level 1 - maximum time at peak temperature during	oldering is 10-3	0 seconds										
For more information regarding material composition	n please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).									
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all					
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the					
Supplier Digital Signature Ra	stislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.25	mg	Supplier	Silicon (Si)	7440-21-3		0.25	mg
Die Attach 0.65	0.65	mg	Supplier	Silver (Ag)	7440-22-4		0.4875	mg
			Supplier	Epoxy resins	129915-35-1		0.1625	mg
Lead Frame 11.5	11.5	mg	Supplier	Silver (Ag)	7440-22-4		0.851	mg
			Supplier	Copper (Cu)	7440-50-8		10.649	mg
Mold Compound-Black	22.31	mg		Epoxy resin	proprietary data		1.5617	mg
			Supplier	Phenolic Resin	Proprietary Data		1.5617	mg
				Silica Amorphous (SiO2)	7631-86-9		3.3465	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1115	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		15.7285	mg
Plating	1.26	mg	Supplier	Tin (Sn)	7440-31-5		1.26	mg
Wire Bond - Au	1.81	mg	Supplier	Gold (Au)	7440-57-5		1.81	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)