IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x Supplier Information Company name* Company unique ID onsemi Contact Name Title - Contact Product-Env-Stewards Authorized Representative* Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards	Form Type * Distribute		aration Class * s 6 - RoHS Yes/No,	Homogeneous Materia	als and Mfg Informatio			
Company name* Company unique ID Contact Name Title - Contact Product-Env-Stewards Authorized Representative* Title - Representative						111		
nsemi Contact Name Title - Contact Product-Env-Stewards Authorized Representative* Title - Representative								
Contact Name Product-Env-Stewards Product Enviro Compliance Authorized Representative* Title - Representative		Unique ID Authority			Response Date*			
Product-Env-Stewards Product Enviro Compliance Authorized Representative* Title - Representative					2025-06-06			
Authorized Representative* Title - Representative		Phone - Contact*			Email - Contact*			
		NA			Product-Env-Stewards@onsemi.com			
Don to t Francis Committee		Phone - Representative*			Email - Representative*			
Product-Env-Stewards Product Enviro Compliance	Compliance NA		P		Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Item Number Mfr Item Name	•	Effective Date	Version 1	Manufacturing Site	Weight*	UOM	Unit Type	
NCV303LSN20T1G SBN 2. V ANA	UNDERVOLT	2025-06-06	1	MY1	14.08	mg	Each	
Manufacturing Process Information Terminal Plating (Crid Array Material Terminal Page Alley)	J-STD-020 MSL Rating	Pagli Propos	as Dody Tampanatu	May Time at Dack	Town ousting Number	a of Dofloys Cv	alag	
Terminal Plating / Grid Array Material Terminal Base Alloy Matta Tin (Sp.) appropriate CIL Allay	7-STD-020 WISE Rating		Peak Process Body Temperature Max Time at Peak T					
Matte Tin (Sn) - annealed CU Alloy	1	400	IC	30	seconds 3			
omments								
vel 1 - maximum time at peak temperature during soldering is 10-30 seconds or more information regarding material composition please refer to page 3								

RoHS Material Composition Declaration			Declaration Type *	Detail	led			
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).								
cadmium, hexavalentchromium, polybromir contains a RoHS restricted substance inexce encompass all such components. Supplier ce as of the date that Supplier completes this fo Company acknowledges that Supplier may l independently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated dipless of an applicable quantity limit, please intifies that it gathered the information it prome. Supplier acknowledges that Company have relied on information provided by other by others, Supplier agrees that, at a mining and the Supplier enter into a written agree esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substational substance below which, if any, RoHS exemption by desired in this form using appropriate method will rely on this certification in determining ters in completing this form, and that Supplies have provided certification between the will respect to the identified part, the Company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects to the identified part, the company's remedies for issues that arise respects the company is the company that the company tha	ws of the European Union member states) of the pnce") in excess of the applicable quantity limit ide in you believe may apply. If the part is an assembly is to ensure its accuracy and that such information the compliance of its products with European Union may not have independently verified such informs regarding their contributions to the part, and tho terms and conditions of that agreement, including the provides in this formation information the Supplier provides in this formation.	entified above. If a y with lower level is true and correct on member state la nation. However, in se certifications are any warranty rigl	n homogeneous material within the part components, the declaration shall t to the best of its knowledge and belief, aws that implement the RoHS Directive. In situations where Supplier has not e at least as comprehensive as the hts and/or remedies provided as part of			
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted			
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.								
Exemption List Version	EL-2011/534/EU							
Declaration Signature								
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recruired by the			
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.42	mg	Supplier	Silicon (Si)	7440-21-3		0.42	mg
Die Attach 0.11	0.11	mg	Supplier	Silver (Ag)	7440-22-4		0.088	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.022	mg
Lead Frame 5.78	5.78	mg	Supplier	Silver (Ag)	7440-22-4		0.0705	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0069	mg
			Supplier	Iron (Fe)	7439-89-6		0.1358	mg
			Supplier	Copper (Cu)	7440-50-8		5.565	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0017	mg
Mold Compound-Black	7.34	mg		Epoxy resin	proprietary data		0.367	mg
			Supplier	Phenolic Resin	Proprietary Data		0.367	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.1468	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0367	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		6.4225	mg
Plating	0.39	mg	Supplier	Tin (Sn)	7440-31-5		0.39	mg
Wire Bond - Au	0.04	mg	Supplier	Gold (Au)	7440-57-5		0.04	mg