ASSOCIATION CONNE	© Copyright 2005, IPC	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					aterials and I	Afg In	formation	1	
Supplier Info	ormation						·								
Company name* Comp				Company unique ID			Unique ID Authority					Response Date*			
nsemi											2024-0	2024-04-16			
Contact Name			Title - Contact			P	Phone - Contact*				Email	Email - Contact*			
Product-Env-St	tewards	Product Enviro Compliance			1	NA				Produ	Product-Env-Stewards@onsemi.com				
Authorized Representative* Titl				Title - Representative			Phone - Representative*				Email	Email - Representative*			
Product-Env-St	tewards	Product Enviro Compliance			1	NA				Produ	Product-Env-Stewards@onsemi.com				
Requ	uester Item Number	Mfr Iten	tem Number Mfr Item Name				Effective Dat	ective Date   Version   Man		Ianufacturing Sit	acturing Site		ht*	UOM	Unit Type
		NCV8160AMX330TB XDFN4 AD 3.3V G Noise and High P				a-Low	2024-04-16	4-16 THB				1.3 mg		Each	
<b>Ianufacturi</b>	ing Proccess Informatio	n													
Termi	al Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 MSL Rating		Peak Process Body Te		Temperatur	ture Max Time at Peak		emperature Number of Reflow Cycles		eles	
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		Au) (no	CU Alloy 1		1		260		C 30		seco	seconds 3			
Comments							•		•		•				
vel 1 - maximu	um time at peak temperature	during so	ldering is 10-3	0 seconds											
or more inforn	nation regarding material co	mposition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information is trought in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.											
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.106267	mg	Supplier	Silicon (Si)	7440-21-3		0.1063	mg
Die Attach Tape	0.012345	mg	Supplier	Acrylic AE Copolymer	58152-79-7		0.0019	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0062	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.0017	mg
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.0009	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0017	mg
Lead Frame	0.778612	mg	Supplier	Magnesium (Mg)	7439-95-4		0.0012	mg
			Supplier	Silicon (Si)	7440-21-3		0.0051	mg
			В	Nickel (Ni)	7440-02-0		0.0234	mg
			Supplier	Copper (Cu)	7440-50-8		0.749	mg
Mold Compound-Black	0.355444	mg		Epoxy resin	proprietary data		0.0167	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.0355	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0004	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		0.2861	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.0167	mg
Plating	0.024188	mg	Supplier	Palladium (Pd)	7440-05-3		0	mg
			В	Nickel (Ni)	7440-02-0		0.0242	mg
			Supplier	Gold (Au)	7440-57-5		0	mg
Wire Bond - Au	0.023144	mg	Supplier	Gold (Au)	7440-57-5		0.0231	mg