© C	Aterial Composit Copyright 2005. IPC, I rnational and Pan-Am	Bannockb	urn, Illinois. A	ll rights reserved nations.	under both	This docum level parts, t	ent is a declarat	ion of the su encompasse	ubstances s all lower	within the manufacture level materials for w	rer listed i which the n	tem. Note: nanufacture	if the item is an as er has engineering	sembly with low responsibility.	
					Form Type Distribute	e *	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
Supplier Information	ı														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2024-04	2024-04-24			
Contact Name			Title - Contact				Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative				Phone - Representative*				Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Produc	Product-Env-Stewards@onsemi.com			
Requester Item	Number	Mfr Item Number		Mfr Item Name			Effective Date	te Version Manufacturing Site			Weight*	UOM	Unit Type		
		NCV8614BMNR2G A		ANA MULTIPLE OUTPUT LDO		0	2024-04-24		Р	PH1		25.32	mg	Each	
Anufacturing Proce	cess Information	I													
Terminal Plating	Terminal Plating / Grid Array Material Terminal I		erminal Base A	e Alloy J-STD-020 MSL Rati		L Rating	Peak Process Body Temperature N		e Max Time at Peak	. Temperat	ture Num	ber of Reflow Cy	eles		
Matte Tin (Sn) - annealed		C	CU Alloy 1		1		260		С	30	secor	ids 3			
omments															
vel 1 - maximum time at	peak temperature d	uring sol	dering is 10-3	0 seconds											
or more information reg	arding material com	position	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.25	mg	Supplier	Silicon (Si)	7440-21-3		0.25	mg
Die Attach	0.65	mg	Supplier	Silver (Ag)	7440-22-4		0.4875	mg
			Supplier	Epoxy resins	129915-35-1		0.1625	mg
Lead Frame	10.18	mg	Supplier	Silver (Ag)	7440-22-4		0.7533	mg
			Supplier	Copper (Cu)	7440-50-8		9.4267	mg
Mold Compound-Black	12.09	mg		Epoxy resin	proprietary data		0.8463	mg
			Supplier	Phenolic Resin	Proprietary Data		0.8463	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		1.8135	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0604	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		8.5234	mg
Plating	0.44	mg	Supplier	Tin (Sn)	7440-31-5		0.44	mg
Wire Bond - Au	1.71	mg	Supplier	Gold (Au)	7440-57-5		1.71	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)