ASSOCIATION CONNECTING ASSOCIATION CONNECTING LECTRONICS INDUSTRIES® international and Pa	IPC. Bannockl	ourn, Illinois, A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declaration en declaration	on of the su	bstances v all lower	vithin the manufactu level materials for v	urer listed which the	item. Note: nanufacture	if the item is an as er has engineering	sembly with low responsibility.	
	21.1 IPC Web Site for Information on IPC-1752 Standard For http://www.ipc.org/IPC-175x Dis				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mf				Ifg Informa	tion				
upplier Information														
Company name* Company			ny unique ID			Unique ID Authority				Respon	Response Date*			
semi										2024-04	2024-04-29			
Contact Name	tact Name Title - Contact					Phone - Contact*				Email ·	Email - Contact*			
Product-Env-Stewards Product Enviro			viro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Representa			entative		Phone - Representative*				Email ·	Email - Representative*				
Product-Env-Stewards Product E			uct Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number	Mfr Iten	n Number	Mfr Item Name			Effective Date	Version	Version Manufacturing Site			Weight*	UOM	Unit Type	
	NJD287	D2873T4G BIPOLAR XTSR		2A/50V	2024-04-29			V	VN5		350.99	mg	Each	
Ianufacturing Proccess Informa	ntion		•			•								
Terminal Plating / Grid Array M	laterial 7	Terminal Base Alloy		J-STD-020 MSI	Rating	Peak Proce	ocess Body Temperature Max Time at Peak		k Tempera	ture Num	ber of Reflow Cyc	eles		
Matte Tin (Sn) - annealed CU Allo		CU Alloy	1			260 C		С	30 seco		seconds 3			
omments														
vel 1 - maximum time at peak temperat	ure during so	ldering is 10-3	0 seconds											
or more information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).									
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, is of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not ndependently verified information provided by others, Supplier agrees that, at a minimum, itssuppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the sertification in this paragraph. If the Company and the Supplier into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of hat agreement, will be the sole and exclusivesource of the Supplier's liability and the Company's remedies for issues that arise regarding information the Supplier provid										
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted					
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).							
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the					
Supplier Digital Signature	astislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.2	mg	Supplier	Silicon (Si)	7440-21-3		0.2	mg
Die Attach	1.4	mg	А	Lead (Pb)	7439-92-1	7a	1.33	mg
			Supplier	Tin (Sn)	7440-31-5		0.07	mg
Lead Frame	214.64	mg	В	Nickel (Ni)	7440-02-0		0.4293	mg
			Supplier	Copper (Cu)	7440-50-8		214.2107	mg
Mold Compound-Black	129.65	mg		Epoxy resin	proprietary data		9.0755	mg
			Supplier	Phenolic Resin	Proprietary Data		3.8895	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		12.965	mg
			Supplier	Carbon Black (C)	1333-86-4		0.6482	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		103.0717	mg
Plating	3.73	mg	Supplier	Tin (Sn)	7440-31-5		3.73	mg
Wire Bond - Al	1.37	mg	Supplier	Aluminum (Al)	7429-90-5		1.37	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signar range of distribution unless otherwise noted)