ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® International and Par	PC. Bannockl	burn. Illinois. A	ll rights reserved utions.	under both	This docume level parts, t	ent is a declarati he declaration e	on of the su	ibstances v s all lower	within the manufact level materials for	urer listed which the	item. Note: manufactur	if the item is an as er has engineering	sembly with low responsibility.	
				Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information					ation				
upplier Information														
Company name* Com			Company unique ID			Unique ID Authority				Respo	Response Date*			
nsemi										2024-0	2024-04-20			
ontact Name	tact Name Title - Contact					Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards Product Enviro C			o Compliance		NA				Produ	Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative			entative		Phone - Representative*			Email	Email - Representative*					
Product-Env-Stewards Product			oduct Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number	Mfr Item Number		Mfr Item Name			Effective Date	Version	N	Ianufacturing Site		Weight*	UOM	Unit Type	
	NLV74H	NLV74HC240ADWG LOG CMOS BUS		S INTRFCE OC	TL	2024-04-20		P	PH1		517.71	mg	Each	
Ianufacturing Proccess Informa	tion		-			•								
Terminal Plating / Grid Array Ma	aterial 7	ial Terminal Base Alloy		J-STD-020 MSI	L Rating	Peak Proc	ocess Body Temperature Max Time at Peak		k Tempera	ature Num	ber of Reflow Cyc	les		
Matte Tin (Sn) - annealed CU Alloy			3		260		С	30	seco	onds 3				
omments														
TTENTION: MSL 3 Rated item require	s Bake and L	Dry Pack (after	electrical test)											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	9.33	mg	Supplier	Silicon (Si)	7440-21-3		9.33	mg	
Die Attach	20.68	mg	Supplier	Silver (Ag)	7440-22-4		15.51	mg	
			Supplier	Epoxy resins	129915-35-1		5.17	mg	
Lead Frame	323.98	mg	Supplier	Silver (Ag)	7440-22-4		3.2398	mg	
			Supplier	Zinc (Zn)	7440-66-6		0.648	mg	
			Supplier	Iron (Fe)	7439-89-6		8.4235	mg	
			Supplier	Copper (Cu)	7440-50-8		311.6688	mg	
Mold Compound-Black	158.46	mg		Epoxy Phenol Resin	proprietary data		16.6383	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		141.8217	mg	
Plating	4.79	mg	Supplier	Tin (Sn)	7440-31-5		4.79	mg	
Wire Bond - Cu	0.47	mg	Supplier	Copper (Cu)	7440-50-8		0.47	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).