ASSOCIATION CONNECTING	Material Composit © Copyright 2005. IPC, international and Pan-Arr	Bannockb	urn, Illinois. A	ll rights reserved u tions.	nder both	This docume level parts, t	ent is a declara he declaration	ion of the s encompasse	ubstances es all lowe	within the manufactu r level materials for w	rer listed	item. Note: manufacture	if the item is an as r has engineering	sembly with lower responsibility.	
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					ials and N	als and Mfg Information				
Supplier Inform	ation														
Company name*			Company unique ID				Unique ID Authority				Respon	Response Date*			
onsemi											2025-00	2025-06-07			
Contact Name			Title - Contact				Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative				Phone - Representative*			Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requeste	Requester Item Number Mfr Item		n Number Mfr Item Name			<u> </u>	Effective Dat	e Version	on Manufacturing Site			Weight*	UOM	Unit Type	
		NLVHC1	IG04DFT1G	Single Inverter			2025-06-07		(CN1		6.2	mg	Each	
Manufacturing]	Proccess Information	1													
Terminal Plating / Grid Array Material Terr		erminal Base A	minal Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperature		re Max Time at Peak	Tempera	ture Num	ber of Reflow Cyc	les			
Matte Tin (Sn) - annealed CU Alloy			U Alloy	1	l		260		C	30	seco	nds 3			
Comments															
evel 1 - maximum ti	me at peak temperature d	luring sol	dering is 10-3	0 seconds											
for more information	on regarding material com	position j	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted							
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all						
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

sigma range of distribution unless	otherwise noted).				-	_		-
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.19	mg	Supplier	Silicon (Si)	7440-21-3		0.19	mg
Lead Frame	2.04	mg	В	Nickel (Ni)	7440-02-0		0.7813	mg
			Supplier	Iron (Fe)	7439-89-6		1.0792	mg
			Supplier	Copper (Cu)	7440-50-8		0.1795	mg
Mold Compound-Black	3.9	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.39	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0195	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		0.5655	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		2.535	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.39	mg
Plating	0.05	mg	Supplier	Tin (Sn)	7440-31-5		0.05	mg
Wire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg