© Copyrig	al Composition D ght 2005. IPC, Bannoc nal and Pan-American	kburn, Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declarat he declaration o	ion of the su	ibstances v s all lower	within the manufactu level materials for w	rer listed ite hich the m	em. Note: i anufacture	if the item is an as r has engineering	sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information			
upplier Information														
Company name* C			Company unique ID			Unique ID Authority				Response	Response Date*			
nsemi									2025-06-07					
Contact Name Title			Title - Contact			Phone - Contact*				Email - O	Email - Contact*			
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Authorized Representative* Ti			Title - Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards	Product Envi	Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com					
Requester Item Numb	Requester Item Number Mfr Iten		n Number Mfr Item Name			Effective Date	te Version Manufacturing Site		v	/eight*	UOM	Unit Type		
	NRVB	NRVBS360T3G RECTIFIER 3.0		A, 60 V SUR		2025-06-07	' VN		VN5		28.02	mg	Each	
Ianufacturing Proccess	Information									<u> </u>				
Terminal Plating / Grie	Terminal Plating / Grid Array Material Terminal Base		Alloy	J-STD-020 MS	Peak Proc	Peak Process Body Temperature Max Time at Peak			Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU		CU Alloy	y 1			260	60 C		30	second	s 3			
omments														
vel 1 - maximum time at peak	temperature during	oldering is 10-3	0 seconds											
or more information regarding	g material compositio	n please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et					
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted				
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature	astislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	1.34	mg	Supplier	Silicon (Si)	7440-21-3		1.34	mg	
Die Attach Solder	5.17	mg	Supplier	Silver (Ag)	7440-22-4		0.1293	mg	
			А	Lead (Pb)	7439-92-1	7a	4.7822	mg	
			Supplier	Tin (Sn)	7440-31-5		0.2585	mg	
Lead Frame	92.28	mg	Supplier	Zinc (Zn)	7440-66-6		0.0923	mg	
			Supplier	Iron (Fe)	7439-89-6		2.2147	mg	
			Supplier	Copper (Cu)	7440-50-8		89.973	mg	
Mold Compound-Black	126.72	mg	Supplier	Ortho Cresol Novolac Resin	29690-82-2		12.672	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.6336	mg	
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		18.3744	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		82.368	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		12.672	mg	
Plating	2.51	mg	Supplier	Tin (Sn)	7440-31-5		2.51	mg	