ABSOCIATION CONNECTING ELECTROMICS INDUSTRIES INDUSTRIES International and Pan-Am	Bannockbu	rn, Illinois. A	ll rights reserved untions.	under both	This docum level parts, t	ent is a declar he declaration	ation of th n encompa	e substances sses all lowe	within the mar	ufacturer s for whic	listed item. the manuf	Note: if t acturer h	he item is an as as engineering	sembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Ty http://www.ipc.org/IPC-175x Distribut				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					Materials	als and Mfg Information				
Supplier Information															
Company name* Company u			y unique ID			Unique ID Authority					Response Date*				
onsemi											2025-07-14				
Contact Name	ontact Name Title - Contact					Phone - Contact*					Email - Contact*				
Product-Env-Stewards Product Enviro Co			o Compliance			NA				I	Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Representative			sentative	e Ph			hone - Representative*			E	Email - Representative*				
Product-Env-Stewards Product Enviro			iro Compliance			NA				I	Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item Number		Mfr Item Name			Effective Da	te Versi	on	Manufacturing Site		Weig	ht*	UOM	Unit Type	
	NTB082N	TB082N65S3F SUPERFET3 650		V D2PAK PKO	G	2025-07-14			СРА		1485	098	mg	Each	
Manufacturing Proccess Information															
Terminal Plating / Grid Array Materia	g / Grid Array Material Terminal Base Alloy		Alloy	J-STD-020 MS	L Rating	Peak Pr	Process Body Temperature Max Time at Peak		at Peak Te	Temperature Number of Reflow Cycles		les			
Matte Tin (Sn) - annealed CU Alloy			1		245		С	30		seconds	3				
Comments															
level 1 - maximum time at peak temperature d	uring sold	lering is 10-3	0 seconds												
for more information regarding material com	position pl	lease refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et	
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 4 - Item(	s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).		
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the
Supplier Digital Signature	astislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	12.3	mg	Supplier	Silicon (Si)	7440-21-3		12.3	mg	
Die Attach Solder	7.33	mg	Supplier	Silver (Ag)	7440-22-4		0.1832	mg	
			А	Lead (Pb)	7439-92-1	7a	6.7803	mg	
			Supplier	Tin (Sn)	7440-31-5		0.3665	mg	
Lead Frame	860.318	mg	Supplier	Tin (Sn)	7440-31-5		1.0324	mg	
			В	Nickel (Ni)	7440-02-0		0.4302	mg	
			Supplier	Copper (Cu)	7440-50-8		858.8555	mg	
Mold Compound-Black	595.0	mg		Epoxy resin	proprietary data		35.7	mg	
			Supplier	Phenolic Resin	Proprietary Data		35.7	mg	
			Supplier	Carbon Black (C)	1333-86-4		2.975	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		505.75	mg	
			Supplier	Silica Crystalline (SiO2)	14808-60-7		14.875	mg	
Plating	5.52	mg	Supplier	Tin (Sn)	7440-31-5		5.52	mg	
Wire Bond - Al	4.63	mg	Supplier	Aluminum (Al)	7429-90-5		4.63	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).