	Material Comp © Copyright 2005. I international and Par	OSITION De PC, Bannockt n-American co	claration ourn, Illinois. <i>A</i> opyright conve	All rights reserved ntions.	under both	This docume level parts, t	ent is a declarat	ion of the encompa	e substance sses all low	s within the er level ma	e manufactur terials for wl	er listed it hich the m	em. Note: if anufacturer	f the item is an as has engineering	sembly with lowe responsibility.
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Ty				Form Type Distribute	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					eous Materia	als and Mfg Information			
Supplie	r Information														
Company name* Company unique I				ique ID	ID Unique I			nique ID Authority				Response Date*			
onsemi												2024-04-19			
Contact N	lame	Title - Contact				Phone - Contact*					Email - Contact*				
Product-l	Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
uthorize	ed Representative*	Title - Representative				Phone - Representative*				Email - Representative*					
Product-	Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com					
	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	Versi	on	Manufacturing Site		Ň	Veight*	UOM	Unit Type
		NTP110	NTP110N65S3HF SUPERFET3 650V TO220			nOhm,	2024-04-19	СРА			2	033.34	mg	Each	
Ianufa	cturing Proccess Informa	tion													
	Terminal Plating / Grid Array Ma	Ferminal Base Alloy J-STD-020 M		J-STD-020 MSI	L Rating	Peak Process Body Temperature		ire Max T	ime at Peak	Temperate	are Numb	er of Reflow Cyc	eles		
Matte Tin (Sn) - annealed			CU Alloy NA				0 C 30				seconds 3				
omments	3														
or more	information regarding material	composition	please refer to	o page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed			
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et				
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of			
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted			
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).					
Exemption List Version	EL-2011/534/EU							
Declaration Signature								
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.								
Supplier Digital Signature	astislav Drska	Le						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless	otherwise noted).							
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	7.1	mg	Supplier	Silicon (Si)	7440-21-3		7.1	mg
Die Attach Solder	4.93	mg	Supplier	Silver (Ag)	7440-22-4		0.1233	mg
			А	Lead (Pb)	7439-92-1	7a	4.5602	mg
			Supplier	Tin (Sn)	7440-31-5		0.2465	mg
Lead Frame	1492.12	mg	В	Nickel (Ni)	7440-02-0		1.0445	mg
			Supplier	Iron (Fe)	7439-89-6		1.4921	mg
			Supplier	Copper (Cu)	7440-50-8		1489.1357	mg
			Supplier	Phosphorus (P)	7723-14-0		0.4476	mg
Mold Compound-Black	513.45	mg		Epoxy resin	proprietary data		30.807	mg
			Supplier	Phenolic Resin	Proprietary Data		30.807	mg
			Supplier	Carbon Black (C)	1333-86-4		2.5673	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		436.4325	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		12.8363	mg
Plating	13.3	mg	Supplier	Tin (Sn)	7440-31-5		13.3	mg
Wire Bond - Al	2.44	mg	Supplier	Aluminum (Al)	7429-90-5		2.44	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).