ASSOCIATION CONNECTING LECTRONICS INDUSTRIES® INFORMATION CONNECTING	PC. Bannockl	burn. Illinois. A	Il rights reserved untions.	under both	This docume level parts, t	ent is a declara	tion of the s	substances es all lowe	within the er level mate	manufacture erials for wh	er listed iten ich the mar	n. Note: i iufacture	if the item is an as r has engineering	sembly with lower responsibility.
				Form Type Distribute	*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia					als and Mfg Information			
Supplier Information														
Company name* Cor			Company unique ID			Unique ID Authority					Response Date*			
onsemi								2025-07-14						
Contact Name Title - Contact			ct	Phone			none - Contact*				Email - Contact*			
Product-Env-Stewards Product H			duct Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title -			itle - Representative			Phone - Representative*				Email - Representative*				
Product-Env-Stewards Pr			Product Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Mfr Item Number		umber Mfr Item Name			Effective Da	e Versior	1	Manufacturing Site		We	eight*	UOM	Unit Type
	NTR410	NTR4101PT1H PFET SOT23 2		0V 3.2A 85MO		2025-07-14			CN1		8.1	3	mg	Each
Manufacturing Proccess Informa	tion							·			·			
Terminal Plating / Grid Array M	ray Material Terminal Base Alloy		Alloy	J-STD-020 MSI	-020 MSL Rating		Peak Process Body Temperature Max Time at P		ne at Peak T	ak Temperature Number of Reflow Cycles		les		
Matte Tin (Sn) - annealed CU Alloy		CU Alloy		1		260		С	30		seconds	3		
Comments														
evel 1 - maximum time at peak temperat	ire during so	ldering is 10-3	0 seconds											
or more information regarding material	composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth						
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	stislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg	
Lead Frame	2.92	mg	Supplier	Silver (Ag)	7440-22-4		0.5198	mg	
			В	Nickel (Ni)	7440-02-0		0.9023	mg	
			Supplier	Iron (Fe)	7439-89-6		1.2468	mg	
			Supplier	Copper (Cu)	7440-50-8		0.2511	mg	
Mold Compound-Black	4.9	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.147	mg	
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0245	mg	
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.147	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.92	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.049	mg	
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.392	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.2205	mg	
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg	
Wire Bond - Cu	0.01	mg	Supplier	Copper (Cu)	7440-50-8		0.01	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).