© Co	terial Composition pyright 2005. IPC, Banational and Pan-Ame	annockbu	urn, Illinois. A	ll rights reserved untions.	nder both	This docum level parts, t	ent is a declara he declaration	tion of the s encompass	substances es all lowe	within the manufact or level materials for	urer listed which the	item. Note: i manufacturer	f the item is an as r has engineering	ssembly with lower responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				e*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Information															
Company name*			Company unique ID				Unique ID Authority					Response Date*			
onsemi											2025-0	2025-08-01			
Contact Name			Title - Contact				Phone - Contact*				Email	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative				Phone - Representative*			Email	Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item I	Requester Item Number Mfr Item		m Number Mfr Item Name				Effective Dat	e Versior	1	Manufacturing Site		Weight*	UOM	Unit Type	
	Ν	NTR4503NT1G N		NFET SOT23 30V 2.5A 140MO)	2025-08-01			CN1		8.13	mg	Each	
Manufacturing Proce	ess Information														
Terminal Plating / Grid Array Material Terminal			erminal Base A	Base Alloy J-STD-020 MSL Rating			Peak Process Body Temperature Max Time at Peak				k Temper	Temperature Number of Reflow Cycles			
Matte Tin (Sn) - annealed CU Al			U Alloy	1			260 C		С	30 se		onds 3			
Comments															
evel 1 - maximum time at j	peak temperature du	ring sold	lering is 10-3	0 seconds											
For more information rega	rding material comp	osition p	lease refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth					
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and co for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	on above	Supplier Acceptance	* Accepted					
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.									
Supplier Digital Signature Ra	stislav Drska	Le							

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	0.16	mg	Supplier	Silicon (Si)	7440-21-3		0.16	mg	
Lead Frame	2.92	mg	Supplier	Silver (Ag)	7440-22-4		0.5198	mg	
			В	Nickel (Ni)	7440-02-0		0.9023	mg	
			Supplier	Iron (Fe)	7439-89-6		1.2468	mg	
			Supplier	Copper (Cu)	7440-50-8		0.2511	mg	
Mold Compound-Black	4.9	mg	Supplier	Boron zinc hydroxide oxide	138265-88-0		0.147	mg	
			Supplier	Zinc Monoxide (ZnO)	1314-13-2		0.0245	mg	
			Supplier	2,4,6-triamino-s-triazincompd.withs- triazine-triol	37640-57-6		0.147	mg	
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.92	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.049	mg	
			Supplier	Ortho-Cresol Novolac Resin	29690-82-2		0.392	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.2205	mg	
Plating	0.14	mg	Supplier	Tin (Sn)	7440-31-5		0.14	mg	
Wire Bond - Cu	0.01	mg	Supplier	Copper (Cu)	7440-50-8		0.01	mg	

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted).