ASDCIATION CONNECTING ELECTROMICS INDUSTRIES International and P	IPC, Bannock	burn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declaration e	ion of the su	ubstances s all lower	within the manufactur level materials for w	er listed ite hich the ma	m. Note: if nufacturer	f the item is an as has engineering	sembly with low responsibility.
				Form Type Distribute	*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				als and Mfg Information			
Supplier Information													
Company name* Company			any unique ID			Unique ID Authority				Response Date*			
onsemi										2024-04-16			
Contact Name	ntact Name Title - Contact				Phone - Contact*					Email - Contact*			
Product-Env-Stewards Product Enviro			iro Compliance			NA				Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Representative			ntative P			Phone - Representative*			Email - Representative*				
Product-Env-Stewards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester Item Number	Requester Item Number Mfr Item		n Number Mfr Item Name			Effective Date	fective Date Version Manufacturing Site		Ianufacturing Site	W	eight*	UOM	Unit Type
	NVMFS 1G	NVMFS5C604NLAFT T6 60V HEFET 1G				2024-04-16		N	MY1		5.95	mg	Each
Aanufacturing Proccess Inform	ation												
Terminal Plating / Grid Array M	Iaterial 7	al Terminal Base Alloy		J-STD-020 MS	L Rating	Peak Proc	ocess Body Temperature Max Time at Peak		Temperatu	e Numb	er of Reflow Cyc	les	
Matte Tin (Sn) - annealed CU Alloy		CU Alloy		1		260		С	30	second	3		
omments													
vel 1 - maximum time at peak tempera	ture during so	dering is 10-3	0 seconds										
or more information regarding materia	l composition	please refer to	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et					
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 4 - Item(	s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted				
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the				
Supplier Digital Signature	astislav Drska	Le							

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless otherwise noted).								
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	4.8	mg	Supplier	Iron (Fe)	7439-89-6		0.0048	mg
			Supplier	Copper (Cu)	7440-50-8		4.7938	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0014	mg
Die	0.61	mg	Supplier	Silicon (Si)	7440-21-3		0.61	mg
Die Attach Solder	1.99	mg	Supplier	Silver (Ag)	7440-22-4		0.0498	mg
			А	Lead (Pb)	7439-92-1	7a	1.8407	mg
			Supplier	Tin (Sn)	7440-31-5		0.0995	mg
Lead Frame	47.6	mg	Supplier	Silver (Ag)	7440-22-4		0.0286	mg
			Supplier	Iron (Fe)	7439-89-6		0.0476	mg
			Supplier	Copper (Cu)	7440-50-8		47.5096	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0143	mg
Mold Compound-Black	49.2	mg		Epoxy resin	proprietary data		3.69	mg
			Supplier	Phenolic Resin	Proprietary Data		1.23	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		3.69	mg
			Supplier	Carbon Black (C)	1333-86-4		0.246	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		40.344	mg
Plating	1.7	mg	Supplier	Tin (Sn)	7440-31-5		1.7	mg
Wire Bond - Cu	0.05	mg	Supplier	Copper (Cu)	7440-50-8		0.05	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).