IPC ASSOCIATION ELECTRONIC	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.							sembly with lower responsibility.		
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Typ http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi				rials and M	ials and Mfg Information					
Supplie	r Information														
Company name*			Company unique ID			τ	Unique ID Authority				Respons	Response Date*			
nsemi											2024-04	2024-04-25			
Contact N	ame		Title - Contact			]	Phone - Contact*				Email - Contact*				
Product-l	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	d Representative*		Title - Representative			I	Phone - Representative*				Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number Mfr Item		Number Mfr Item Name				Effective Da	Oate Version Manufacturing Site			Weight*	UOM	Unit Type		
		NVMFSC0D9N04C 40V		40V T6 SL in 5x6 Dualcool			2024-04-25		1	PBB		121.5064	mg	Each	
<b>Aanufa</b>	cturing Process Inform	ation													
	Terminal Plating / Grid Array Material Terminal Base Alloy			Alloy J-S	STD-020 MS	0-020 MSL Rating Peak Process Body Temperature Max Time at Po				re Max Time at Peal	k Tempera	ure Numb	er of Reflow Cyc	eles	
Matte Tin (Sn) - annealed CU Alloy			CU Alloy	1			260		С	30	secon	ds 3			
Comments															
evel 1 - m	aximum time at peak tempera	ture during sol	dering is 10-3	30 seconds											
or more	information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledges that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its paragraph. If the Company and the Supplier supplier have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusivesource of the Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.										
RoHS Declaration * 4 - Item(s	) does not contain RoHS restricted substance	s per the definition above except for selected exemp	tions Supplier Acceptance	* Accepted						
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.										
Supplier Digital Signature Ra	astislav Drska	-En								

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

<b>Homogeneous Material</b>	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	19.1	mg	Supplier	Zinc (Zn)	7440-66-6		0.0229	mg
			Supplier	Iron (Fe)	7439-89-6		0.4489	mg
			Supplier	Copper (Cu)	7440-50-8		18.6225	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0057	mg
Die	2.54	mg	Supplier	Silicon (Si)	7440-21-3		2.54	mg
Die Attach Solder	3.021	mg	Supplier	Silver (Ag)	7440-22-4		0.0755	mg
			A	Lead (Pb)	7439-92-1	7a	2.7944	mg
			Supplier	Tin (Sn)	7440-31-5		0.151	mg
Lead Frame	45.8	mg	Supplier	Silver (Ag)	7440-22-4		0.1374	mg
			Supplier	Zinc (Zn)	7440-66-6		0.055	mg
			Supplier	Iron (Fe)	7439-89-6		1.0763	mg
			Supplier	Copper (Cu)	7440-50-8		44.5176	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0137	mg
Mold Compound-Black	42.715	mg	Supplier	Trimethoxysilylpropanethiol	4420-74-0		0.2136	mg
			Supplier	Boron zinc hydroxide oxide	138265-88-0		6.4073	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		6.4073	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1068	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		27.2308	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		2.3493	mg
Plating	8.33	mg	Supplier	Tin (Sn)	7440-31-5		8.33	mg
Wire Bond	4.0E-4	mg	Supplier	Palladium (Pd)	7440-05-3		0	mg
			Supplier	Copper (Cu)	7440-50-8		0.0004	mg