© Copyrigi	l Composition De ht 2005. IPC, Bannock al and Pan-American d	burn, Illinois. A	ll rights reserved untions.	under both	This docume level parts, t	ent is a declarati he declaration e	on of the su	ibstances v s all lower	within the manufactu level materials for w	rer listed i which the r	tem. Note: i nanufacturer	f the item is an as r has engineering	sembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				*	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materia					als and Mfg Information			
upplier Information														
Company name* Compa			npany unique ID			Unique ID Authority				Respon	Response Date*			
onsemi										2024-04	2024-04-17			
Contact Name Title - Con			Contact			Phone - Contact*				Email -	Email - Contact*			
Product-Env-Stewards Product En			Enviro Compliance			NA				Product-Env-Stewards@onsemi.com				
Authorized Representative* Title - Rep			presentative			Phone - Representative*			Email - Representative*					
Product-Env-Stewards Product			duct Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com			
Requester Item Number	Number Mfr Item Number		nber Mfr Item Name			Effective Date	Version	ersion Manufacturing Site			Weight*	UOM	Unit Type	
	SS16H	3	60V 1A Schottky Rectif			2024-04-17		Т	TSCBE		6.000001	mg	Each	
Janufacturing Proccess In	nformation						-							
Terminal Plating / Grid	Terminal Plating / Grid Array Material Terminal Base .		Alloy	J-STD-020 MSL Rating		Peak Process Body Temperature Max Time at		e Max Time at Peak	ak Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU		CU Alloy	1			260 C		30	seconds 3					
omments														
vel 1 - maximum time at peak t	emperature during s	oldering is 10-3	0 seconds											
or more information regarding	material composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP), Dibutyl phthalate (DBP).									
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of					
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted					
Exemption: 7a: Lead in high melting temperature type solders (i.e. lead based solder alloys containing 85% by weight or more lead).										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
Instructions: Complete all of the required Requester) and click on Submit Form to h			e drop-dowi	a. This will display the signature area. Digita	lly sign the declaration (if required by the					
Supplier Digital Signature	astislav Drska	Le								

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Clip	0.22002	mg	В	Nickel (Ni)	7440-02-0		0.0001	mg
			Supplier	Copper (Cu)	7440-50-8		0.2199	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0001	mg
Die	0.67998	mg	Supplier	Titanium (Ti)	7440-32-6		0.001	mg
			Supplier	Silver (Ag)	7440-22-4		0.0253	mg
			Supplier	Silicon (Si)	7440-21-3		0.6474	mg
			В	Nickel (Ni)	7440-02-0		0.0063	mg
Die Attach Solder	0.250021	mg	Supplier	Silver (Ag)	7440-22-4		0.0063	mg
			А	Lead (Pb)	7439-92-1	7a	0.2313	mg
			Supplier	Tin (Sn)	7440-31-5		0.0125	mg
Lead Frame	1.39002	mg	Supplier	Iron (Fe)	7439-89-6		0.0014	mg
			Supplier	Copper (Cu)	7440-50-8		1.3882	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0004	mg
Mold Compound-Black	3.25998	mg		Metal Hydroxide	proprietary data		0.1141	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.2608	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0163	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		2.608	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.2608	mg
Plating	0.19998	mg	Supplier	Tin (Sn)	7440-31-5		0.2	mg