ASSOCIATION CONNECTING ELECTRONICS INDUSTRES® international and Pa	IPC, Bannockl	burn, Illinois. A	Il rights reserved untions.	under both	This docum level parts, t	ent is a declara the declaration	tion of the s encompasse	ubstances es all lowe	within the manufact r level materials for	turer listed which the	item. Note: manufacture	if the item is an a er has engineering	ssembly with low responsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Distril								erials and I	als and Mfg Information				
Supplier Information														
Company name* Con			Company unique ID			Unique ID Authority				Respo	Response Date*			
onsemi											2025-06-07			
Contact Name Title - Contact			ct	F			Phone - Contact*				Email - Contact*			
Product-Env-Stewards Product Env			nviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Repr			esentative			Phone - Representative*			Email	Email - Representative*				
Product-Env-Stewards Prod			Product Enviro Compliance			NA				Produ	Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Iten		n Number Mfr Item Name				Effective Dat	e Version]	Manufacturing Site		Weight*	UOM	Unit Type	
	SSA210	SSA210 2A 100V S		SCHOTTKY RECT		2025-06-07	25-06-07 PANJITFG		PANJITFG		64.016	mg	Each	
Aanufacturing Proccess Inform	ation													
Terminal Plating / Grid Array M	ninal Plating / Grid Array Material Terminal Base .		Alloy	J-STD-020 MSL Rating		Peak Process Body Temperature Max Tim		re Max Time at Pea	Peak Temperature Number of Reflow Cycles					
Matte Tin (Sn) - annealed CU Alloy		CU Alloy		1		260		С	30	seco	onds 3			
omments														
vel 1 - maximum time at peak temperat	ture during so	Idering is 10-3	0 seconds											
or more information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed			
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		mium (Cr6+), Polybrominated Biphenyls (Pl		dmium and quantity limit of 0.1% by mass (10 minated Diphenyl Ethers (PBDE), and Bis(2-et				
cadmium, hexavalentchromium, polybromina contains a RoHS restricted substance inexces encompass all such components. Supplier cer as of the date that Supplier completes this for Company acknowledges that Supplier may h independently verified information provided certification in this paragraph. If the Company	ated biphenyls and/or polybrominated dip s of an applicable quantity limit, please in iffies that it gathered the information it pr m.Supplier acknowledges that Company ave relied on informationprovided by oth by others, Supplier agrees that, at a minir and the Supplier enter into a written agr esource of the Supplier's liability and the	henyl ethers (each a "RoHS restricted substa ndicate below which, if any, RoHS exemption ovides in this form using appropriate methoo will rely on this certification in determining ers in completing this form, and that Supplie num, itssuppliers have provided certification eement with respect to the identified part, the Company's remedies for issues that arise reg	nce") in exco n you believe ls to ensure i the compliar r may not ha s regarding t terms and co	e may apply. If the part is an assembly with low s accuracy and that such information is true an ce of its products with European Union member de independently verified such information. Ho neir contributions to the part, and those certifica	ove. If a homogeneous material within the part er level components, the declaration shall d correct to the best of its knowledge and belief, er state laws that implement the RoHS Directive. wever, in situations where Supplier has not ations are at least as comprehensive as the anty rights and/or remedies provided as part of			
RoHS Declaration * 4 - Item(s) does not contain RoHS restricted subst	ances per the definition above except for sele	ected exempt	ions Supplier Acceptance	* Accepted			
Exemption: 7a: Lead in high melting temp	erature type solders (i.e. lead based sol	der alloys containing 85% by weight or m	ore lead).					
Exemption List Version	EL-2011/534/EU							
Declaration Signature								
Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.								
Supplier Digital Signature	astislav Drska	Le						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3

sigma range of distribution unless otherwise noted).									
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure	
Die	1.28	mg	Supplier	Silicon (Si)	7440-21-3		1.28	mg	
Die Attach Solder	2.098	mg	Supplier	Silver (Ag)	7440-22-4		0.0525	mg	
			А	Lead (Pb)	7439-92-1	7a	1.9407	mg	
			Supplier	Tin (Sn)	7440-31-5		0.1049	mg	
Lead Frame	18.636	mg	Supplier	Iron (Fe)	7439-89-6		0.024	mg	
			Supplier	Copper (Cu)	7440-50-8		18.6	mg	
			Supplier	Phosphorus (P)	7723-14-0		0.012	mg	
Mold Compound-Black	41.002	mg		Metal Hydroxide	proprietary data		1.4351	mg	
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		3.2802	mg	
			Supplier	Carbon Black (C)	1333-86-4		0.205	mg	
			Supplier	Fused Silica (SiO2)	60676-86-0		32.8016	mg	
			Supplier	Phenolic Resin (Novolac)	9003-35-4		3.2802	mg	
Plating	1.0	mg	Supplier	Tin (Sn)	7440-31-5		1	mg	