

		<b>Material Composition Declaration</b> © Copyright 2005, IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.					
1752-21.1		IPC Web Site for Information on IPC-1752 Standard <a href="http://www.ipc.org/IPC-175x">http://www.ipc.org/IPC-175x</a>		Form Type * Distribute		Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information				
<b>Supplier Information</b>										
Company name* onsemi			Company unique ID		Unique ID Authority			Response Date* 2024-04-20		
Contact Name Product-Env-Stewards			Title - Contact Product Enviro Compliance		Phone - Contact* NA			Email - Contact* Product-Env-Stewards@onsemi.com		
Authorized Representative* Product-Env-Stewards			Title - Representative Product Enviro Compliance		Phone - Representative* NA			Email - Representative* Product-Env-Stewards@onsemi.com		
	Requester Item Number	Mfr Item Number	Mfr Item Name		Effective Date	Version	Manufacturing Site	Weight*	UOM	Unit Type
		STK5C4U332J-E	3phase inverter HIC		2024-04-20		VN2	4800.0	mg	Each
<b>Manufacturing Process Information</b>										
	Terminal Plating / Grid Array Material	Terminal Base Alloy	J-STD-020 MSL Rating		Peak Process Body Temperature		Max Time at Peak Temperature		Number of Reflow Cycles	
	Matte Tin (Sn) - annealed	CU Alloy	NA		0	C	30	seconds	3	
Comments										
For more information regarding material composition please refer to page 3										

RoHS Material Composition Declaration		Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).		
<p>Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a “RoHS restricted substance”) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier’s liability and the Company’s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier’s Standard Terms and Conditions of Sale applicable to such part shall apply.</p>			
RoHS Declaration *	4 - Item(s) does not contain RoHS restricted substances per the definition above except for selected exemptions		Supplier Acceptance * Accepted
<b>Exemption: 7c-I Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound.</b>			
Exemption List Version	EL-2011/534/EU		
Declaration Signature			
<b>Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.</b>			
Supplier Digital Signature	Rastislav Drska		

**Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Ceramic Substrate	1230.07	mg	Supplier	Bisphenol A_Epichlorohydrin Polymer	25068-38-6		15.3759	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		60.6424	mg
			B	Nickel (Ni)	7440-02-0		2.0911	mg
			Supplier	Acrylic resins	Proprietary Data		0.861	mg
			Supplier	Copper (Cu)	7440-50-8		82.6607	mg
			Supplier	Barium Sulfate (BaSO4)	7727-43-7		0.615	mg
			Supplier	Aluminum (Al)	7429-90-5		1067.8237	mg
Chip Parts	14.02	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		1.2842	mg
			Supplier	Silver (Ag)	7440-22-4		0.4627	mg
			Supplier	Epoxy resins	129915-35-1		0.1781	mg
			Supplier	Bisphenol A, Epichlorohydrin polymer	25036-25-3, 25068-38-6		0.0084	mg
			Supplier	Tin (Sn)	7440-31-5		0.4767	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.2748	mg
			Supplier	Ceramic	12013-47-7, 12047-27-7		5.0584	mg
			Supplier	Palladium (Pd)	7440-05-3		0.0196	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		3.5709	mg
			B	Nickel (Ni)	7440-02-0		1.7665	mg
			A	Lead Oxide (PbO)	1317-36-8	7c	0.0252	mg
			Supplier	Chromium Trioxide (Cr2O3)	1308-38-9		0.0014	mg
			Supplier	Copper (Cu)	7440-50-8		0.8931	mg
Die	11.21	mg	Supplier	Silicon (Si)	7440-21-3		11.21	mg
Lead Frame	465.65	mg	Supplier	Tin (Sn)	7440-31-5		0.2794	mg
			Supplier	Copper (Cu)	7440-50-8		465.3706	mg
Mold Compound-Black	3071.21	mg		Phenolic Resin	proprietary data		184.2726	mg
			Supplier	Epoxy Phenol Resin	Proprietary Data		307.121	mg
			Supplier	Carbon Black (C)	1333-86-4		15.356	mg
			Supplier	Aluminum Hydroxide (Al(OH)3)	21645-51-2		168.9165	mg
			Supplier	Silica Crystalline (SiO2)	14808-60-7		2395.5437	mg
Plating	1.2	mg	Supplier	Tin (Sn)	7440-31-5		0.7429	mg
			B	Nickel (Ni)	7440-02-0		0.4571	mg

Solder Ball	3.59	mg	Supplier	Silver (Ag)	7440-22-4		0.1002	mg
			Supplier	Tin (Sn)	7440-31-5		3.4694	mg
			B	Antimony (Sb)	7440-36-0		0.0029	mg
			Supplier	Copper (Cu)	7440-50-8		0.0176	mg
Wire Bond	3.05	mg	Supplier	Silicon (Si)	7440-21-3		0.0043	mg
			Supplier	Aluminum (Al)	7429-90-5		3.0457	mg