

## Product Overview

### MC74ACT14: Hex Inverter with Schmitt Trigger Input

For complete documentation, see the data sheet.

The MC74AC14/74ACT14 contains six logic inverters which accept standard CMOS Input signals (TTL levels for MC74ACT14) and provide standard CMOS output levels. They are capable of transforming slowly changing input signals into sharply defined, jitter-free output signals. In addition, they have a greater noise margin than conventional inverters.

The MC74AC14/74ACT14 has hysteresis between the positive-going and negative-going input thresholds (typically 1.0 V) which is determined internally by transistor ratios and is essentially insensitive to temperature and supply voltage variations.

### Features

- Schmitt Trigger Inputs
- Outputs Source/Sink 24 mA
- ACT14 Has TTL Compatible Inputs
- Pb-Free Packages are Available

### Part Electrical Specifications

Product	Compliance	Status	Channels	Output	V <sub>CC</sub> Min (V)	V <sub>CC</sub> Max (V)	t <sub>pd</sub> Max (ns)	I <sub>O</sub> Max (mA)	Package Type
MC74ACT14DG	Pb-free	Active	6	CMOS	2	5.5	11.5	24	SOIC-14
	Halide free								
MC74ACT14DR2G	Pb-free	Active	6	CMOS	2	5.5	11.5	24	SOIC-14
	Halide free								
MC74ACT14DTR2G	Pb-free	Active	6	CMOS	2	5.5	11.5	24	TSSOP-14
	Halide free								

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com).

Created on: 4/19/2019