

## Product Overview

### MC74ACT253: Dual 4-Input Multiplexer with 3-State Outputs

For complete documentation, see the data sheet.

The MC74ACT253/74ACT253 is a dual 4-input multiplexer with 3-state outputs. It can select two bits of data from four sources using common select inputs. The outputs may be individually switched to a high impedance state with a HIGH on the respective Output Enable (OE) inputs, allowing the outputs to interface directly with bus oriented systems.

### Features

- Multifunctional Capability
- Noninverting 3-State Outputs
- Outputs Source/Sink 24 mA
- ACT253 Has TTL Compatible Inputs
- These devices are available in Pb-free package(s). Specifications herein apply to both standard and Pb-free devices. Please see our website at [www.onsemi.com](http://www.onsemi.com) for specific Pb-free orderable part numbers, or contact your local ON Semiconductor sales office or representative.

### Part Electrical Specifications

Product	Compliance	Status	Channels	V <sub>CC</sub> Min (V)	V <sub>CC</sub> Max (V)	t <sub>pd</sub> Max (ns)	I <sub>O</sub> Max (mA)	Package Type
MC74ACT253DG	Pb-free	Active	2	4.5	5.5	13	null	SOIC-16
	Halide free							
MC74ACT253DR2G	Pb-free	Active	2	4.5	5.5	13	24	SOIC-16
	Halide free							

For more information please contact your local sales support at [www.onsemi.com](http://www.onsemi.com).

Created on: 4/19/2019