



Product Overview

NBXSBA025: Clock Oscillator Module, PureEdge™, 425 MHz LVPECL, 2.5 V / 3.3 V

For complete documentation, see the [data sheet](#)

Product Description

The NBXSBA025, single frequency, crystal oscillator (XO) is designed to meet today's requirements for 2.5 V / 3.3 V LVPECL clock generation applications. The device uses a high Q fundamental crystal and Phase Lock Loop (PLL) multiplier to provide 425.00 MHz, ultra low jitter and phase noise LVPECL differential output. This device is a member of ON Semiconductor's PureEdge™ clock family that provides accurate and precision clock solutions. Available in 5 mm x 7 mm SMD (CLCC) package on 16 mm tape and reel in quantities of 1,000 and 100.

Features

- LVPECL Differential Output
- Uses High Q Fundamental Mode Crystal and PLL Multiplier
- Ultra Low Jitter and Phase Noise 0.5 ps (12 kHz to 20 MHz)
- Output Frequency 425.00 MHz
- Operating Range: 2.5 V +/-5% or 3.3 V +/-10%
- Total Frequency Stability +/-50 PPM
- This is a PbFree Device

Applications

- 4x Fiber Channel
- Host Bus Adapter

For more information please contact your local sales support at www.onsemi.com

Created on: 7/11/2015