# onsemi

# TinyLogic<sup>®</sup> Low Power Configurable Gate with Voltage-Level Translator

# 74AUP1T97

#### Description

The 74AUP1T97 is a universal configurable 2–input logic gate that provides single supply voltage level translation. This device is designed for applications with inputs switching levels that accept 1.8 V low voltage CMOS signals while operating from either a single 2.5 V or 3.3 V supply voltage. The 74AUP1T97 is an ideal low power solution for mixed voltage signal applications especially for battery–powered portable applications. This product guarantees very low static and dynamic power consumption across entire voltage range. All inputs are implemented with hysteresis to allow for slower transition input signals and better switching noise immunity.

The 74AUP1T97 provides for multiple functions as determined by various configurations of the three inputs. The potential logic functions provided are MUX, AND, NAND, OR, and NOR, inverter and buffer. Refer to Figures 3 to 9.

#### Features

- Single Supply Voltage Translator
  - 1.8 V to 3.3 V Input at  $V_{CC} = 3.3$  V
  - 1.8 V to 2.5 V Input at  $V_{CC} = 2.5$  V
- 2.3 V to 3.6 V V<sub>CC</sub> Supply Voltage Operation
- 3.6 V Over–Voltage Tolerant I/O's at V<sub>CC</sub> from 2.3 V to 3.6 V
- Power-Off High-Impedance Inputs and Outputs
- Low Static Power Consumption
  - $I_{CC} = 0.9 \ \mu A \ Maximum$
- Low Dynamic Power Consumption
  - C<sub>PD</sub> = 2.7 pF Typical at 3.3 V
- Ultra-Small MicroPak<sup>TM</sup> Packages

#### Logic Diagram



Figure 1. Logic Diagram (Positive Logic)



CASE 517DP



SIP6 CASE 127EB

#### MARKING DIAGRAM



#### **ORDERING INFORMATION**

Device	Package	Shipping <sup>†</sup>
74AUP1T97FHX	UDFN-6 (Pb-Free/Halide Free)	5000 / Tape & Reel
74AUP1T97L6X	SIP-6 (Pb-Free/Halide Free)	5000 / Tape & Reel

+For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, <u>BRD8011/D</u>.

# **PIN CONFIGURATIONS**

#### Table 1. PIN DESCRIPTIONS

Pin	Name	Description
1	В	Data Input
2	GND	Ground
3	А	Data Input
4	Y	Output
5	V <sub>CC</sub>	Supply Voltage
6	С	Data Input



Figure 2. MicroPak<sup>™</sup> (Top View)

#### **Table 2. FUNCTION TABLE**

	Inputs		Output
С	В	Α	Y
L	L	L	L
L	L	Н	L
L	Н	L	н
L	н	Н	Н
Н	L	L	L
Н	L	Н	Н
Н	Н	L	L
Н	Н	Н	Н

H = HIGH Logic Level
 L = LOW Logic Level

### Table 3. FUNCTION SELECTION TABLE

Logic Function	Connection Configuration
2-to-1 MUX	Figure 3
2–Input AND Gate	Figure 4
2-Input OR Gate with One Inverted Input	Figure 5
2-Input NAND Gate with One Inverted Input	Figure 5
2-Input AND Gate with One Inverted Input	Figure 6
2-Input NOR Gate with One Inverted Input	Figure 6
2-Input OR Gate	Figure 7
Inverter	Figure 8
Buffer	Figure 9

#### Logic Configurations

Figure 3 through Figure 9 show the logical functions that can be implemented using the 74AUP1T97. The diagrams show the DeMorgan's equivalent logic duals for a given



Note: 1. When C is L, Y = B. 2. When C is H, Y = A.

1





Figure 5. Input OR Gate with One Inverted Input 2–Input NAND Gate with One Inverted Input



Figure 7. 2-Input OR Gate

two-input function. The logical implementation is next to the board-level physical implementation of how the pins of the function should be connected.







Figure 6. 2–Input AND Gate with One Inverted Input 2–Input NOR Gate with One Inverted Input



Figure 8. Inverter



Figure 9. Buffer

#### **ABSOLUTE MAXIMUM RATINGS**

Symbol		Parameter	Min.	Max.	Unit
V <sub>CC</sub>	Supply Voltage		-0.5	4.6	V
V <sub>IN</sub>	DC Input Voltage		-0.5	4.6	V
V <sub>OUT</sub>	DC Output Voltage HIGH V <sub>CC</sub>	H or LOW State(Note 3) = 0 V	-0.5 -0.5	V <sub>CC</sub> + 0.5 4.6	V
I <sub>IK</sub>	DC Input Diode Current VIN <	< 0 V	-	-50	mA
I <sub>OK</sub>	DC Output Diode Current V <sub>OU</sub> - V <sub>OU</sub> -	T < 0 V T > V <sub>CC</sub>	-	-50 +50	mA
I <sub>OH</sub> / I <sub>OL</sub>	DC Output Source / Sink Current		-	±50	mA
IO	Continuous Output Current		-	±20	mA
I <sub>CC</sub> or I <sub>GND</sub>	DC $V_{CC}$ or Ground Current per Sup	oply Pin	-	±50	mA
T <sub>STG</sub>	Storage Temperature Range		-65	+150	°C
TJ	Junction Temperature Under Bias		-	+150	°C
TL	Junction Lead Temperature, Solder	ing 10s	-	+260	°C
P <sub>D</sub>	Power Dissipation at +85°C Micro Micro	oPak–6 oPak2–6	-	130 120	mW
ESD	Human Body Model, JEDEC:JESD Charged Device Model, JEDEC:JE	22-A114 SD22-C101	-	5000+ 2000	V

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.
I<sub>O</sub> absolute maximum rating must be observed.

#### Table 4. RECOMMENDED OPERATING CONDITIONS (Note 4)

Symbol	Parameter	Conditions	Min	Мах	Unit
V <sub>CC</sub>	Supply Voltage		2.3	3.6	V
V <sub>IN</sub>	Input Voltage		0	3.6	V
V <sub>OUT</sub>	Output Voltage	V <sub>CC</sub> = 0 V HIGH or LOW State	0 0	3.6 V <sub>CC</sub>	V
I <sub>OH</sub> / I <sub>OL</sub>	Output Current	$V_{CC} = 3.0 \text{ V to } 3.6 \text{ V}$ $V_{CC} = 2.3 \text{ V to } 2.7 \text{ V}$	-	±4.0 ±3.1	mA
T <sub>A</sub>	Operating Free-Air Temperature		-40	+85	°C
$\theta_{JA}$	Thermal Resistance	MicroPak-6 MicroPak2-6	-	500 560	°C/W

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability. 4. Unused inputs must be held HIGH or LOW. They may not float.

## Table 5. DC ELECTRICAL CHARACTERISTICS

				T <sub>A</sub> = +	25°C	T <sub>A</sub> = -40°C	C to +85°C	
Symbol	Parameter	Conditions	V <sub>CC</sub> (V)	Min	Max	Min	Max	Unit
VP	Positive Threshold	-	2.3 V to 2.7 V	0.60	1.10	0.60	1.10	V
	Voltage		3.0 V to 3.6 V	0.75	1.16	0.75	1.19	V
V <sub>N</sub>	Negative Threshold	-	2.3 V to 2.7 V	0.35	0.60	0.35	0.60	V
	voitage		3.0 V to 3.6 V	0.50	0.85	0.50	0.85	V
V <sub>H</sub>	Hysteresis Voltage	-	2.3 V to 2.7 V	0.23	0.60	0.10	0.60	V
			3.0 V to 3.6 V	0.25	0.56	0.15	0.56	V
V <sub>OH</sub>	HIGH Level Output	I <sub>OH</sub> = -20 μA	$2.3~V \leq V_{CC} \leq 3.6~V$	V <sub>CC</sub> -0.1	-	V <sub>CC</sub> -0.1	-	V
	voitage	I <sub>OH</sub> = -2.3 mA	2.3 V	2.05	-	1.97	-	V
		I <sub>OH</sub> = -3.1 mA		1.90	-	1.85	-	V
		I <sub>OH</sub> = -2.7 mA	3.0 V	2.72	-	2.67	-	V
		I <sub>OH</sub> = -4 mA		2.60	-	2.55	-	V
V <sub>OL</sub>	LOW Level Output	I <sub>OL</sub> = 20 μA	$2.3~V \leq V_{CC} \leq 3.6~V$	-	0.10	-	0.10	V
	Voltage	I <sub>OL</sub> = 2.3 mA	2.3 V	-	0.31	-	0.33	V
		I <sub>OH</sub> = 3.1 mA		_	0.44	-	0.45	V
		I <sub>OL</sub> = 2.7 mA	3.0 V	-	0.31	-	0.33	V
		I <sub>OL</sub> = 4.0 mA		-	0.44	-	0.45	V
I <sub>IN</sub>	Input Leakage Current	$0 \le V_{IN} \le 3.6$	0 V to 3.6 V	-	±0.10	-	±0.50	μΑ
I <sub>OFF</sub>	Power Off Leakage Current	$0 \leq (V_{IN},V_O) \leq 3.6$	0 V	-	0.10	-	0.50	μΑ
$\Delta I_{OFF}$	Additional Power Off Leakage Current	$V_{IN}$ or $V_{O} = 0$ V to 3.6 V	0 V to 0.2 V	-	0.20	-	0.60	μΑ
I <sub>CC</sub>	Quiescent Supply	$V_{IN} = V_{CC}$ or GND	2.3 V to 3.6 V	-	0.50	-	0.90	μA
	Current	$V_{CC} \leq V_{IN} \leq 3.6 \ V$		_	-	-	±0.90	μA
ΔI <sub>CC</sub>	Increase in I <sub>CC</sub> per Input	One Input at 0.3 V or 1.1 V, other Inputs at 0 or $V_{CC}$	2.3 V to 2.7 V	-	-	-	4	μΑ
		One Input at 0.45 V or 1.2 V, other Inputs at 0 or $V_{CC}$	3.0 V to 3.6 V	-	_	-	12	μΑ

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

#### Table 6. AC ELECTRICAL CHARACTERISTICS

				т	A = +25°	C	T <sub>A</sub> = - +85	-40 to 5°C		
Symbol	Parameter	Conditions	V <sub>CC</sub> (V)	Min	Тур	Max	Тур	Max	Unit	Figure
t <sub>PHL</sub> , t <sub>PLH</sub>	Propagation Delay	$C_L = 5 \text{ pF},$ $R_L = 1 \text{ M}\Omega$	$\begin{array}{l} 2.30 \ V \leq V_{CC} \leq 2.70 \ V, \\ V_{IN} = 1.65 \ V \ to \ 1.95 \ V \end{array}$	1.1	3.7	5.5	1.1	6.8	ns	Figure 10 &
			$\begin{array}{l} 2.30 \ V \leq VCC \leq 2.70 \ V \\ V_{IN} = 2.30 \ V \ to \ 2.70 \ V \end{array}$	1.1	3.8	6.5	1.1	7.0		11
			$\begin{array}{l} 2.30 \ V \leq V_{CC} \leq 2.70 \ V, \\ V_{IN} = 3.0 \ V \ to \ 3.60 \ V \end{array}$	1.1	3.9	6.0	1.1	6.5		
			$\begin{array}{l} 3.00 \ V \leq V_{CC} \leq 3.60 \ V, \\ V_{IN} = 1.65 \ V \ to \ 1.95 \ V \end{array}$	1.0	3.3	4.9	1.0	8.0		
			$\begin{array}{l} 3.00 \ V \leq V_{CC} \leq 3.60 \ V, \\ V_{IN} = 2.30 \ V \ to \ 2.70 \ V \end{array}$	1.0	3.2	4.6	1.0	5.8		
			$\begin{array}{l} 3.00 \ V \leq V_{CC} \leq 3.60 \ V, \\ V_{IN} = 3.00 \ V \ to \ 3.60 \ V \end{array}$	1.0	3.1	4.7	1.0	5.5		
		$C_L = 10 \text{ pF},$ $R_L = 1 \text{ M}\Omega$	$\begin{array}{l} 2.30 \ V \leq V_{CC} \leq 2.70 \ V, \\ V_{IN} = 1.65 \ V \ to \ 1.95 \ V \end{array}$	1.3	4.1	6.5	1.0	7.9		
			$\begin{array}{l} 2.30 \text{ V} \leq \text{V}_{CC} \leq 2.70 \text{ V}, \\ \text{V}_{IN} = 2.30 \text{ V} \text{ to } 2.70 \text{ V} \end{array}$	1.3	4.0	6.2	1.0	7.1		
			2.30 V $\leq$ V_{CC} $\leq$ 2.70 V, V_{IN} = 3.0 V to 3.60 V	1.3	3.7	5.7	1.0	6.5		
			$3.00~V \leq V_{CC} \leq 3.60~V, \\ V_{IN}$ = 1.65 V to 1.95 V	1.3	3.5	5.6	1.0	8.5		
			$\begin{array}{l} 3.00 \text{ V} \leq \text{V}_{CC} \leq 3.60 \text{ V}, \\ \text{V}_{IN} = 2.30 \text{ V} \text{ to } 2.70 \text{ V} \end{array}$	1.3	3.4	5.3	1.0	6.1		
			$\begin{array}{l} 3.00 \ V \leq V_{CC} \leq 3.60 \ V, \\ V_{IN} = 3.00 \ V \ to \ 3.60 \ V \end{array}$	1.3	3.3	5.2	1.0	5.9		
		$C_L = 15 \text{ pF},$ $R_L = 1 \text{ M}\Omega$	2.30 V $\leq$ V_{CC} $\leq$ 2.70 V, V_{IN} = 1.65 V to 1.95 V	1.5	4.6	6.9	1.0	8.7		
			2.30 V $\leq$ V_{CC} $\leq$ 2.70 V, V_{IN} = 2.30 V to 2.70 V	1.5	4.4	6.8	1.0	7.9		
			$2.30V \leq V_{CC} \leq 2.70$ V, $V_{IN} = 3.0$ V to 3.60 V	1.5	4.2	6.3	1.0	7.4		
			3.00 V $\leq$ V_{CC} $\leq$ 3.60 V, V_{IN} = 1.65 V to 1.95 V	1.3	3.9	6.2	1.0	9.1		
			$3.00~V \leq V_{CC} \leq 3.60~V, \\ V_{IN}$ = 2.30 V to 2.70 V	1.3	3.8	5.6	1.0	6.8		
			$\begin{array}{l} 3.00 \ V \leq V_{CC} \leq 3.60 \ V, \\ V_{IN} = 3.00 \ V \ to \ 3.60 \ V \end{array}$	1.3	3.8	5.6	1.0	6.2		
		$C_L = 30 \text{ pF},$ $R_L = 1 \text{ M}\Omega$	2.30 V $\leq$ V_{CC} $\leq$ 2.70 V, V_{IN} = 1.65 V to 1.95 V	1.3	4.2	7.9	1.3	8.5		
			2.30 V $\leq$ V_{CC} $\leq$ 2.70 V, V_{IN} = 2.30 V to 2.70 V	1.3	3.9	7.9	1.3	8.5		
			$2.30V \leq V_{CC} \leq 2.70$ V, $V_{IN}$ = 3.0 V to 3.60 V	1.0	3.7	7.3	1.0	8.9		
			$\begin{array}{l} 3.00 \text{ V} \leq \text{V}_{CC} \leq 3.60 \text{ V}, \\ \text{V}_{IN} = 1.65 \text{ V} \text{ to } 1.95 \text{ V} \end{array}$	1.3	3.5	6.1	1.3	7.9		
			$\begin{array}{l} 3.00V \leq V_{CC} \leq 3.60 \ \overline{V}, \\ V_{IN} = 2.30 \ V \ to \ 2.70 \ V \end{array}$	1.1	3.0	5.9	1.1	6.8		
			$\begin{array}{l} 3.00 \ V \leq V_{CC} \leq 3.60 \ V, \\ V_{IN} = 2.30 \ V \ to \ 2.70 \ V \end{array}$	1.0	2.7	5.7	1.0	6.5		
C <sub>IN</sub>	Input Capacitance	_	0	-	2.1	-	-	-	pF	-
C <sub>OUT</sub>	Output Capacitance	-	0	-	3.0	-	-	-		
C <sub>PD</sub>	Power Dissipation	-	$2.30 \text{ V} \leq \text{V}_{CC} \leq 2.70 \text{ V}$	_	2.0	-	-	-		
	Capachance		$3.00 \text{ V} \le \text{V}_{CC} \le 3.60 \text{ V}$	-	2.7	-	-	-		

# AC LOADINGS AND WAVEFORMS







Figure 11. AC Waveforms

	Vo	c
Symbol	3.3 V ±0.3 V	2.5 V ±0.2 V
V <sub>mi</sub>	V <sub>IN</sub> / 2	V <sub>IN</sub> / 2
V <sub>mo</sub>	V <sub>CC</sub> / 2	V <sub>CC</sub> / 2

MicroPak is trademark of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries.



SIP6 1.45X1.0 CASE 127EB ISSUE O

DATE 31 AUG 2016



special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.



UDFN6 1.0X1.0, 0.35P CASE 517DP ISSUE O DATE 31 AUG 2016 0.89 -ン|0.05|C в 1.00±0.050 А 0.35 2X 5X 0.40 PIN 1 MIN 250uM 0.66 1.00±0.050 1X 0.45 □ 0.05 C TOP VIEW - 6X 0.19 2X **RECOMMENDED LAND PATTERN** FOR SPACE CONSTRAINED PCB 0.05 C 0.90 -0.35 0.50±0.05 С 5X 0.52 SIDE VIEW 6X 0.14±0.05 (0.08) 4X — 0.73 2 DETAIL A 1 3 1X 0.57 – 0.20 6X ALTERNATIVE LAND PATTERN FOR UNIVERSAL APPLICATION - (0.05) 6X 5X 0.30±0.05 0.60 4 0.10(M) C B A 0.35 (0.08) .05 C 4X 0.35±0.050 BOTTOM VIEW NOTES: A. COMPLIES TO JEDEC MO-252 STANDARD **B. DIMENSIONS ARE IN MILLIMETERS.** C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009 0.075X45° DETAIL A CHAMFER PIN 1 LEAD SCALE: 2X

DESCRIPTION: UDEN6 1 0X1 0 0 35P PAGE 1 OF 1	
DESCRIPTION UDENG 1 0X1 0 0 35P PAGE 1 OF 1	

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights of others.

onsemi, ONSEMI, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi's product/patent coverage may be accessed at <u>www.onsemi.com/site/pdf/Patent-Marking.pdf</u>. onsemi reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and onsemi makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or indental damages. Buyer is responsible for its products and applications using onsemi products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by onsemi. "Typical" parameters which may be provided in onsemi data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. onsemi does not convey any license under any of its intellectual property rights nor the rights of others. onsemi products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification. Buyer shall indemnify and hold onsemi and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs,

#### ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation onsemi Website: www.onsemi.com

ONLINE SUPPORT: <u>www.onsemi.com/support</u> For additional information, please contact your local Sales Representative at <u>www.onsemi.com/support/sales</u>