





JN Semiconductor®

To kara more about Old Semiconductor, please visit our website at

Please note. As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



March 2025

D45C11 PNP Current Driver Transistor

Features

- This device is designed for power amplifier, regulator and switching circuits where speed is important.
- · Sourced from Process 5P.
- NZT751 for characteristics.



Absolute Maximum Ratings* T_A = 2 °C unle other .se noted

Symbol	™e r Maitre	Units
V _{CEO}	Collector-Emitter '80	V
I _C	Collector Currer - C tinuous -4.0	А
T _J , T _{STG}	Operating and Sturne Inction Temperature Range -55 to +150	°C

^{*}These ratings ar initial values bove which the serviceability of any semiconductor device may be impaired.

NOTES:

- 1) These rall his are bould on a maximum junction temperal, re of 150 degrees C.
- 2' nest re aguy state limits, l'he factory should be consulted on applications involving pulsed or low duty cycle or rations

Therma! Characteristics in-25°C unless otherwise noted

Symbol	Parameter	Max.	Units
P _D	Total Davice Dissipation Derate above 25°C	60 480	W mW/°C
$R_{ heta JC}$	Thermal Resistance, Junction to Case	2.1	°C/W
$R_{ heta JA}$	Thermal Resistance, Junction to Ambient	62.5	°C/W

Electrical Characteristics	T _A =25°C unless otherwise noted
----------------------------	---

Symbol	Parameter	Test Condition	Min.	Max.	Units
Off Character	istics			•	
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	$I_C = -100 \text{mA}, I_B = 0$	-80		V
I _{CES}	Collector-Cutoff Current	$V_{CE} = -90V, I_{E} = 0$		-10	μΑ
I _{EBO}	Emitter-Cutoff Current	$V_{EB} = -5.0V, I_{B} = 0$		-100	μΑ
On Character	istics				
h _{FE}	DC Current Gain	$V_{CE} = -1.0V, I_{C} = -0.2A$ $V_{CE} = -1.0V, I_{C} = -1.0A$	40 20	120	
V _{CE (sat)}	Collector-Emitter Saturation Voltage	$I_C = -1.0A, I_B = -50mA$		-0.5	V
V _{BE (sat)}	Base-Emitter Saturation Voltage	I _C = -1.0A, I _B = -100mA		-1.	V
Small Signal	Characteristics				,C
C _{ob}	Output Capacitance	V _{CB} = -10V, f = 1.0MHz		21	pF
f⊤	Current Gain - Bandwidth Product	$I_{C} = -20 \text{mA}$. $V_{CE} = -4.0 \text{V}$			MHz



U.

TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

CorePUUS™ Global Power Resource SM CorePOWER™ Green FPS™

CROSSVOLT™ Green FPS™ e-Series™

CTL™ Gmax™

MICROCOUPLER™
MicroFET™
MicroPak™
MillerDriv™
MotionMax™
MotionMax™
Motion-SPM™

Fairchild Semiconductor® Motion-SPM™
FACT Quiet Series™ OPTOLOGIC®
FACT® OPTOPLANAR®
FAST®

FastvCore™

 $\begin{array}{ll} \mathsf{FETBench^{\mathsf{TM}}} & \mathsf{PDP} \; \mathsf{SPM^{\mathsf{TM}}} \\ \mathsf{FlashWriter}^{\otimes *} & \mathsf{Power\text{-}SPM^{\mathsf{TM}}} \end{array}$

PowerTrench[®] PowerXS™

Programmable Active Droop™

QFET[®]
QS™
Quiet Series™
RapidConfigure™

Saving our world, 1mW/W/kW at a time™ SmartMax™

SMART START™

SMART STARTIM
SPM®
STEALTHIM
SuperFETIM
SuperSOTIM-3
SuperSOTIM-6
SuperSOTIM-8
SuperSOTIM-8
SuperMOSIM

SyncFET* Sync*Lock TEN GL RAL The Power Franchise®

franchise
TinyBoost™
TinyBuck™
TinyCalc™
TinyCogic®
TINYOPTO™
TinyPower™
M™

TinyW ™
TriFault etect™
RUEC RRENT™*

SegL'es U.'∃C."
U.'Ta CRFET™
CAIFET™
VCX™
Visus Max™

DISCLAIMER

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE IT AUTH IZED FOR USE AS CRITICAL COMPCINENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN DVAL FEARCH LD SEMICOLID FOR CORPORATION.

As used herein

- 1. Life sup, if devices or silvens are devices or systems which, (a) are intimeded to urgin him that the body or (b) support or sustain life and who falled to perform when properly used in accordance with intimediate for use predicted in the labeling can be reasonably expected presult in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-C ATERFE'T 'NG POLICY

Fairchild Semison du do. Corporation's Ana-Count, reiting Colicy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counter 'sitir g of semiconductor parts is a crowing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase so interfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and incumulated productions. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strong, 'encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I41

^{*} Trademarks of System General Corporation, used under license t a. ild Sem. indució



ON Semiconductor and the are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor and severally, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify an

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800–282–9855 Toll Free USA/Canada Europe, Middle East and Africa Technical Support:

Europe, Middle East and Africa Technical Support: Phone: 421 33 790 2910 Japan Customer Focus Center Phone: 81-3-5817-1050 ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative