MOSFET – N-Channel, SUPERFET® II, FRFET®

650 V, 41 mΩ, 76 A

FCH041N65F-F085

V_{DS}	$R_{DS(ON)}$ MAX	I_D MAX
650 V	41 mΩ @ 10 V	76 A



N-CHANNEL MOSFET



TO-247-3LD
CASE 340CK

Description

SuperFET II Mosfet is **onsemi**'s brand-new high voltage super-junction (SJ) MOSFET family that is utilizing charge balance technology for outstanding low on-resistance and lower gate charge performance. This technology is tailored to minimize conduction loss, provide superior switching performance, dv/dt rate and higher avalanche energy. Consequently, SuperFET II MOSFET is very well suited for the Soft switching and Hard Switching topologies like High Voltage Full Bridge and Half Bridge DC-DC, Interleaved Boost PFC, Boost PFC for HEV-EV automotive.

SuperFET II FRFET MOSFET's optimized body diode reverse recovery performance can remove additional component and improve system reliability.

Features

- Typ. $R_{DS(on)}$ = 34 mΩ at V_{GS} = 10 V, I_D = 38 A
- Typ. $Q_{g(tot)}$ = 234 nC at V_{GS} = 10 V, I_D = 38 A
- UIS Capability
- AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant

Applications

- Automotive On Board Charger
- Automotive DC-DC Converter for HEV

MARKING DIAGRAM



$Y	= **onsemi** Logo
&Z	= Assembly Plant Code
&3	= Numeric Date Code
&K	= Lot Code
FCH041N65F	= Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 8 of this data sheet.

© Semiconductor Components Industries, LLC, 2014

ABSOLUTE MAXIMUM RATINGS (T_C = 25 °C unless otherwise noted)

Symbol	Parameter		Value	Unit
V_{DSS}	Drain-to-Source Voltage		650	V
V_{GSS}	Gate-to-Source Voltage		±20	V
I_D	Drain Current - Continuous (V_{GS} = 10) (Note 1)	T_C = 25 °C	76	A
		T_C = 100 °C	48	A
	Pulsed Drain Current		See Fig. 4	A
E_{AS}	Single Pulsed Avalanche Rating (Note 2)		2025	mJ
dv/dt	MOSFET dv/dt		100	V/ns
	Peak Diode Recovery dv/dt (Note 3)		50	
P_D	Power Dissipation		595	W
	Derate Above 25 °C		4.76	W/°C
T_J, T_{STG}	Operating and Storage Temperature Range		−55 to +150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Repetitive rating: pulse-width limited by maximum junction temperature.
2. I_{AS} = 15 A, R_G = 25 Ω, starting T_J = 25 °C.
3. I_{SD} ≤ 38 A, di/dt ≤ 200 A/μs, V_{DD} ≤ 380 V, starting T_J = 25 °C.

THERMAL CHARACTERISTICS

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case, Max.	0.21	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient, Max. (Note 4)	40	

4. $R_{\theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins. $R_{\theta JC}$ is guaranteed by design, while $R_{\theta JA}$ is determined by the board design. The maximum rating presented here is based on mounting on a 1 in^2 pad of 2 oz copper.

ELECTRICAL CHARACTERISTICS (T_C = 25 °C unless otherwise noted)

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV_{DSS}	Drain-to-Source Breakdown Voltage	I_D = 250 μA, V_{GS} = 0 V	650	–	–	V
I_{DSS}	Drain-to-Source Leakage Current	V_{DS} = 650 V, V_{GS} = 0 V, T_J = 25 °C	–	–	10	μA
		V_{DS} = 650 V, V_{GS} = 0 V, T_J = 150 °C (Note 5)	–	–	1	mA
I_{GSS}	Gate-to-Source Leakage Current	V_{GS} = ±20 V	–	–	±100	nA
ON CHARACTERISTICS						
$V_{GS(th)}$	Gate-to-Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 250 μA	3	-	5	V
$R_{DS(on)}$	Drain-to-Source On Resistance	I_D = 38 A, V_{GS} = 10 V, T_J = 25 °C	–	34	41	mΩ
		I_D = 38 A, V_{GS} = 10 V, T_J = 150 °C (Note 5)	–	80	96	
DYNAMIC CHARACTERISTICS						
C_{iss}	Input Capacitance	V_{DS} = 25 V, V_{GS} = 0 V, f = 1 MHz	–	10200	13566	pF
C_{oss}	Output Capacitance		–	10529	14004	
C_{rss}	Reverse Transfer Capacitance		–	227	–	
$C_{oss(eff.)}$	Effective Output Capacitance	V_{DS} = 0 V to 520 V, V_{GS} = 0 V	–	843	–	pF
R_g	Gate Resistance	f = 1 MHz	–	0.5	2.18	Ω
$Q_{g(tot)}$	Total Gate Charge	V_{DD} = 380 V, I_D = 38 A, V_{GS} = 10 V	–	234	304	nC
$Q_{g(th)}$	Threshold Gate Charge		–	17	22	
Q_{gs}	Gate-to-Source Gate Charge		–	50	–	
Q_{gd}	Gate-to-Drain “Miller” Charge		–	90	–	
SWITCHING CHARACTERISTICS						
t_{on}	Turn-On Time	V_{DD} = 380 V, I_D = 38 A, V_{GS} = 10 V, R_G = 4.7 Ω	–	94	207	ns
$t_{d(on)}$	Turn-On Delay Time		–	55	–	
t_r	Turn-On Rise Time		–	39	–	
$t_{d(off)}$	Turn-Off Delay Time		–	183	–	
t_f	Turn-Off Fall Time		–	8	–	
t_{off}	Turn-Off Time		–	191	402	
DRAIN-SOURCE DIODE CHARACTERISTICS						
V_{SD}	Source-to-Drain Diode Voltage	V_{GS} = 0 V, I_{SD} = 38 A	–	–	1.2	V
t_{rr}	Reverse Recovery Time	V_{DD} = 480 V, I_F = 38 A, di_{SD}/dt = 100 A/μs	–	235	–	ns
Q_{rr}	Reverse Recovery Charge		–	2	–	μC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. The maximum value is specified by design at T_J = 150 °C. Product is not tested to this condition in production.

TYPICAL CHARACTERISTICS



Figure 1. Normalized Power Dissipation vs. Case Temperature



Figure 2. Maximum Continuous Drain Current vs. Case Temperature



Figure 3. Normalized Maximum Transient Thermal Impedance



Figure 4. Peak Current Capability

TYPICAL CHARACTERISTICS (continued)



Figure 5. Forward Bias Safe Operating Area



Figure 6. Transfer Characteristics



Figure 7. Forward Diode Characteristics



Figure 8. Saturation Characteristics



Figure 9. Saturation Characteristics



Figure 10. R_{DSON} vs. Gate Voltage

TYPICAL CHARACTERISTICS (continued)



Figure 11. Normalized R_{DSON} vs. Junction Temperature



Figure 12. Normalized Gate Threshold Voltage vs. Temperature



Figure 13. Normalized Drain to Source Breakdown Voltage vs. Junction Temperature



Figure 14. Capacitance vs. Drain to Source Voltage



Figure 15. Gate Charge vs. Gate to Source Voltage



Figure 16. Eoss vs. Drain to Source Voltage



Figure 17. Gate Charge Test Circuit & Waveform



Figure 18. Resistive Switching Test Circuit & Waveforms



Figure 19. Unclamped Inductive Switching Test Circuit & Waveforms



Figure 20. Peak Diode Recovery dv/dt Test Circuit & Waveforms

PACKAGE MARKING AND ORDERING INFORMATION

Device	Device Marking	Package	Reel Size	Tape Width	Quantity
FCH041N65F-F085	FCH041N65F	TO-247-3	–	–	30 Units

SUPERFET and FRFET are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.

REVISION HISTORY

Revision	Description of Changes	Date
7	Add R_g max limit to 2.18 ohm.	11/26/2025

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.

TO−247−3LD SHORT LEAD
CASE 340CK
ISSUE A

DATE 31 JAN 2019



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.40	1.50	1.60
b	1.17	1.26	1.35
b2	1.53	1.65	1.77
b4	2.42	2.54	2.66
c	0.51	0.61	0.71
D	20.32	20.57	20.82
D1	13.08	~	~
D2	0.51	0.93	1.35
E	15.37	15.62	15.87
E1	12.81	~	~
E2	4.96	5.08	5.20
e	~	5.56	~
L	15.75	16.00	16.25
L1	3.69	3.81	3.93
ØP	3.51	3.58	3.65
ØP1	6.60	6.80	7.00
Q	5.34	5.46	5.58
S	5.34	5.46	5.58

NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON13851G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−247−3LD SHORT LEAD**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales