NPT Trench IGBT

1200 V, 25 A

FGA25N120ANTDTU

TO−3P−3
CASE 340BZ

Description

Using **onsemi**'s proprietary trench design and advanced NPT Technology, the 1200 V NPT IGBT offers superior conduction and switching performances, high avalanche ruggedness and easy parallel operation. This device is well suited for the resonant or soft switching application such as induction heating, microwave oven.

Features

- NPT Trench Technology, Positive Temperature Coefficient
- Low Saturation Voltage: $V_{CE(sat)}$, typ = 2.0 V @ I_C = 25 A and T_C = 25°C
- Low Switching Loss: $E_{CE\ off,\ typ}$ = 0.96 mJ @ I_C = 25 A and T_C = 25°C
- Extremely Enhanced Avalanche Capability
- This Device is Pb−Free Halide, Free and RoHS Compliant

Applications

- Induction Heating, Microwave Oven

MARKING DIAGRAM

FGA25N120	= Specific Device Code
A	= Assembly Location
YWW	= Date Code (Year and Week)
ZZ	= Assembly Lot Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CES}	Collector−Emitter Voltage	1200	V
V_{GES}	Gate−Emitter Voltage	±20	
I_C	Collector Current (@T_C = 25°C)	50	A
	Collector Current (@T_C = 100°C)	25	
I_{CM}	Pulsed Collector Current (Note 1)	90	A
I_F	Diode Continuous Forward Current (@T_C = 25°C)	50	A
	Diode Continuous Forward Current (@T_C = 100°C)	25	A
I_{FM}	Diode Maximum Forward Current	150	A
P_D	Maximum Power Dissipation (@T_C = 25°C)	312	W
	Maximum Power Dissipation (@T_C = 100°C)	125	W
T_J	Operating Temperature Range	−55 to +150	°C
T_{STG}	Storage Temperature Range	−55 to +150	°C
T_L	Maximum Lead Temp for Soldering Purpose, 1/8" from Case for 5 s	300	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

NOTES:

1. Repetitive Rating: Pulse−width limited by maximum junction temperature.

© Semiconductor Components Industries, LLC, 2006

THERMAL CHARACTERISTICS

Symbol	Parameter	Value	Unit
$R_{\theta JC}$(IGBT)	Thermal Resistance, Junction to Case	0.4	°C/W
$R_{\theta JC}$(DIODE)	Thermal Resistance, Junction to Case	2.0	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	40	°C/W

ORDERING INFORMATION

Part Number	Top Mark	Package	Packing Method	Reel Size	Tape Width	Quantity
FGA25N120ANTDTU−F109	FGA25N120ANTD	TO−3PN	Tube	N/A	N/A	30

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

ELECTRICAL CHARACTERISTICS OF THE IGBT (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Off Characteristics						
I_{CES}	Collector Cut−Off Current	V_{CE} =V_{CES}, V_{GE} = 0 V	–	–	3	mA
I_{GES}	G−E Leakage Current	V_{GE} =V_{GES}, V_{CE} = 0 V	–	–	±250	nA
On Characteristics						
$V_{GE(th)}$	G−E Threshold Voltage	I_C = 25 mA, V_{CE} = V_{GE}	3.5	5.5	7.5	V
$V_{CE(Sat)}$	Collector to Emitter Saturation Voltage	I_C = 25 A, V_{GE} = 15 V	–	2.0	–	V
		I_C = 25 A, V_{GE} = 15 V, T_C = 125°C	–	2.15	–	V
		I_C = 50 A, V_{GE} = 15 V	–	2.65	–	V
Dynamic Characteristics						
C_{ies}	Input Capacitance	V_{CE} = 30 V, V_{GE} = 0 V, f = 1 MHz	–	3700	–	pF
C_{oes}	Output Capacitance		–	130	–	pF
C_{res}	Reverse Transfer Capacitance		–	80	–	pF
Switching Characteristics						
$t_{d(on)}$	Turn−On Delay Time	V_{CC} = 600 V, I_C = 25 A, R_G = 10 Ω, V_{GE} = 15 V, Inductive Load, T_C = 125°C	–	50		ns
t_r	Rise Time		–	60		ns
$t_{d(off)}$	Turn−Off Delay Time		–	190		ns
t_f	Fall Time		–	100		ns
E_{on}	Turn−On Switching Loss		–	4.1		mj
E_{off}	Turn−Off Switching Loss		–	0.96		mj
E_{ts}	Total Switching Loss		–	5.06		mj
$t_{d(on)}$	Turn−On Delay Time	V_{CC} = 600 V, I_C = 25 A, R_G = 10 Ω, V_{GE} = 15 V, Inductive Load, T_C = 125°C	–	50		ns
t_r	Rise Time		–	60		ns
$t_{d(off)}$	Turn−Off Fall Time		–	200		ns
t_f	Fall Time		–	154		ns
E_{on}	Turn−On Switching Loss		–	4.3		mj
E_{off}	Turn−Off Switching Loss		–	1.5		mj
E_{ts}	Total Switching Loss		–	5.8		mj
Q_g	Total Gate Charge	V_{CE} = 600 V, I_C = 25 A, V_{GE} = 15 V	–	200		nC
Q_{ge}	Gate−Emitter Charge		–	15		nC
Q_{gc}	Gate−Collector Charge		–	100		nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ELECTRICAL CHARACTERISTICS OF DIODE (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions		Min.	Typ.	Max.	Unit
V_{FM}	Diode Forward Voltage	I_F = 25 A	T_C = 25°C	–	2.0	3.0	V
			T_C = 125°C	–	2.1	–	
t_{rr}	Diode Reverse Recovery Time	I_F = 25 A, dI_F/dt = 100 A/μs	T_C = 25°C	–	235	350	ns
			T_C = 125°C	–	300	–	
I_{rr}	Diode Peak Reverse Recovery Current		T_C = 25°C	–	27	40	A
			T_C = 125°C	–	31	–	
Q_{rr}	Diode Reverse Recovery Charge		T_C = 25°C	–	3130	4700	nC
			T_C = 125°C	–	4650	–	

TYPICAL PERFORMANCE CHARACTERISTICS

Figure 1. Typical Output Characteristics

Figure 2. Typical Saturation Voltage Characteristics

Figure 3. Saturation Voltage vs. Case Temperature at Variant Current Level

Figure 4. V_{GE} vs Saturation Voltage

Figure 5. V_{GE} vs. Saturation Voltage

Figure 6. V_{GE} vs. Saturation Voltage

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)

Figure 7. Capacitance Characteristics

Figure 8. Turn On−Characteristics vs. Gate Resistance

Figure 9. Turn Off−Characteristics vs. Gate Resistance

Figure 10. Switching Loss vs. Gate Resistance

Figure 11. Turn−On Characteristics vs. Collector Current

Figure 12. Turn−Off Characteristics vs. Collector Current

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)

Figure 13. Switching Loss vs Collector Current

Figure 14. Gate Charge Characteristics

Figure 15. SOA Characteristics

Figure 16. Turn−Off SOA

Figure 17. Transient Thermal Impedance of IGBT

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)

Figure 18. Forward Characteristics

Figure 19. Reverse Recovery Current

Figure 20. Stored Charge

Figure 21. Reverse Recovery Time

TO−3P−3LD / EIAJ SC−65, ISOLATED
CASE 340BZ
ISSUE O

DATE 31 OCT 2016

NOTES: UNLESS OTHERWISE SPECIFIED

A) THIS PACKAGE CONFORMS TO EIAJ SC-65 PACKAGING STANDARD.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSION AND TOLERANCING PER ASME14.5-2009.
D) DIMENSIONS ARE EXCLUSSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSSIONS.

DOCUMENT NUMBER:	**98AON13862G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−3P−3LD / EIAJ SC−65, ISOLATED**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales