MOSFET – P-Channel, QFET

-60 V, -30 A, 26 mΩ

FQPF47P06, FQPF47P06YDTU

V_{DSS}	$R_{DS(ON)}$ MAX	I_D MAX
−60 V	26 mΩ @ −10 V	−30 A



P−Channel MOSFET



TO−220 Fullpack, 3−Lead / TO−220F−3SG
CASE 221AT



TO−220−3LD LF
CASE 340BJ

Description

This P−Channel enhancement mode power MOSFET is produced using **onsemi**'s proprietary planar stripe and DMOS technology. This advanced MOSFET technology has been especially tailored to reduce on−state resistance, and to provide superior switching performance and high avalanche energy strength. These devices are suitable for switched mode power supplies, audio amplifier, DC motor control, and variable switching power applications.

Features

- −30 A, −60 V, $R_{DS(on)}$ = 26 mΩ (Max.) @ V_{GS} = −10 V, I_D = −15 A
- Low Gate Charge (Typ. 84 nC)
- Low Crss (Typ. 320 pF)
- 100% Avalanche Tested
- 175°C Maximum Junction Temperature Rating

MARKING DIAGRAM



FQPF47P06 = Specific Device Code
A = Assembly Location
YWW = Date Code (Year & Week)
ZZ = Assembly Lot

ORDERING INFORMATION

Device	Package	Shipping
FQPF47P06	TO−220−3 Fullpack (Pb−Free)	1000 Units / Tube
FQPF47P06YDTU	TO−220−3 (Pb−Free)	800 Units / Tube

© Semiconductor Components Industries, LLC, 2001

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise specified)

Symbol	Parameter		FQPF47P06 / FQPF47P06YDTU	Unit
V_{DSS}	Drain−Source Voltage		−60	V
I_D	Drain Current	− Continuous (T_C = 25°C)	−30	A
		− Continuous (T_C = 100°C)	−21.2	A
I_{DM}	Drain Current (Note 1)	− Pulsed	−120	A
V_{GSS}	Gate−Source Voltage		+ 25	V
E_{AS}	Single Pulsed Avalanche Energy (Note 2)		820	mJ
I_{AR}	Avalanche Current (Note 1)		−30	A
E_{AR}	Repetitive Avalanche Energy (Note 1)		6.2	mJ
dv/dt	Peak Diode Recovery dv/dt (Note 3)		−7.0	V/ns
P_D	Power Dissipation (T_C = 25°C)		62	W
		− Derate above 25°C	0.41	W/°C
T_J, T_{STG}	Operating and Storage Temperature Range		−55 to +175	°C
T_L	Maximum Lead Temperature for Soldering Purposes, 1/8" from Case for 5 Seconds		300	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. L = 1.06 mH, I_{AS} = −30 A, V_{DD} = −25 V, R_G = 25 Ω, Starting T_J = 25°C
3. I_{SD} ≤ −47 A, di/dt ≤ 300A/μs, V_{DD} ≤ BV_{DSS}, Starting T_J = 25°C

THERMAL CHARACTERISTICS

Symbol	Characteristic	Typ	Max	Unit
$R_{\theta JC}$	Thermal Resistance, Junction−to−Case	−	2.42	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction−to−Ambient	−	62.5	°C/W

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
BV_{DSS}	Drain−Source Breakdown Voltage	V_{GS} = 0 V, I_D = −250 μA	−60	−−	−	V
ΔBV_{DSS} / ΔT_J	Breakdown Voltage Temperature Coefficient	I_D = −250 μA, Referenced to 25°C	−	−0.06	−	V/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = −60 V, V_{GS} = 0 V	−	−	−1	μA
		V_{DS} = −48 V, T_C = 150°C	−	−	−10	μA
I_{GSSF}	Gate−Body Leakage Current, Forward	V_{GS} = −25 V, V_{DS} = 0 V	−	−	−100	nA
I_{GSSR}	Gate−Body Leakage Current, Reverse	V_{GS} = 25 V, V_{DS} = 0 V	−	−	100	nA
ON CHARACTERISTICS						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = −250 μA	−2.0	−	−4.0	V
$R_{DS(on)}$	Static Drain−Source On−Resistance	V_{GS} = −10 V, I_D = −15 A	−	0.021	0.026	Ω
g_{FS}	Forward Transconductance	V_{DS} = −30 V, I_D = −15 A (Note 4)	−	19	−	S
DYNAMIC CHARACTERISTICS						
C_{iss}	Input Capacitance	V_{DS} = −25 V, V_{GS} = 0 V, f = 1.0 MHz	−	2800	3600	pF
C_{oss}	Output Capacitance		−	1300	1700	pF
C_{rss}	Reverse Transfer Capacitance		−	320	420	pF
SWITCHING CHARACTERISTICS						
$t_{d(on)}$	Turn−On Delay Time	V_{DD} = −30 V, I_D = −23.5 A, R_G = 25 Ω (Note 4, 5)	−	50	110	ns
t_r	Turn−On Rise Time		−	450	910	ns
$t_{d(off)}$	Turn−Off Delay Time		−	100	210	ns
t_f	Turn−Off Fall Time		−	195	400	ns
Q_g	Total Gate Charge	V_{DS} = −48 V, I_D = −47 A, V_{GS} = −10 V (Note 4, 5)	−	84	110	nC
Q_{gs}	Gate−Source Charge		−	18	−	nC
Q_{gd}	Gate−Drain Charge		−	44	−	nC
DRAIN−SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATING						
I_S	Maximum Continuous Drain−Source Diode Forward Current		−	−	−30	A
I_{SM}	Maximum Pulsed Drain−Source Diode Forward Current		−	−	−120	A
V_{SD}	Drain−Source Diode Forward Voltage	V_{GS} = 0 V, I_S = −30 A	−	−	−4.0	V
t_{rr}	Reverse Recovery Time	V_{GS} = 0 V, I_S = −47 A, dI_F / dt = 100 A/μs (Note 4)	−	130	−	ns
Q_{rr}	Reverse Recovery Charge		−	0.55	−	μC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse Test: Pulse width ≤ 300 μs, Duty cycle ≤ 2%
5. Essentially independent of operating temperature

TYPICAL CHARACTERISTICS



Figure 1. On–Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On–Resistance Variation vs. Drain Current and Gate Voltage



Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature



Figure 5. Capacitance Characteristics



Figure 6. Gate Charge Characteristics

TYPICAL CHARACTERISTICS (CONTINUED)



Figure 7. Breakdown Voltage Variation vs. Temperature



Figure 8. On−Resistance Variation vs. Temperature



Figure 9. Maximum Safe Operating Area



Figure 10. Maximum Drain Current vs. Case Temperature



Figure 11. Transient Thermal Response Curve



Figure 12. Gate Charge Test Circuit & Waveform



Figure 13. Resistive Switching Test Circuit & Waveforms



Figure 14. Unclamped Inductive Switching Test Circuit & Waveforms



Figure 15. Peak Diode Recovery dv/dt Test Circuit & Waveforms

TO−220 Fullpack, 3−Lead / TO−220F−3SG
CASE 221AT
ISSUE B

DATE 19 JAN 2021



Scale 1:1







DIM	MILLIMITERS		
	MIN	NOM	MAX
A	4.50	4.70	4.90
A1	2.56	2.76	2.96
A2	2.34	2.54	2.74
b	0.70	0.80	0.90
b2	~	~	1.47
c	0.45	0.50	0.60
D	15.67	15.87	16.07
D1	15.60	15.80	16.00
E	9.96	10.16	10.36
e	2.34	2.54	2.74
F	~	0.84	~
H1	6.48	6.68	6.88
L	12.78	12.98	13.18
L1	3.03	3.23	3.43
ø P	2.98	3.18	3.38
ø P1	~	1.00	~
Q	3.20	3.30	3.40

NOTES:
A. DIMENSION AND TOLERANCE AS ASME Y14.5-2009
B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUCSIONS.
C. OPTION 1 - WITH SUPPORT PIN HOLE
OPTION 2 - NO SUPPORT PIN HOLE

DOCUMENT NUMBER:	**98AON67439E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**TO−220 FULLPACK, 3−LEAD / TO−220F−3SG**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

TO−220−3LD LF
CASE 340BJ
ISSUE O

DATE 31 AUG 2016



NOTES:

A. EXCEPT WHERE NOTED CONFORMS TO EIAJ SC91A.
B DOES NOT COMPLY EIAJ STD. VALUE.
C. ALL DIMENSIONS ARE IN MILLIMETERS.
D. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSIONS.
E. DIMENSION AND TOLERANCE AS PER ASME Y14.5-1994.

DOCUMENT NUMBER:	**98AON13842G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−220−3LD LF**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales