


NPN Epitaxial Silicon Transistor


KSD882



1. Emitter
2. Collector
3. Base

TO-126-3LD
CASE 340AS

MARKING DIAGRAM



&3 = 3-Digit Date Code
D882 = Specific Device Code
Y = h_{FE} Grade

ORDERING INFORMATION

Device	Package	Shipping
KSD882YS	TO-126-3 (Pb-Free)	2000 Units / Bulk Bag
KSD882YSTU	TO-126-3 (Pb-Free)	1920 Units / Tube

Recommended Applications

- Audio Frequency Power Amplifier

Features

- Low Speed Switching
- Complement to KSB772

ABSOLUTE MAXIMUM RATINGS

($T_A = 25^\circ\text{C}$ unless otherwise noted) (Note 1)

Symbol	Parameter	Ratings	Units
BV_{CBO}	Collector-Base Voltage	40	V
BV_{CEO}	Collector-Emitter Voltage	30	V
BV_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current (DC)	3	A
I_{CP}	Collector Current (Pulse) (Note 2)	7	A
I_B	Base Current	0.6	A
P_D	Total Device Dissipation, $T_C = 25^\circ\text{C}$ $T_A = 25^\circ\text{C}$	10 1	W
T_J, T_{STG}	Junction and Storage Temperature	-55 ~ +150	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.
2. $PW \leq 10$ ms, Duty Cycle $\leq 50\%$.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Characteristic	Test Condition	Min	Typ.	Max	Unit
BV_{CBO}	Collector-Base Breakdown Voltage	$I_C = 500 \mu\text{A}, I_E = 0$	40	-	-	V
BV_{CEO}	Collector-Emitter Breakdown Voltage	$I_C = 5 \text{ mA}, I_B = 0$	30	-	-	V
BV_{EBO}	Emitter-Base Breakdown Voltage	$I_E = 500 \mu\text{A}, I_C = 0$	5	-	-	V
I_{CBO}	Collector Cut-off Current	$V_{CB} = 30 \text{ V}, I_E = 0$	-	-	1	μA
I_{EBO}	Emitter Cut-off Current	$V_{EB} = 3 \text{ V}, I_C = 0$	-	-	1	μA
h_{FE1} h_{FE2}	DC Current Gain (Note 3)	$V_{CE} = 2 \text{ V}, I_C = 20 \text{ mA}$ $V_{CE} = 2 \text{ V}, I_C = 1 \text{ A}$	30 60	150 160	400	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage (Note 3)	$I_C = 2 \text{ A}, I_B = 0.2 \text{ A}$	-	0.3	0.5	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage (Note 3)	$I_C = 2 \text{ A}, I_B = 0.2 \text{ A}$	-	1.0	2.0	V
f_T	Current Gain Bandwidth Product	$V_{CE} = 5 \text{ V}, I_E = 0.1 \text{ A}$	-	90	-	MHz
C_{ob}	Output Capacitance	$V_{CB} = 10 \text{ V}, I_E = 0, f = 1 \text{ MHz}$	-	45	-	pF

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: $PW \leq 350 \mu\text{s}$, Duty Cycle $\leq 2\%$ Pulsed.

KSD882

h_{FE} CLASSIFICATION

Classification	R	O	Y	G
h_{FE2}	60 ~ 120	100 ~ 200	160 ~ 320	200 ~ 400

TYPICAL CHARACTERISTICS




Figure 1. Static Characteristic




Figure 2. DC Current Gain




Figure 3. Base-Emitter Saturation Voltage
Collector-Emitter Saturation Voltage




Figure 4. Current Gain Bandwidth Product




Figure 5. Collector Output Capacitance




Figure 6. Safe Operating Areas

TYPICAL CHARACTERISTICS (Continue)




Figure 7. Derating Curve of Safe Operating Areas




Figure 8. Power Derating

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

