LDO Regulator – Dual, Adjustable Current Limit, Diagnostic Features

3.3 V to 20 V

NCV47821

The NCV47821 dual channel LDO regulator with 200 mA per channel is designed for use in harsh automotive environments. The device has a high peak input voltage tolerance and reverse input voltage, reverse bias, overcurrent and overtemperature protections. The integrated current sense feature (adjustable by resistor connected to CSO pin for each channel) provides diagnosis and system protection functionality. The CSO pin output current creates voltage drop across CSO resistor which is proportional to output current of each channel. Extended diagnostic features in OFF state are also available and controlled by dedicated input and output pins.

Features

- Adjustable Outputs: 3.3 V to 20 V ±3% Output Voltage
- Output Current per Channel: up to 200 mA
- Two Independent Enable Inputs (3.3 V Logic Compatible)
- Adjustable Current Limits: up to 300 mA
- Protection Features:
  - Current Limitation
  - Thermal Shutdown
  - Reverse Input Voltage and Reverse Bias Voltage
- Diagnostic Features:
  - Short To Battery (STB) and Open Load (OL) in OFF State
  - Internal Components for OFF State Diagnostics
  - Open Collector Flag Output
- AEC–Q100 Grade 1 Qualified and PPAP Capable
- These Devices are Pb–Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications

- Audio and Infotainment System
- Active Safety System



Figure 1. Application Schematic
(See Application Section for More Details)



TSSOP–14
Exposed Pad
CASE 948AW

MARKING DIAGRAM



A	= Assembly Location
L	= Wafer Lot
Y	= Year
W	= Work Week
▪	= Pb–Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information on page 14 of this data sheet.

© Semiconductor Components Industries, LLC, 2017



Figure 2. Simplified Block Diagram

Share Feedback
Your Opinion Matters



Figure 3. Pin Connections

Table 1. PIN FUNCTION DESCRIPTION

Pin No. TSSOP−14 EPAD	Pin Name	Description
1	V_{in}	Power Supply Input for Channel 1 and supply of control circuits of whole chip. At least 4.4 V power supply must be used for proper IC functionality.
2	CSO1	Current Sense Output 1, Current Limit setting and Output Current value information. See Application Section for more details.
3	EN1	Enable Input 1; low level disables the Channel 1. (Used also for OFF state diagnostics control for Channel 1)
4	GND	Power Supply Ground.
5	EN2	Enable Input 2; low level disables the Channel 2. (Used also for OFF state diagnostics control for Channel 2)
6	CSO2	Current Sense Output 2, Current Limit setting and Output Current value information. See Application Section for more details.
7	V_{in}	Power Supply Input for Channel 2. Connect to pin 1 or different power supply rail.
8	V_{out2}	Regulated Output Voltage 2.
9	ADJ2	Adjustable Voltage Setting Input 2. See Application Section for more details.
10	DE	Diagnostic Enable Input.
11	EF	Error Flag (Open Collector) Output. Active Low.
12	CS	Channel Select Input for OFF state diagnostics. Set CS = Low for OFF state diagnostics of Channel 1. Set CS = High for OFF state diagnostics of Channel 2. Corresponding EN pin has to be used for diagnostics control (see Application Information section for more details).
13	ADJ1	Adjustable Voltage Setting Input 1. See Application Section for more details.
14	V_{out1}	Regulated Output Voltage 1.
EPAD	EPAD	Exposed Pad is connected to Ground. Connect to GND plane on PCB.

Share Feedback
Your Opinion Matters

Table 2. MAXIMUM RATINGS

Rating	Symbol	Min	Max	Unit
Input Voltage DC	V_{in}	−42	45	V
Input Voltage (Note 1) Load Dump − Suppressed	U_{s*}	−	60	V
Enable Input Voltage	$V_{EN1,2}$	−42	45	V
ADJ Input Voltage	$V_{ADJ1,2}$	−0.3	10	V
CSO Voltage	$V_{CSO1,2}$	−0.3	7	V
DE, CS and EF Voltages	V_{DE}, V_{CS} V_{EF}	−0.3	7	V
Output Voltage	$V_{out1,2}$	−1	40	V
Junction Temperature	T_J	−40	150	°C
Storage Temperature	T_{STG}	−55	150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Load Dump Test B (with centralized load dump suppression) according to ISO16750−2 standard. Guaranteed by design. Not tested in production. Passed Class C according to ISO16750−1.

Table 3. ESD CAPABILITY (Note 2)

Rating	Symbol	Min	Max	Unit
ESD Capability, Human Body Model	ESD_{HBM}	−2	2	kV

2. This device series incorporates ESD protection and is tested by the following methods:
   ESD Human Body Model tested per AEC−Q100−002 (JS−001−2010)
   Field Induced Charge Device Model ESD characterization is not performed on plastic molded packages with body sizes < 50 mm2 due to the inability of a small package body to acquire and retain enough charge to meet the minimum CDM discharge current waveform characteristic defined in JEDEC JS−002−2014.

Table 4. LEAD SOLDERING TEMPERATURE AND MSL (Note 3)

Rating	Symbol	Min	Max	Unit
Moisture Sensitivity Level	MSL	1		−

3. For more information, please refer to our Soldering and Mounting Techniques Reference Manual, SOLDERRM/D

THERMAL CHARACTERISTICS (Note 4)

Rating	Symbol	Value	Unit
Thermal Characteristics (single layer PCB) Thermal Resistance, Junction−to−Air (Note 5) Thermal Reference, Junction−to−Lead (Note 5)	 $R_{\theta JA}$ $R_{\psi JL}$	 52 9.0	°C/W
Thermal Characteristics (4 layers PCB) Thermal Resistance, Junction−to−Air (Note 5) Thermal Reference, Junction−to−Lead (Note 5)	 $R_{\theta JA}$ $R_{\psi JL}$	 31 10	°C/W

4. Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.
5. Values based on copper area of 645 mm^2 (or 1 in^2) of 1 oz copper thickness and FR4 PCB substrate. Single layer − according to JEDEC51.3, 4 layers − according to JEDEC51.7

Table 5. RECOMMENDED OPERATING RANGES

Rating	Symbol	Min	Max	Unit
Input Voltage (Note 6)	V_{in}	4.4	40	V
Nominal Output Voltages	$V_{out_nom1,2}$	3.3	20	V
Output Current Limit (Note 7)	$I_{LIM1,2}$	10	300	mA
Junction Temperature	T_J	−40	150	°C
Current Sense Output (CSO) Capacitor	$C_{CSO1,2}$	1	4.7	μF

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

6. Minimum V_{in} = 4.4 V or ($V_{out1,2}$ + 0.5 V), whichever is higher.
7. Corresponding $R_{CSO1,2}$ is in range from 25.5 kΩ down to 850 Ω.

Share Feedback
Your Opinion Matters

Table 6. ELECTRICAL CHARACTERISTICS V_{in} = 13.5 V, $V_{EN1,2}$ = 3.3 V, V_{DE} = 0 V, $R_{CSO1,2}$ = 0 Ω, $C_{CSO1,2}$ = 1 μF, C_{in} = 1 μF, $C_{out1,2}$ = 10 μF, Min and Max values are valid for temperature range −40°C ≤ T_J ≤ +150°C unless noted otherwise and are guaranteed by test, design or statistical correlation. Typical values are referenced to T_J = 25°C (Note 8)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
REGULATOR OUTPUTS						
Output Voltage (Accuracy %) (Note 9)	V_{in} = V_{in_min} to 40 V $I_{out1,2}$ = 5 mA to 200 mA	$V_{out1,2}$	−3	–	+3	%
Line Regulation (Note 9)	V_{in} = V_{in_min} to ($V_{out_nom1,2}$ + 20 V) $I_{out1,2}$ = 5 mA	$Reg_{line1,2}$	–	0.1	1.0	%
Load Regulation	V_{in} = ($V_{out_nom1,2}$ + 8.5 V) $I_{out1,2}$ = 5 mA to 200 mA	$Reg_{load1,2}$	–	0.4	1.4	%
Dropout Voltage (Note 10)	$V_{out_nom1,2}$ = 5 V, $I_{out1,2}$ = 200 mA $V_{DO1,2}$ = V_{in} − $V_{out1,2}$	$V_{DO1,2}$	–	250	500	mV
DISABLE AND QUIESCENT CURRENTS						
Disable Current	$V_{EN1,2}$ = 0 V, $V_{out_nom1,2}$ = 5 V, −40°C ≤ T_J ≤ +125°C	I_{DIS}	–	0.1	10	μA
Quiescent Current, I_q = I_{in} − (I_{out1} +I_{out2})	I_{out1} = I_{out2} = 500 μA, V_{in} = (V_{out_nom} + 8.5 V)	I_q	–	0.6	1.0	mA
Quiescent Current, I_q = I_{in} − (I_{out1} +I_{out2})	I_{out1} = I_{out2} = 200 mA, V_{in} = (V_{out_nom} + 8.5 V)	I_q	–	15.5	25	mA
CURRENT LIMIT PROTECTION						
Current Limit	$V_{out1,2}$ = 0.9 x $V_{out_nom1,2}$ V_{in} = ($V_{out_nom1,2}$ + 8.5 V)	$I_{LIM1,2}$	300	–	–	mA
PSRR & NOISE						
Power Supply Ripple Rejection (Note 11)	f = 100 Hz, 0.5 $V_{p-p1,2}$	$PSRR_{1,2}$	–	75	–	dB
Output Noise Voltage (Note 11)	f = 10 Hz to 100 kHz, $C_{b1,2}$ = 10 nF	$V_{n1,2}$	–	137	–	μV_{rms}
ENABLE						
Enable Input Threshold Voltage Logic Low (OFF) Logic High (ON)	 $V_{out1,2}$ ≤ 0.1 V $V_{out1,2}$ ≥ 0.9 x $V_{out_nom1,2}$ ($V_{out_nom1,2}$ = 5 V)	$V_{th(EN1,2)}$	 0.99 –	 1.8 1.9	 – 2.31	V
Enable Input Current	$V_{EN1,2}$ = 3.3 V, $V_{out_nom1,2}$ = 5 V	$I_{EN1,2}$	2	8	20	μA
Turn On Time from Enable ON to 90 % of V_{out}	$I_{out1,2}$ = 100 mA, $C_{b1,2}$ = 10 nF, R_{n1} = 82 kΩ, R_{n2} = 27 kΩ	t_{on}	–	1.7	–	ms
OUTPUT CURRENT SENSE						
CSO Voltage Level at Current Limit	$V_{out1,2}$ = 0.9 x $V_{out_nom1,2}$, ($V_{out_nom1,2}$ = 5 V) $R_{CSO1,2}$ = 1 kΩ	$V_{CSO_Ilim1,2}$	2.448 (−4%)	2.55	2.652 (+4%)	V
CSO Transient Voltage Level	$C_{CSO1,2}$ = 4.7 μF, $R_{CSO1,2}$ = 1 kΩ $I_{out1,2}$ pulse from 10 mA to 300 mA, tr = 1 μs	$V_{CSO1,2}$	–	–	3.3	V
Output Current to CSO Current Ratio (Note 11, 12)	$V_{CSO1,2}$ = 2 V, $I_{out1,2}$ = 1 mA to 10 mA ($V_{out_nom1,2}$ = 5 V)	$I_{out1,2}$/ $I_{CSO1,2}$	– (−5%)	98	– (+5%)	–
Output Current to CSO Current Ratio (Note 12)	$V_{CSO1,2}$ = 2 V, $I_{out1,2}$ = 10 mA to 300 mA ($V_{out_nom1,2}$ = 5 V)	$I_{out1,2}$/ $I_{CSO1,2}$	– (−5%)	100	– (+5%)	–
CSO Current at no Load Current	$V_{CSO1,2}$ = 0 V, $I_{out1,2}$ = 0 mA, ($V_{out_nom1,2}$ = 5 V)	$I_{CSO_off1,2}$	–	–	10	μA

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

8. Performance guaranteed over the indicated operating temperature range by design and/or characterization tested at T_A ≈ T_J. Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.
9. Minimum input voltage V_{in_min} is 4.4 V or ($V_{out_nom1,2}$ + 1 V) whichever is higher. $V_{out_nom1,2}$ measured at ADJ1,2 pin due to excluding R_{n1} and R_{n2} accuracy.
10. Measured when the output voltage $V_{out1,2}$ has dropped by 2% of $V_{out_nom1,2}$ from the nominal valued obtained at V_{in} = $V_{out1,2}$ + 8.5 V.
11. Values based on design and/or characterization.
12. Not guaranteed in dropout.

Share Feedback
Your Opinion Matters

Table 6. ELECTRICAL CHARACTERISTICS V_{in} = 13.5 V, $V_{EN1,2}$ = 3.3 V, V_{DE} = 0 V, $R_{CSO1,2}$ = 0 Ω, $C_{CSO1,2}$ = 1 μF, C_{in} = 1 μF, $C_{out1,2}$ = 10 μF, Min and Max values are valid for temperature range −40°C ≤ T_J ≤ +150°C unless noted otherwise and are guaranteed by test, design or statistical correlation. Typical values are referenced to T_J = 25°C (Note 8)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
DIAGNOSTICS						
Overcurrent Voltage Level Threshold	$V_{out_nom1,2}$ = 5 V, $R_{CSO1,2}$ = 1 kΩ	$V_{OC1,2}$	92	95	98	% of $V_{CSO_Ilim1,2}$
Short To Battery (STB) Voltage Threshold in OFF state	V_{in} = 4.4 V to 18 V, I_{out1} = I_{out2} = 0 mA, V_{DE} = 3.3 V	$V_{STB1,2}$	2	3	4	V
Open Load (OL) Current Threshold in OFF state	V_{in} = 4.4 V to 18 V, V_{DE} = 3.3 V	$I_{OL1,2}$	5.0	10	25	mA
Diagnostics Enable Threshold Voltage Logic Low Logic High		$V_{th(DE)}$	 0.99 –	 1.8 1.9	 – 2.31	V
Channel Select Threshold Voltage Logic Low Logic High		$V_{th(CS)}$	 0.99 –	 1.8 1.9	 – 2.31	V
Error Flag Low Voltage	I_{EF} = −1 mA	V_{EF_Low}	–	0.04	0.4	V
THERMAL SHUTDOWN						
Thermal Shutdown Temperature (Note 11)	I_{out1} = I_{out2} = 5 mA, $V_{out_nom1,2}$ = 5 V, each channel measured separately	$T_{SD1,2}$	150	175	195	°C

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

8. Performance guaranteed over the indicated operating temperature range by design and/or characterization tested at $T_A \approx T_J$. Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.
9. Minimum input voltage V_{in_min} is 4.4 V or ($V_{out_nom1,2}$ + 1 V) whichever is higher. $V_{out_nom1,2}$ measured at ADJ1,2 pin due to excluding R_{n1} and R_{n2} accuracy.
10. Measured when the output voltage $V_{out1,2}$ has dropped by 2% of $V_{out_nom1,2}$ from the nominal valued obtained at V_{in} = $V_{out1,2}$ + 8.5 V.
11. Values based on design and/or characterization.
12. Not guaranteed in dropout.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 4. Reference Voltage vs. Temperature



Figure 5. Quiescent Current vs. Input Voltage



Figure 6. Reference Voltage vs. Input Voltage



Figure 7. Input Current vs. Input Voltage (Reverse Input Voltage)



Figure 8. Dropout Voltage vs. Output Current



Figure 9. Output Current Limit vs. Input Voltage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 10. Output Current Limit vs. R_{CSO}



Figure 11. Output Current (% of I_{LIM}) vs. CSO Voltage



Figure 12. Quiescent Current vs. Output Current (Low Load)



Figure 13. Quiescent Current vs. Output Current (High Load)



Figure 14. Output Current to CSO Current Ratio vs. Output Current



Figure 15. Output Current to CSO Current Ratio vs. Output Current (in dropout)

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 16. Output Capacitor Stability Region vs. Output Current



Figure 17. Noise vs. Frequency



Figure 18. PSRR vs. Frequency

Share Feedback
Your Opinion Matters

DEFINITIONS

General

All measurements are performed using short pulse low duty cycle techniques to maintain junction temperature as close as possible to ambient temperature.

Output voltage

The output voltage parameter is defined for specific temperature, input voltage and output current values or specified over Line, Load and Temperature ranges.

Line Regulation

The change in output voltage for a change in input voltage measured for specific output current over operating ambient temperature range.

Load Regulation

The change in output voltage for a change in output current measured for specific input voltage over operating ambient temperature range.

Dropout Voltage

The input to output differential at which the regulator output no longer maintains regulation against further reductions in input voltage. It is measured when the output drops 2% of V_{out_nom} below its nominal value. The junction temperature, load current, and minimum input supply requirements affect the dropout level.

Quiescent and Disable Currents

Quiescent Current (I_q) is the difference between the input current (measured through the LDO input pin) and the output load current. If Enable pin is set to LOW the regulator reduces its internal bias and shuts off the output, this term is called the disable current (I_{DIS}).

Current Limit

Current Limit is value of output current by which output voltage drops below 90% of its nominal value.

PSRR

Power Supply Rejection Ratio is defined as ratio of output voltage and input voltage ripple. It is measured in decibels (dB).

Line Transient Response

Typical output voltage overshoot and undershoot response when the input voltage is excited with a given slope.

Load Transient Response

Typical output voltage overshoot and undershoot response when the output current is excited with a given slope between low−load and high−load conditions.

Thermal Protection

Internal thermal shutdown circuitry is provided to protect the integrated circuit in the event that the maximum junction temperature is exceeded. When activated at typically 175°C, the regulator turns off. This feature is provided to prevent failures from accidental overheating.

Maximum Package Power Dissipation

The power dissipation level is maximum allowed power dissipation for particular package or power dissipation at which the junction temperature reaches its maximum operating value, whichever is lower.

Share Feedback
Your Opinion Matters

APPLICATIONS INFORMATION

Circuit Description

The NCV47821 is an integrated dual low dropout regulator that provides a regulated voltage at 200 mA to each output. It is enabled with an input to the enable pin. The regulator voltage is provided by a PNP pass transistor controlled by an error amplifier with a bandgap reference, which gives it the lowest possible dropout voltage. The output current capability of the LDO is 200 mA per output and the base drive quiescent current is controlled to prevent oversaturation when the input voltage is low or when the output is overloaded. The integrated current sense feature provides diagnosis and system protection functionality. The current limit of the device is adjustable by resistor connected to CSO pin. Voltage on CSO pin is proportional to output current. The regulator is protected by both current limit and thermal shutdown. Thermal shutdown occurs above 150°C to protect the IC during overloads and extreme ambient temperatures.

Regulator

The error amplifier compares the reference voltage to a sample of the output voltage ($V_{out1,2}$) and drives the base of a PNP series pass transistor via a buffer. The reference is a bandgap design to give it a temperature stable output. Saturation control of the PNP is a function of the load current and input voltage. Oversaturation of the output power device is prevented, and quiescent current in the ground pin is minimized.

Regulator Stability Considerations

The input capacitor (C_{in}) is necessary to stabilize the input impedance to avoid voltage line influences. The output capacitor ($C_{out1,2}$) helps determine three main characteristics of a linear regulator: startup delay, load transient response and loop stability. The capacitor value and type should be based on cost, availability, size and temperature constraints. The aluminum electrolytic capacitor is the least expensive solution, but, if the circuit operates at low temperatures (−25°C to −40°C), both the value and ESR of the capacitor will vary considerably. The capacitor manufacturer's data sheet usually provides this information. The value for the output capacitor $C_{out1,2}$, shown in Figure 1 should work for most applications; see also Figure 16 for output stability at various load and Output Capacitor ESR conditions. Stable region of ESR in Figure 16 shows ESR values at which the LDO output voltage does not have any permanent oscillations at any dynamic changes of output load current. Marginal ESR is the value at which the output voltage waving is fully damped during four periods after the load change and no oscillation is further observable.

ESR characteristics were measured with ceramic capacitors and additional series resistors to emulate ESR. Low duty cycle pulse load current technique has been used to maintain junction temperature close to ambient temperature.

Calculating Bypass Capacitor

If improved stability (reducing output voltage ringing during transients) is demanded, connect the bypass capacitor $C_{b1,2}$ between Adjustable Input pin and $V_{out1,2}$ pin according to Applications circuit at Figure 1. Parallel combination of bypass capacitor $C_{b1,2}$ with the feedback resistor R_{n1} contributes in the device transfer function as an additional zero and affects the device loop stability, therefore its value must be optimized. Attention to the Output Capacitor value and its ESR must be paid. See also Stability in High Speed Linear LDO Regulators Application Note, AND8037/D for more information. Optimal value of bypass capacitor is given by following expression

$$C_{bn} = \frac{1}{2 \times \pi \times f_z \times R_{n1}} (F) \qquad \text{(eq. 1)}$$

where

- R_{n1} the upper feedback resistor
- f_z the frequency of the zero added into the device transfer function by R_{n1} and C_{b1} external components.

Set the R_{n1} resistor according to output voltage requirement. Chose the f_z with regard on the output capacitance $C_{out1,2}$, refer to the table below.

$C_{out1,2}$ (μF)	10	22	47	100
f_Z range (kHz)	max 19	max 19	N/A*	N/A*

NOTE: * For $C_{out1,2}$ = 47 μF and higher, $C_{b1,2}$ capacitors are not needed for stability improvement. $C_{b1,2}$ capacitors are useful for reduction start up overshoot and noise reduction. See electrical characteristic table.

Ceramic capacitors and its part numbers listed bellow have been used as low ESR output capacitors $C_{out1,2}$ from the table above to define the frequency ranges of additional zero required for stability:

GRM31CR71C106KAC7 (10 μF, 16 V, X7R, 1206)
GRM32ER71C226KE18 (22 μF, 16 V, X7R, 1210)
GRM32ER61C476ME15 (47 μF, 16 V, X5R, 1210)
GRM32ER60J107ME20 (100 μF, 6.3 V, X5R, 1210)

Enable Inputs

An enable pin is used to turn a channel on or off. By holding the pin down to a voltage less than 0.99 V, the output of the channel will be turned off. When the voltage on the enable pin is greater than 2.31 V, the output of the channel will be enabled to power its output to the regulated output voltage. The enable pins may be connected directly to the input pin to give constant enable to the output channel.

Share Feedback
Your Opinion Matters

Setting the Output Voltage

The output voltage range can be set between 3.3 V and 20 V. This is accomplished with an external resistor divider feeding back the voltage to the IC back to the error amplifier by the voltage adjust pin ADJ. The internal reference voltage is set to a temperature stable reference (V_{REF1}) of 1.265 V. The output voltage is calculated from the following formula. Ignoring the bias current into the ADJ pin:

$$V_{out_nom_n} = V_{REF1}\left(1 + \frac{R_{n1}}{R_{n2}}\right) \quad \text{(eq. 2)}$$

Use $R_{n2} < 50\ k\Omega$ to avoid significant voltage output errors due to ADJ bias current.

Designers should consider the tolerance of R_{n1} and R_{n2} during the design phase.

Setting the Output Current Limit

The output current limit can be set up to 300 mA by external resistor $R_{CSO1,2}$ (see Figure 1). Capacitor C_{CSO} of 1 μF in parallel with R_{CSO} is required for stability of current limit control circuitry (see Figure 1).

$$V_{CSO1,2} = I_{out1,2}\left(R_{CSO1,2} \times \frac{1}{100}\right) \quad \text{(eq. 3)}$$

$$I_{LIM1,2} = \frac{100}{1} \times \frac{2.55}{R_{CSO1,2}} \quad \text{(eq. 4)}$$

$$R_{CSO1,2} = \frac{100}{1} \times \frac{2.55}{I_{LIM1,2}} \quad \text{(eq. 5)}$$

where

$R_{CSO1,2}$ – current limit setting resistor

$V_{CSO1,2}$ – voltage at CSO pin proportional to $I_{out1,2}$

$I_{LIM1,2}$ – current limit value

$I_{out1,2}$– output current actual value

CSO pin provides information about output current actual value. The CSO voltage is proportional to output current according to Equation 3.

Once output current reaches its limit value ($I_{LIM1,2}$) set by external resistor R_{CSO} than voltage at CSO pin is typically 2.55 V. Calculations of $I_{LIM1,2}$ or $R_{CSO1,2}$ values can be done using Equation 4 and Equation 5, respectively. Minimum and maximum value of Output Current Limit can be calculated according Equation 6 and 7.

$$I_{LIM1,2_min} = RATIO_{min} \times \frac{V_{CSO1,2_min}}{R_{CSO1,2_max}} \quad \text{(eq. 6)}$$

$$I_{LIM1,2_max} = RATIO_{max} \times \frac{V_{CSO1,2_max}}{R_{CSO1,2_min}} \quad \text{(eq. 7)}$$

where

$RATIO_{min}$ – minimum value of Output Current to CSO Current Ratio from electrical characteristics table and particular output current range

$RATIO_{max}$ – maximum value of Output Current to CSO Current Ratio from electrical characteristics table and particular output current range

$V_{CSO1,2_min}$ – minimum value of CSO Voltage Level at Current Limit from electrical characteristics table

$V_{CSO1,2_max}$ – maximum value of CSO Voltage Level at Current Limit from electrical characteristics table

$R_{CSO1,2_min}$ – minimum value of $R_{CSO1,2}$ with respect its accuracy

$R_{CSO1,2_max}$ – maximum value of $R_{CSO1,2}$ with respect its accuracy

Designers should consider the tolerance of $R_{CSO1,2}$ during the design phase.

Diagnostic in OFF State

The NCV47821 contains also circuitry for OFF state diagnostics for Short to Battery (STB) and Open Load (OL). There are internal current sources, Pull−Up and Pull Down resistors which provide additional cost savings for overall application by excluding external components and their assembly cost and saving PCB space and safe control IOs of a Microcontroller Unit (MCU).

Simplified functional schematic and truth table is shown in Figure 19 and related flowchart in Figure 20.



EN	DE	I_{PU}	EF	V_{out}	Diagnostic Status/Action
L	L	OFF	HZ	Unknown	None (Diagnostics OFF)
L	H	OFF	L	$V_{out} > V_{out_OFF}$	Short to Battery (STB)
L	H	OFF	HZ	$V_{out} < V_{out_OFF}$	Check for Open Load (OL)
H	H	ON	L	$V_{out} > V_{out_OFF}$	Open Load (OL)
H	H	ON	HZ	$V_{out} < V_{out_OFF}$	No Failure (V_{out} close to 0 V)

Figure 19. Simplified Functional Diagram of OFF State Diagnostics (STB and OL)

Share Feedback
Your Opinion Matters



Figure 20. Flowchart for Diagnostics in OFF State

The diagnostics in OFF state shall be performed for each channel separately. For diagnostics of Channel 1 the input CS pin has to be put logic low, for diagnostics of Channel 2 the input CS pin has to be put logic high. Corresponding EN pin has to be used for control (EN1 for Channel 1 and EN2 for Channel 2). For detailed information see Diagnostic Features Truth Table in Figure 21.

Diagnostic in ON State

Diagnostic in ON State provides information about Overcurrent or Short to Ground failures, during which the EF output is in logic low state. The diagnostics in ON state shall be performed for each channel separately. For diagnostics of Channel 1 the input CS pin has to be put logic low, for diagnostics of Channel 2 the input CS pin has to be put logic high. For detailed information see Diagnostic Features Truth Table in Figure 21.

Operational Status	EN [13]	DE	CS	Output Voltage (V_{out1} or V_{out2})	Diagnostic Output (CSO1 or CSO2)	Error Flag (EF)
Disabled	L	L	X	Low (~0 V)	Low (~0 V)	HZ
Short to Battery	L	H	L/H [14]	High (V_{out} ~ V_{in})	Low (~0 V)	L [15]
Open Load (OFF)	H	H	L/H [14]	High (V_{out} ~ V_{in})	Low (~0 V)	L [16]
Normal (OFF)	H	H	L/H [14]	Low (~0 V)	Low (~0 V)	HZ [16]
Open Load (ON)	H	L	X	V_{out_nom}	Low (~0 V)	HZ
Normal (ON)	H	L	X	V_{out_nom}	Proportional to I_{out} (±10 %)	HZ
Over Current	H	L	L/H [17]	≤ 90 % of V_{out_nom}	High (~2.55 V)	L
Short to Ground	H	L	L/H [17]	Low (~0 V)	High (~2.55 V)	L

Figure 21. Diagnostic Features Truth Table

13. State of EN pin of appropriate channel
14. CS = L means CH1 diagnostics and CS = H means CH2 diagnostics in OFF state (DE = H) via EF output, appropriate EN pin is used for turning internal switch ON and OFF (e.g. when DE = H and CS = L and EN1 = L then IPU1 is OFF, when DE = H and CS = L and EN1 = H then IPU1 is ON)
15. Internal current source turned OFF (between V_{out} and V_{in} of appropriate channel)
16. Internal current source turned ON (between V_{out} and V_{in} of appropriate channel)
17. CS = L means CH1 diagnostics and CS = H means CH2 diagnostics in ON state (e.g. when CS = L and EF = L then CH1 has Overcurrent or Short to Ground failure, when CS = H and EF = L then CH1 has Overcurrent or Short to Ground failure)

Share Feedback
Your Opinion Matters

Thermal Considerations

As power in the device increases, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and the ambient temperature affect the rate of junction temperature rise for the part. When the device has good thermal conductivity through the PCB, the junction temperature will be relatively low with high power applications. The maximum dissipation the device can handle is given by:

$$P_{D(MAX)} = \frac{\left[T_{J(MAX)} - T_A\right]}{R_{\theta JA}} \quad \text{(eq. 8)}$$

Since T_J is not recommended to exceed 150°C, then the device soldered on 645 mm^2, 1 oz copper area, FR4 can dissipate up to 2.38 W when the ambient temperature (T_A) is 25°C. See Figure 22 for $R_{\theta JA}$ versus PCB area. The power dissipated by the device can be calculated from the following equations:

$$P_D \approx V_{in}\left(I_q @ I_{out1,2}\right) + I_{out1}\left(V_{in} - V_{out1}\right) + I_{out2}\left(V_{in} - V_{out2}\right) \quad \text{(eq. 9)}$$

or

$$V_{in(MAX)} \approx \frac{P_{D(MAX)} + \left(V_{out1} \times I_{out1}\right) + \left(V_{out2} \times I_{out2}\right)}{I_{out1} + I_{out2} + I_q} \quad \text{(eq. 10)}$$



Figure 22. Thermal Resistance vs. PCB Copper Area

Hints

V_{in} and GND printed circuit board traces should be as wide as possible. When the impedance of these traces is high, there is a chance to pick up noise or cause the regulator to malfunction. Place external components, especially the output capacitor, as close as possible to the device and make traces as short as possible.

ORDERING INFORMATION

Device	Output Voltage	Marking	Package	Shipping†
NCV47821PAAJR2G	Adjustable	Line1: NCV4 Line2: 7821	TSSOP−14 Exposed Pad (Pb−Free)	2500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters

TSSOP−14 EP
CASE 948AW
ISSUE C

DATE 09 OCT 2012

SCALE 1:1



TOP VIEW



SIDE VIEW



SECTION B−B
NOTE 8



END VIEW



BOTTOM VIEW



DETAIL A

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE PROTRUSION SHALL BE 0.07 mm MAX. AT MAXIMUM MATERIAL CONDITION. DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT. MINIMUM SPACE BETWEEN PROTRUSION AND ADJACENT LEAD IS 0.07.
4. DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.15 mm PER SIDE. DIMENSION D IS DETERMINED AT DATUM H.
5. DIMENSION E1 DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSIONS. INTERLEAD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.25 mm PER SIDE. DIMENSION E1 IS DETERMINED AT DATUM H.
6. DATUMS A AND B ARE DETERMINED AT DATUM H.
7. A1 IS DEFINED AS THE VERTICAL DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.
8. SECTION B−B TO BE DETERMINED AT 0.10 TO 0.25 mm FROM THE LEAD TIP.

	MILLIMETERS	
DIM	MIN	MAX
A	----	1.20
A1	0.05	0.15
A2	0.80	1.05
b	0.19	0.30
b1	0.19	0.25
c	0.09	0.20
c1	0.09	0.16
D	4.90	5.10
D2	3.09	3.62
E	6.40 BSC	
E1	4.30	4.50
E2	2.69	3.22
e	0.65 BSC	
L	0.45	0.75
L2	0.25 BSC	
M	0 °	8 °

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

DOCUMENT NUMBER:	**98AON66474E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**TSSOP−14 EP, 5.0X4.4**		**PAGE 1 OF 1**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales