Bipolar Transistor (–)50 V, (–)3 A, Low V_{CE}(sat), (PNP)NPN Single

NSVS50030SB3, NSVS50031SB3

This device is bipolar junction transistor featuring high current, low saturation voltage, and high speed switching.

Suitable for motor driver, relay driver, DC–DC converter of automotive applications. AEC–Q101qualified and PPAP capable.

Features

- Large Current Capacitance
- Low Collector to Emitter Saturation Voltage
- High–Speed Switching
- High Allowable Power Dissipation
- AEC–Q101Qualified and PPAP Capable
- Pb–Free, Halogen Free and RoHS Compliance
- Ultra Small Package Facilitates Miniaturization in End Products (Mounting Height: 0.9 mm)

Typical Applications

- DC / DC Converter
- Relay Drivers, Lamp Drivers, Motor Drivers
- Camera Flash

Specifications

ABSOLUTE MAXIMUM RATINGS at T_A = 25°C

Parameter	Symbol	Value	Unit
Collector to Base Voltage	V_{CBO}	(–50) 100	V
Collector to Emitter Voltage	V_{CES}	(–50) 100	V
Collector to Emitter Voltage	V_{CEO}	(–)50	V
Emitter to Base Voltage	V_{EBO}	(–)6	V
Collector Current	I_C	(–)3	A
Collector Current (Pulse)	I_{CP}	(–)6	A
Base Current	I_B	(–)600	mA
Collector Dissipation (Note 1)	P_C	1.1	W
Junction Temperature	Tj	175	°C
Storage Temperature	Tstg	–55 to +175	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Surface mounted on ceramic substrate. (600 mm^2 x 0.8 mm)

ELECTRICAL CONNECTION



NSVS50030SB3 NSVS50031SB3



CPH3
CASE 318BA

MARKING DIAGRAMS



XXX = HAE: NSVS50030SB3
= HCE: NSVS50031SB3
M = Single Digit Date Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2017

ORDERING INFORMATION

Device	Marking	Package	Shipping (Qty / Packing) †
NSVS50030SB3T1G	HAE	CPH3 (Pb−Free / Halogen Free)	3,000/ Tape & Reel
NSVS50031SB3T1G	HCE		

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted)

Parameter	Symbol	Conditions	Value			Unit
			Min	Typ	Max	
Collector Cutoff Current	I_{CBO}	V_{CB} = (−)40 V, I_E = 0 A			(−)1	μA
Emitter Cutoff Current	I_{EBO}	V_{EB} = (−)4 V, I_C = 0 A			(−)1	μA
DC Current Gain	h_{FE}	V_{CE} = (−)2 V, I_C = (−)100 mA	200		560	
Gain−Bandwidth Product	f_T	V_{CE} = (−)10 V, I_C = (−)500 mA		(360) 380		MHz
Output Capacitance	Cob	V_{CB} = (−)10 V, f = 1 MHz		(24) 13		pF
Collector to Emitter Saturation Voltage	V_{CE}(sat)	I_C = (−)1 A, I_B = (−)50 mA		(−100) 80	(−200) 120	mV
		I_C = (−)2 A, I_B = (−)100 mA		(−185) 140	(−500) 210	mV
Base to Emitter Saturation Voltage	V_{BE}(sat)	I_C = (−)2 A, I_B = (−)100 mA		(−)0.88	(−)1.2	V
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	I_C = (−)10 μA, I_E = 0 A	(−50) 100			V
Collector to Emitter Breakdown Voltage	$V_{(BR)CES}$	I_C = (−)100 μA, R_{BE} = 0 Ω	(−50) 100			V
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	I_C = (−)1 mA, R_{BE} = ∞	(−)50			V
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	I_E = (−)10 μA, I_C = 0 A	(−)6			V
Turn−On Time	t_{on}	See Fig.1		(30) 35		ns
Storage Time	t_{stg}			(230) 300		ns
Fall Time	t_f			(15) 22		ns

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.



Figure 1. Switching Time Test Circuit

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 2. I_C − V_{CE}



Figure 3. I_C − V_{CE}



Figure 4. I_C − V_{BE}



Figure 5. I_C − V_{BE}



Figure 6. h_{FE} − I_C



Figure 7. h_{FE} − I_C

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)



Figure 8. f_T – I_C



Figure 9. f_T – I_C



Figure 10. Cob – V_{CB}



Figure 11. Cob – V_{CB}



Figure 12. V_{CE}(sat) – I_C



Figure 13. V_{CE}(sat) – I_C

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)



Figure 14. $V_{CE}(sat) - I_C$



Figure 15. $V_{CE}(sat) - I_C$



Figure 16. $V_{BE}(sat) - I_C$



Figure 17. $V_{BE}(sat) - I_C$



Figure 18. ASO



Figure 19. $P_C - T_A$

CPH3
CASE 318BA
ISSUE O

DATE 30 NOV 2011



DOCUMENT NUMBER:	**98AON65437E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**CPH3**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales