MOSFET – Power, Complementary, WDFN 2X2 mm

20 V/-20 V, 4.6 A/-4.1 A

NTLJD3119C

$V_{(BR)DSS}$	$R_{DS(on)}$ MAX	I_D MAX
N−Channel 20 V	65 mΩ @ 4.5 V	3.8 A
	85 mΩ @ 2.5 V	2.0 A
	120 mΩ @ 1.8 V	1.7 A
P−Channel −20 V	100 mΩ @ −4.5 V	−4.1 A
	135 mΩ @ −2.5 V	−2.0 A
	200 mΩ @ −1.8 V	−1.6 A

Features

- Complementary N−Channel and P−Channel MOSFET
- WDFN Package with Exposed Drain Pad for Excellent Thermal Conduction
- Footprint Same as SC−88 Package
- Leading Edge Trench Technology for Low On Resistance
- 1.8 V Gate Threshold Voltage
- Low Profile (< 0.8 mm) for Easy Fit in Thin Environments
- This is a Pb−Free Device

Applications

- Synchronous DC−DC Conversion Circuits
- Load/Power Management of Portable Devices like PDA's, Cellular Phones and Hard Drives
- Color Display and Camera Flash Regulators



WDFN6
CASE 506AN

MARKING DIAGRAM



JM = Specific Device Code
M = Date Code
▪ = Pb−Free Package
(Note: Microdot may be in either location)

PIN CONNECTIONS



(Top View)

ORDERING INFORMATION

Device	Package	Shipping†
NTLJD3119CTBG	WDFN6 (Pb−Free)	3000/Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2016

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter			Symbol	Value	Unit
Drain−to−Source Voltage		N−Ch	V_{DSS}	20	V
		P−Ch		−20	
Gate−to−Source Voltage		N−Ch	V_{GS}	±8.0	V
		P−Ch			
N−Channel Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	3.8	A
		T_A = 85°C		2.8	
	t ≤ 5 s	T_A = 25°C		4.6	
P−Channel Continuous Drain Current (Note 1)	Steady State	T_A = 25°C	I_D	−3.3	A
		T_A = 85°C		−2.4	
	t ≤ 5 s	T_A = 25°C		−4.1	
Power Dissipation (Note 1)	Steady State	T_A = 25°C	P_D	1.5	W
	t ≤ 5 s			2.3	
N−Channel Continuous Drain Current (Note 2)	Steady State	T_A = 25°C	I_D	2.6	A
		T_A = 85°C		1.9	
P−Channel Continuous Drain Current (Note 2)	Steady State	T_A = 25°C	I_D	−2.3	A
		T_A = 85°C		−1.6	
Power Dissipation (Note 2)	Steady State	T_A = 25°C	P_D	0.71	W
Pulsed Drain Current	N−Ch	t_p = 10 μs	I_{DM}	18	A
	P−Ch			−20	
Operating Junction and Storage Temperature			T_J, T_{STG}	−55 to 150	°C
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)			T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Surface Mounted on FR4 Board using 1 in sq pad size (Cu area = 1.127 in sq [2 oz] including traces).
2. Surface Mounted on FR4 Board using the minimum recommended pad size of 30 mm^2, 2 oz Cu.

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
SINGLE OPERATION (SELF−HEATED)			
Junction−to−Ambient – Steady State (Note 3)	$R_{\theta JA}$	83	°C/W
Junction−to−Ambient – Steady State Min Pad (Note 4)	$R_{\theta JA}$	177	
Junction−to−Ambient – t ≤ 5 s (Note 3)	$R_{\theta JA}$	54	
DUAL OPERATION (EQUALLY HEATED)			
Junction−to−Ambient – Steady State (Note 3)	$R_{\theta JA}$	58	°C/W
Junction−to−Ambient – Steady State Min Pad (Note 4)	$R_{\theta JA}$	133	
Junction−to−Ambient – t ≤ 5 s (Note 3)	$R_{\theta JA}$	40	

3. Surface Mounted on FR4 Board using 1 in sq pad size (Cu area = 1.127 in sq [2 oz] including traces).
4. Surface Mounted on FR4 Board using the minimum recommended pad size (30 mm^2, 2 oz Cu).

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	N/P	Test Conditions		Min	Typ	Max	Unit
OFF CHARACTERISTICS								
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	N	V_{GS} = 0 V	I_D = 250 μA	20			V
		P		I_D = −250 μA	−20			
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}/T_J$	N				10.4		mV/°C
		P				9.95		
Zero Gate Voltage Drain Current	I_{DSS}	N	V_{GS} = 0 V, V_{DS} = 16 V	T_J = 25 °C			1.0	μA
		P	V_{GS} = 0 V, V_{DS} = −16 V				−1.0	
		N	V_{GS} = 0 V, V_{DS} = 16 V	T_J = 85 °C			10	
		P	V_{GS} = 0 V, V_{DS} = −16 V				−10	
Gate−to−Source Leakage Current	I_{GSS}	N	V_{DS} = 0 V, V_{GS} = ±8.0 V				±100	nA
		P	V_{DS} = 0 V, V_{GS} = ±8.0 V				±100	
ON CHARACTERISTICS (Note 5)								
Gate Threshold Voltage	$V_{GS(TH)}$	N	V_{GS} = V_{DS}	I_D = 250 μA	0.4	0.7	1.0	V
		P		I_D = −250 μA	−0.4	−0.7	−1.0	
Gate Threshold Temperature Coefficient	$V_{GS(TH)}/T_J$	N				−3.0		mV/°C
		P				2.44		
Drain−to−Source On Resistance	$R_{DS(on)}$	N	V_{GS} = 4.5 V , I_D = 3.8 A			37	65	mΩ
		P	V_{GS} = −4.5 V , I_D = −4.1 A			75	100	
		N	V_{GS} = 2.5 V , I_D = 2.0 A			46	85	
		P	V_{GS} = −2.5 V, I_D = −2.0 A			101	135	
		N	V_{GS} = 1.8 V , I_D = 1.7 A			65	120	
		P	V_{GS} = −1.8 V, I_D = −1.6 A			150	200	
Forward Transconductance	g_{FS}	N	V_{DS} = 10 V, I_D = 1.7 A			4.2		S
		P	V_{DS} = −5.0 V , I_D = −2.0 A			3.1		
CHARGES, CAPACITANCES AND GATE RESISTANCE								
Input Capacitance	C_{ISS}	N	f = 1.0 MHz, V_{GS} = 0 V	V_{DS} = 10 V		271		pF
		P		V_{DS} = −10 V		531		
Output Capacitance	C_{OSS}	N		V_{DS} = 10 V		72		
		P		V_{DS} = −10 V		91		
Reverse Transfer Capacitance	C_{RSS}	N		V_{DS} = 10 V		43		
		P		V_{DS} = −10 V		56		
Total Gate Charge	$Q_{G(TOT)}$	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 3.8 A			3.7		nC
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −2.0 A			5.5		
Threshold Gate Charge	$Q_{G(TH)}$	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 3.8 A			0.3		
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −2.0 A			0.7		
Gate−to−Source Charge	Q_{GS}	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 3.8 A			0.6		
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −2.0 A			1.0		
Gate−to−Drain Charge	Q_{GD}	N	V_{GS} = 4.5 V, V_{DS} = 10 V, I_D = 3.8 A			1.0		
		P	V_{GS} = −4.5 V, V_{DS} = −10 V, I_D = −2.0 A			1.4		

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	N/P	Test Conditions		Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS (Note 6)								
Turn−On Delay Time	$t_{d(ON)}$	N	V_{GS} = 4.5 V, V_{DD} = 16 V, I_D = 1.0 A, R_G = 2.0 Ω			3.8		ns
Rise Time	t_r					4.7		
Turn−Off Delay Time	$t_{d(OFF)}$					11.1		
Fall Time	t_f					5.8		
Turn−On Delay Time	$t_{d(ON)}$	P	V_{GS} = −4.5 V, V_{DD} = −10 V, I_D = −2.0 A, R_G = 2.0 Ω			5.2		
Rise Time	t_r					13.2		
Turn−Off Delay Time	$t_{d(OFF)}$					13.7		
Fall Time	t_f					19.1		
DRAIN−SOURCE DIODE CHARACTERISTICS								
Forward Diode Voltage	V_{SD}	N	V_{GS} = 0 V, T_J = 25 °C	I_S = 1.0 A		0.69	1.0	V
		P		I_S = −1.0 A		−0.75	−1.0	
		N	V_{GS} = 0 V, T_J = 125 °C	I_S = 1.0 A		0.52		
		P		I_S = −1.0 A		−0.64		
Reverse Recovery Time	t_{RR}	N	V_{GS} = 0 V, dI_S / dt = 100 A/μs	I_S = 1.0 A		10.2		ns
		P		I_S = −1.0 A		16.2		
Charge Time	t_a	N		I_S = 1.0 A		6.0		
		P		I_S = −1.0 A		10.6		
Discharge Time	t_b	N		I_S = 1.0 A		4.2		
		P		I_S = −1.0 A		5.6		
Reverse Recovery Charge	Q_{RR}	N		I_S = 1.0 A		3.0		nC
		P		I_S = −1.0 A		5.7		

5. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%.
6. Switching characteristics are independent of operating junction temperatures.

TYPICAL PERFORMANCE CURVES – N–CHANNEL (T_J = 25°C unless otherwise noted)



Figure 1. On–Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On–Resistance versus Drain Current



Figure 4. On–Resistance versus Drain Current and Gate Voltage



Figure 5. On–Resistance Variation with Temperature



Figure 6. Drain–to–Source Leakage Current versus Voltage

TYPICAL PERFORMANCE CURVES – N–CHANNEL (T_J = 25°C unless otherwise noted)



Figure 7. Capacitance Variation



Figure 8. Gate–To–Source and Drain–To–Source Voltage versus Total Charge



Figure 9. Resistive Switching Time Variation versus Gate Resistance



Figure 10. Diode Forward Voltage versus Current

TYPICAL PERFORMANCE CURVES – P–CHANNEL (T_J = 25°C unless otherwise noted)



Figure 11. On–Region Characteristics



Figure 12. Transfer Characteristics



Figure 13. On–Resistance versus Drain Current



Figure 14. On–Resistance versus Drain Current and Gate Voltage



Figure 15. On–Resistance Variation with Temperature



Figure 16. Drain–to–Source Leakage Current versus Voltage

TYPICAL PERFORMANCE CURVES – P–CHANNEL (T_J = 25°C unless otherwise noted)



Figure 17. Capacitance Variation



Figure 18. Gate–To–Source and Drain–To–Source Voltage versus Total Charge



Figure 19. Resistive Switching Time Variation versus Gate Resistance



Figure 20. Diode Forward Voltage versus Current



Figure 21. Maximum Rated Forward Biased Safe Operating Area

TYPICAL PERFORMANCE CURVES (T_J = 25°C unless otherwise noted)



Figure 22. Thermal Response



WDFN6 2x2, 0.65P
CASE 506AN
ISSUE H

DATE 25 JAN 2022



TOP VIEW

DETAIL A
OPTIONAL CONSTRUCTIONS

NOTES:

1. DIMENSIONING AND TOLERANCING PER. ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.



SIDE VIEW



DETAIL B
OPTIONAL CONSTRUCTIONS

DIM	MILLIMETERS MIN.	MAX.
A	0.70	0.80
A1	0.00	0.05
A3	0.20 REF	
b	0.25	0.35
D	2.00 BSC	
D2	0.57	0.77
E	2.00 BSC	
E2	0.90	1.10
e	0.65 BSC	
F	0.95 BSC	
k	0.25 REF	
L	0.20	0.30
L1	---	0.10



BOTTOM VIEW



RECOMMENDED
MOUNTING FOOTPRINT
SOLDERMASK DEFINED

GENERIC MARKING DIAGRAM*

XX = Specific Device Code
M = Date Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	98AON20861D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	WDFN6 2x2, 0.65P	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales