MOSFET - Power, Single N-Channel, SO8-FL
40 V, 0.42 mΩ, 509 A

NTMFS0D4N04XM

$V_{(BR)DSS}$	$R_{DS(on)}$ MAX	I_D MAX
40 V	0.42 mΩ @ 10 V	509 A

Features
- Low $R_{DS(on)}$ to Minimize Conduction Losses
- Low Capacitance to Minimize Driver Losses
- Small Footprint (5x6 mm) with Compact Design
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications
- Motor Drive
- Battery Protection
- ORing



N−CHANNEL MOSFET



DFN5 (SO8−FL)
CASE 506FA

MARKING DIAGRAM

0D4N4 = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
ZZ = Lot Traceability

ORDERING INFORMATION
See detailed ordering, marking and shipping information on page 2 of this data sheet.

MAXIMUM RATINGS (T_J = 25°C unless otherwise stated)

Parameter		Symbol	Value	Unit
Drain−to−Source Voltage		V_{DSS}	40	V
Gate−to−Source Voltage	DC	V_{GS}	±20	V
Continuous Drain Current	T_C = 25°C	I_D	509	A
	T_C = 100°C		360	
Power Dissipation	T_C = 25°C	P_D	197	W
Pulsed Drain Current	T_C = 25°C, t_p = 10 μs	I_{DM}	4044	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	−55 to +175	°C
Source Current (Body Diode)		I_S	202	A
Single Pulse Avalanche Energy	I_{PK} = 38.6 A	E_{AS}	2396	mJ
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)		T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case (Note 2)	$R_{\theta JC}$	0.76	°C/W
Thermal Resistance, Junction−to−Ambient (Notes 1, 2)	$R_{\theta JA}$	38.2	

1. Surface−mounted on FR4 board using 650 mm^2, 2 oz Cu pad.
2. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.

© Semiconductor Components Industries, LLC, 2022

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 250 μA, T_J = 25°C	40			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$\Delta V_{(BR)DSS}/\Delta T_J$	I_D = 250 μA, Referenced to 25°C		14.9		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 40 V, T_J = 25°C			10	μA
		V_{DS} = 40 V, T_J = 125°C			100	
Gate−to−Source Leakage Current	I_{GSS}	V_{GS} = 20 V, V_{DS} = 0 V			100	nA
ON CHARACTERISTICS						
Drain−to−Source On Resistance	$R_{DS(ON)}$	V_{GS} = 10 V, I_D = 50 A, T_J = 25°C		0.33	0.42	mΩ
Gate Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = 330 μA, T_J = 25°C	2.5	3	3.5	V
Gate Threshold Voltage Temperature Coefficient	$\Delta V_{GS(TH)}/\Delta T_J$	V_{GS} = V_{DS}, I_D = 330 μA		−7.21		mV/°C
Forward Trans−conductance	g_{FS}	V_{DS} = 5 V, I_D = 50 A		286		S
CHARGES, CAPACITANCES & GATE RESISTANCE						
Input Capacitance	C_{ISS}	V_{DS} = 20 V, V_{GS} = 0 V, f = 1 MHz		8577		pF
Output Capacitance	C_{OSS}			6090		
Reverse Transfer Capacitance	C_{RSS}			120		
Output Charge	Q_{OSS}	V_{DD} = 20 V, I_D = 50 A, V_{GS} = 10 V		183		nC
Total Gate Charge	$Q_{G(TOT)}$			133		
Threshold Gate Charge	$Q_{G(TH)}$			25.2		
Gate−to−Source Charge	Q_{GS}			37.2		
Gate−to−Drain Charge	Q_{GD}			24.2		
Gate Resistance	R_G	f = 1 MHz		0.42		Ω
SWITCHING CHARACTERISTICS						
Turn−On Delay Time	$t_{d(ON)}$	Resistive Load, V_{GS} = 0/10 V, V_{DD} = 20 V, I_D = 50 A, R_G = 0 Ω		34.5		ns
Rise Time	t_r			11.1		
Turn−Off Delay Time	$t_{d(OFF)}$			49.4		
Fall Time	t_f			13		
SOURCE−TO−DRAIN DIODE CHARACTERISTICS						
Forward Diode Voltage	V_{SD}	I_S = 50 A, V_{GS} = 0 V, T_J = 25°C		0.79	1.2	V
		I_S = 50 A, V_{GS} = 0 V, T_J = 125°C		0.63		
Reverse Recovery Time	t_{RR}	V_{GS} = 0 V, I_S = 50 A, dI/dt = 100 A/μs, V_{DD} = 20 V		94.4		ns
Charge Time	t_a			55.3		
Discharge Time	t_b			39.1		
Reverse Recovery Charge	Q_{RR}			316		nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

DEVICE ORDERING INFORMATION

Device	Marking	Package	Shipping†
NTMFS0D4N04XMT1G	0D4N4	DFN5 (Pb−Free)	1500 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate Voltage



Figure 4. On−Resistance vs. Drain Current



Figure 5. Normalized ON Resistance vs. Junction Temperature



Figure 6. Drain to Source Voltage vs Drain Leakage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS (CONTINUED)



Figure 7. Capacitance Characteristics



Figure 8. Gate Charge Characteristics



Figure 9. Resistive Switching Time Variation vs. Gate Resistance



Figure 10. Diode Forward Characteristics



Figure 11. Safe Operating Area (SOA)



Figure 12. Avalanche Current vs. Pulse Time (UIS)

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS (CONTINUED)



Figure 13. Thermal Response

Share Feedback
Your Opinion Matters



DFN−5 5.00x5.90x1.00, 1.27P
CASE 506FA
ISSUE B

DATE 10 SEP 2026







NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSIONS D1 AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.





MILLIMETERS			
DIM	MIN	NOM	MAX
A	0.90	1.00	1.10
A1	0.00	−−−	0.05
b	0.33	0.41	0.51
c	0.23	0.28	0.33
D	5.00	5.15	5.30
D1	4.80	5.00	5.20
D2	3.90	4.10	4.30
E	6.00	6.15	6.30
E1	5.70	5.90	6.10
E2	3.55	3.75	3.95
e	1.27 BSC		
G	0.50	0.55	0.70
G1	0.26	0.36	0.46
k	1.10	1.25	1.40
L	0.50	0.60	0.70
L1	0.150 REF		
M	3.00	3.40	3.80
Θ	0°	−−−	12°



RECOMMENDED MOUNTING FOOTPRINT

*For additional information on our Pb−Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*

XXXX = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON21323H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**DFN−5 5.00x5.90x1.00, 1.27P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales