

# MOSFET – Power, N-Channel

100 V, 1.4 mΩ

## NVCR4LS1D4N10MCA

### Features

- Typical  $R_{DS(on)}$  = 1.1 mΩ at  $V_{GS} = 10$  V
- Typical  $Q_{g(tot)}$  = 131 nC at  $V_{GS} = 10$  V
- AEC-Q101 Qualified
- RoHS Compliant

### DIMENSION (μm)

Die Size	7080 × 4515
Die Size (Sawn)	7060 ±15 × 4495 ±15
Source Attach Area	(6508 × 2055.6) × 2
Gate Attach Area	330 × 600
Die Thickness	101.6 ±19.1

Gate and Source: AlSiCu  
 Drain: Ti-NiV-Ag (back side of die)  
 Passivation: Polyimide  
 Wafer Diameter: 8 inch  
 Wafer Sawn on UV Tape  
 Bad Dice Identified in Inking  
 Gross Die Counts: 765

The Chip is 100% Probed to Meet the Conditions and Limits Specified at  $T_J = 25^\circ\text{C}$ .

Symbol	Parameter	Condition	Min	Typ	Max	Unit
$BV_{DSS}$	Drain to Source Breakdown Voltage	$I_D = 250 \mu\text{A}, V_{GS} = 0 \text{ V}$	100	-	-	V
$I_{DSS}$	Drain to Source Leakage Current	$V_{DS} = 100 \text{ V}, V_{GS} = 0 \text{ V}$	-	-	10	μA
$I_{GSS}$	Gate to Source Leakage Current	$V_{GS} = \pm 20 \text{ V}, V_{DS} = 0 \text{ V}$	-	-	±100	nA
$V_{GS(th)}$	Gate to Source Threshold Voltage	$V_{GS} = V_{DS}, I_D = 799 \mu\text{A}$	2.0	-	4.0	V
* $R_{DS(on)}$	Bare Die Drain to Source On Resistance	$I_D = 40 \text{ A}, V_{GS} = 10 \text{ V}$	-	1.1	1.4	mΩ
* $V_{SD}$	Source to Drain Diode Voltage	$I_{SD} = 40 \text{ A}, V_{GS} = 0 \text{ V}$	-	-	1.3	V
$E_{AS}$	Single Pulse Drain-to-Source Avalanche Energy	$L = 0.3 \text{ mH}, I_{AS} = 65 \text{ A}$	633	-	-	mJ

\*Accurate  $R_{DS(on)}$ ,  $V_{SD}$  test at die level is not feasible as limited by the test contact precision attainable in a die form. The max  $R_{DS(on)}$ ,  $V_{SD}$  specification is defined from the historical performance of the die in package but is not guaranteed by test in production. The die  $R_{DS(on)}$  performance depends on the Source wire/ribbon bonding layout.



### ORDERING INFORMATION

Device	Package
NVCR4LS1D4N10MCA	Wafer Sawn on Foil

### RECOMMENDED STORAGE CONDITIONS

Temperature	22 to 28°C
RH	40 to 66%

# NVCR4LS1D4N10MCA

**MOSFET MAXIMUM RATINGS** in Reference to the NVBLS1D5N10MC electrical data in TOLL  
( $T_J = 25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Ratings	Unit
$V_{DSS}$	Drain to Source Voltage	100	V
$V_{GS}$	Gate to Source Voltage	$\pm 20$	V
$I_D$	Continuous Drain Current $R_{\theta JC}$ ( $V_{GS} = 10$ ) (Note 1) $T_C = 25^\circ\text{C}$ $T_C = 100^\circ\text{C}$	300 214	A
$E_{AS}$	Single Pulse Avalanche Energy (Note 2)	633	mJ
$P_D$	Power Dissipation $R_{\theta JC}$	331	W
	Derate Above $25^\circ\text{C}$	2.2	W/ $^\circ\text{C}$
$T_J, T_{STG}$	Operating and Storage Temperature	$-55$ to $+175$	$^\circ\text{C}$
$R_{\theta JC}$	Thermal Resistance, Junction to Case	0.45	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Maximum Thermal Resistance, Junction to Ambient (Note 3)	33	$^\circ\text{C}/\text{W}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

- Current is limited by silicon.
- Starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.3$  mH,  $I_{AS} = 65$  A,  $V_{DD} = 100$  V during inductor charging and  $V_{DD} = 0$  V during time in avalanche.
- $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance, where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design, while  $R_{\theta JA}$  is determined by the board design. The maximum rating presented here is based on mounting on a  $650$  mm<sup>2</sup> pad of 2oz copper.

**ELECTRICAL CHARACTERISTICS** in Reference to the NVBLS1D5N10MC electrical data in TOLL  
( $T_J = 25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
--------	-----------	-----------------	------	------	------	------

### OFF CHARACTERISTICS

$BV_{DSS}$	Drain to Source Breakdown Voltage	$I_D = 250$ $\mu\text{A}$ , $V_{GS} = 0$ V	100	–	–	V
$I_{DSS}$	Drain to Source Leakage Current	$V_{DS} = 100$ V, $V_{GS} = 0$ V	–	–	10	$\mu\text{A}$
$I_{GSS}$	Gate to Source Leakage Current	$V_{GS} = \pm 20$ V	–	–	$\pm 100$	nA

### ON CHARACTERISTICS

$V_{GS(th)}$	Gate to Source Threshold Voltage	$V_{GS} = V_{DS}$ , $I_D = 799$ $\mu\text{A}$	2.0	–	4.0	V
$R_{DS(on)}$	Drain to Source on Resistance	$I_D = 80$ A, $V_{GS} = 10$ V	–	1.2	1.5	m $\Omega$

### DYNAMIC CHARACTERISTICS

$C_{iss}$	Input Capacitance	$V_{DS} = 50$ V, $V_{GS} = 0$ V, $f = 1$ MHz	–	10100	–	pF
$C_{oss}$	Output Capacitance		–	5100	–	pF
$C_{rss}$	Reverse Transfer Capacitance		–	84	–	pF
$Q_{g(ToT)}$	Total Gate Charge	$V_{GS} = 10$ V, $V_{DS} = 50$ V, $I_D = 80$ A	–	131	–	nC
$Q_{g(th)}$	Threshold Gate Charge		–	25	–	nC
$Q_{gs}$	Gate to Source Gate Charge		–	49	–	nC
$Q_{gd}$	Gate to Drain "Miller" Charge		–	21	–	nC

### SWITCHING CHARACTERISTICS

$t_{d(on)}$	Turn-On Delay	$V_{DS} = 50$ V, $I_D = 80$ A, $V_G = 10$ V, $R_G = 6$ $\Omega$	–	39	–	ns
$t_r$	Rise Time		–	71	–	ns
$t_{d(off)}$	Turn-Off Delay		–	83	–	ns
$t_f$	Fall Time		–	90	–	ns

### DRAIN-SOURCE DIODE CHARACTERISTIC

$V_{SD}$	Source to Drain Diode Voltage	$I_{SD} = 80$ A, $V_{GS} = 0$ V	–	–	1.3	V
$t_{rr}$	Reverse Recovery Time	$I_F = 71$ A, $dI_{SD}/dt = 100$ A/ $\mu\text{s}$	–	110	–	ns
$Q_{rr}$	Reverse Recovery Charge		–	143	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

# NVCR4LS1D4N10MCA

## TYPICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

# NVCR4LS1D4N10MCA

## TYPICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source Voltage vs. Total Charge




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Voltage vs. Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area




Figure 12. Maximum Drain Current vs. Time in Avalanche

# NVCR4LS1D4N10MCA

## TYPICAL CHARACTERISTICS




Figure 13. Transient Thermal Impedance

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)