NB4N121KMNGEVB Evaluation Board User's Manual

Board Name: NB4N121KMNGEVB Device Name: NB4N121KMN



ON Semiconductor®

http://onsemi.com

EVAL BOARD USER'S MANUAL

Description

The NB4N121K Evaluation Board was designed to provide a flexible and convenient platform to quickly evaluate, characterize and verify the performance and operation of the device under test NB4N121K.

The NB4N121K is a Clock differential input fanout distribution device with 1 to 21 HCSL level differential outputs, optimized for ultra low propagation delay variation. The NB4N121K is designed with HCSL clock distribution for FBDIMM applications in mind. Inputs can accept differential LVPECL, CML, or LVDS levels. Single-ended LVPECL, CML, LVCMOS or LVTTL levels are accepted with the proper V_{REFAC} supply. Clock input pins incorporate an internal 50 Ω on die termination resistors. Output drive current at IREF (Pin 1) for 1X load is selected by connecting a 0 k Ω to 1 k Ω external resistor to GND. To drive a 2X load, connect the I_{REF} Pin 1 through 20 k Ω to 50 $k\Omega$ external resistors. The NB4N121K specifically guarantees low output-to-output skews. Optimal design, layout, and processing minimize skew within a device and from device to device. System designers can take advantage of the NB4N121K's performance to distribute low skew clocks across the backplane or the motherboard. The device is packaged in a low profile 8 x 8 mm 52-pin QFN package.

This user's manual provides detailed information on the board's contents, layout and use. The manual should be used in conjunction with the NB4N121K data sheet which contains full technical details on device specifications and operation.

Board Features

- Fully assembled evaluation board with Device–Under– Test (DUT) soldered mounted. The device may be demounted and replaced by a test fixture socket (ANTARES Test Technology, P/N FP0052QN0805C, 3350 Scott Blvd., Bldg 58, Santa Clara, CA 95054, Phone: (408) 988–6800, www.antares–att.com,) for manual insertion of different sample device units.
- Accommodates the electrical characterization of the NB4N121K in the QFN52 package
- Equal length input and output data lines to minimize skew measurement calibration.
- Default 1X output drive (50 Ω load) with optional 2X load capability (25 Ω load) selectable by installing pulldown resistors and adjusting board R_{REF} setting on I_{REF} (pin1). Adjustable R_{REF} resistor potentiometer for fine tuning output drive current (amplitude) levels.
- Single + 3.3 V Operation for direct LOW Impedance probe connection (50 Ω to GND).
- Appendix 1: Device Information

Appendix 2: Schematics

Appendix 3: IREF Pin Load Plot

Appendix 4: Bill of Materials, Board Stackup

Board Map





V_{CC} and GND Supply Connections





Front Notes:

- 1. V_{CCO} and V_{CC} contacts must be ganged and connected together to the positive 3.3 V supply.
- 2. CLK_{SEL} is not used (no SMA).

Back Notes:

- 1. C2 and C3 are power supply caps
- 2. R_{REF} trimpot is connected from I_{REF} to GND to select output drive for 1X (0 to 1 k Ω ; Short to GND) or 2X loading (20 K to 50 k Ω ; Open or Short to V_{CC}). See Appendix 3: Device I_{REF} pin 1 load plot of R_{REF} vs. I_{REF} current

C2 and C3 Power Supply Caps



Figure 2. Back

3. Back D.U.T. area detail: (See Figure 3) Odd numbered resistors R17 to R81 are populated for 1X load. Even numbered resistors are not populated. The even numbered resistors may be repopulated with 50 Ω (to GND) components to convert the board to 2X load use with 50 Ω scope input impedance loading (presents a 25 Ω parallel load to the device outputs). Even numbered "series shorting" resistors R17 to R81 are populated zero ohm value. These may be repopulated with a series resistor value to improve signal integrity. Components C1, C4, C5, C6, and C7 are 0.01 µF bypass caps.



Figure 3. Back D.U.T. Area Detail

Test and Measurements Setup Details:

Step 1: Basic Equipment

- Signal Generator
- Oscilloscope
- Power Supply

- Voltmeter
- Matched High–Speed Coax Cables with SMA Connectors

Step 2: Board Test Connections Setup: (1X Load configuration, I_{REF} pin shorted to GND)



Figure 4. NB4N121KMNGEVB Evaluation Board Connector Configuration

Table 1. Power Supply Connections

Positive and GND supplies must be connected to anvil clips for proper operation. Bridge V_{CC} and V_{CCO} board connection together.

Board Connector Pin	Supply	Value	Device Pin
V _{CC} , V _{CCO} (Note 1)	V _{CC}	3.0 to 3.6 V	7, 26, 39, 52
GND	GND	0 V	2
I _{REF} (Note 2) R _{REF} to GND		For 1x loading: 0 to 50 k Ω For 2x loading: 20 K to 50 k Ω	1
EXPOSED PAD Vias	GND	Thermal Conduit	Exposed Pad

1. Short together and connect to V_{CC} supply. See Appendix 4: Board Lamination Stackup

2. See Appendix 3: Device I_{REF} pin 1 Load Plot of R_{REF} vs. I_{REF} Current

Board Connector	Device Pin Name	Device Pin	
VTCLK	VTCLK	3	
CLK	CLK	4	
CLK	CLK	5	
VTCLK	VTCLK	6	
Q20	Q20	8	
Q20	Q20	9	
Q19	Q19	10	
Q19	Q19	11	
Q18	Q18	12	
Q19	Q19	13	
Q17	Q17	14	
Q17	Q17	15	
Q16	Q16	16	
Q16	Q16	17	
Q15	Q15	18	
Q15	Q15	19	
Q14	Q14	20	
Q14	Q14	21	
Q13	Q13	22	
Q13	Q13	23	
Q12	Q12	24	
Q12	Q12	25	
Q11	Q11	27	
Q11	Q11	28	
Q10	Q10	29	
Q10	Q10	30	
Q9	<u>Q9</u>	31	
Q9	Q9	32	
<u>Q8</u>	<u>Q</u> 8	33	
Q8	Q8	34	
Q7	<u>Q7</u>	35	
Q7	Q7	36	
<u>Q6</u>	<u>Q6</u>	37	
Q6	Q6	38	
Q5	Q5	40	
Q5	Q5	41	
<u>Q4</u>	<u>Q</u> 4	42	
Q4	Q4	43	
Q3	<u>Q</u> 3	44	
Q3	Q3	45	
Q2	Q2	46	
Q2	Q2	47	
Q1	<u>Q1</u>	48	
Q1	Q1	49	
QO	QO	50	
Q0	Q0	51	

Table 1. Input/Output Board to Device Pin Connections

Input Pins and Signals

CLK and $\overline{\text{CLK}}$ pins require differential LVPECL levels swinging around an acceptable common mode voltage per datasheet. Internal impedance matching resistor of 50 Ω is provided for driver termination from input pin to the respective VTx pin. Typically the VTx pins are connected to a VTT of V_{CC} -2.0 V. The differential inputs can be driven single ended per the datasheet.

Output Pins and Signals

Output pairs in use must always be balance in each pins loading and termination even if only one side of an output pair is delivered to receiver or scope. Do not unbalance an output pair by loading or probing only one line. Unused outputs should be left floating open. The Rs resistors values are zero Ω , but may be changed to value such as 6 to 12 Ω to improve signal integrity.

For 1X loading, set R_{REF} potentiometer between 0 and 1 k Ω to GND for 1X loading (see Appendix 1: Device I_{REF}) pin 1 load plot of R_{REF} vs. I_{REF} current).

For 50 Ω (Low Impedance) probes with High Bandwidth (>1 GHz): The odd numbered Serial Resistors R17 to R81 positions are populated with zero Ω resistors. The even numbered Parallel Loading resistors R18 to R82 should not be populated (open). Scope module inputs will provide proper termination 50 Ω to GND. Un-probed outputs will need to be externally loaded with 50 Ω to GND for proper balanced operation.

For High Impedance Probes, low input capacitance probe with High Bandwidth (>1 GHz), odd numbered Series Resistors positions R17 to R81 are populated with 0 Ω value components. The even numbered Parallel Loading resistors R18 to R82 should also all be populated with 50 Ω (to GND) components for proper termination.

For 2X loading, set the R_{REF} between 20 K and 50 k Ω to GND or tie I_{REF} directly to V_{CC} .

For 50 Ω (Low Impedance) probes with High Bandwidth (>1 GHz), the odd numbered Serial Resistors R17 to R81 positions should be populated with zero Ω value components. All even numbered Parallel Loading resistors R18 to R82 should have 50 Ω value components installed. A typical scope (probe) 50 Ω impedance in parallel with the installed even numbered Parallel Loading 50 Q resistors R18 to R82 will present a 25 Ω (2X) load to the device. Un-probed outputs will need to be externally loaded with 50 Ω to GND to present the proper 25 Ω load to the device.

For High Impedance Probes, low input capacitance probe with High Bandwidth (>1 GHz), odd numbered Series Resistors positions R17 to R81 are populated with 0 Ω value components. The even numbered Parallel Loading resistors R18 to R82 should also all be populated with 25 Ω (to GND) components for proper termination.

Low Impedance Probes:

Use 50 Ω (Low Impedance) probes with High Bandwidth (>1 GHz). The odd numbered Resistors R18 to R82 positions should be populated with 50 Ω value components.

A typical scope (probe) 50 Ω impedance in parallel with the installed odd numbered 50 Ω Resistor value will present a 25 Ω load to the device. Un-probed outputs will need to be externally loaded with 25 Ω to GND for proper operation.

High Impedance Probes:

Use a high impedance, low input capacitance probe with High Bandwidth (>1 GHz) and repopulate odd numbered Resistors R18 to R82 (25 Ω value).

Step 3: Electrical Measurements

Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 l_{fpm} . Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

APPENDIXES

Appendix 1: Device Information









Figure 8. Output Loading Diagram

$R_{S1}^{C} = 0 \Omega$,

 $R_{REF}^{A} = 0-1 \ k\Omega$ for 1X Load, 20 K-50 K for 2X Load R_{Lx}^{B} may be open for 1X load (supplied by scope input module, may be 50 Ω for 2X load to present a 25 Ω load with scope 50 Ω input module impedance.



Table 2. PIN DESCRIPTION

Pin	Name	I/O	Description	
1	I _{REF}	Output	Output current programming pin to select 1X or 2X load. Connect a selected resistor from I_{REF} pin to GND (See Appendix 3: Device I_{REF} pin 1 load plot of R_{REF} vs. I_{REF} current.	
2	GND	_	Supply Ground. GND pin must be externally connected to power supply to guarantee proper operation.	
3, 6	VTCLK, VTCLK	-	Internal 50 Ω Termination Resistor connection Pins. In the differential configuration when the input termination pins are connected to the common termination voltage, and if no signal is applied then the device may be susceptible to self-oscillation.	
4	CLK	LVPECL Input	CLOCK Input (TRUE)	
5	CLK	LVPECL Input	CLOCK Input (INVERT)	
7, 26, 39, 52	V _{CC}	-	Positive Supply pins. V_{CC} pins must be externally connected to a power supply to guarantee proper operation.	
8, 10, 12, 14, 16, 18, 20, 22, 24, 27, 29, 31, 33, 35, 37, 40, 42, 44, 46, 48, 50	Q[20–0]	HCSL Output	Output (INVERT)	
9, 11, 13, 15, 17, 19, 21, 23, 25, 28, 30, 32, 34, 36, 38, 41, 43, 45, 47, 49, 51	Q[20-0]	HCSL Output	Output (TRUE)	
Exposed Pad	EP	GND	Exposed Pad. The thermally exposed pad (EP) on package bottom (see case drawing) must be attached to a sufficient heat-sinking con- duit for proper thermal operation. (Note 1)	

Appendix 2: Schematics





Figure 11. Pins 14 to 26



Figure 12. Pins 27 to 39



Figure 14. Schematic Bypass and Supply Connector Details



Appendix 3: Device I_{REF} Pin 1 Load Plot of R_{REF} vs. I_{REF} Current

Figure 15. Device I_{REF} pin 1 Load Plot of R_{REF} vs. I_{REF} Current

Appendix 4: Bill of Materials, Board Lamination Stackup, and Fabrication Notes

Bill of Materials Table

Тор	Bot	Description	Value	Source	Source P/N	Reference Designators
0	5	Cap, Chip, 0.1 μF, 0603, 50 V, 10% X7R	0.1 μF			C1, C4, C5, C6, C7
0	2	Cap, Chip, 10 μF, Tant "C", 25 V, 10%	10 μF			C2, C3
1	0	ANTARES 52 QFN Socket			FP0052QN0805C	Alternative construction option: ANTARES Test Technology 3350 Scott Blvd., Bldg 58, Santa Clara, CA 95054, Phone: (408) 988–6800, <u>www.antares-att.com</u>
	4	2–56 Pem Nuts				DUT1
3		TP1, TP2, TP3				KEYSTONE 5016 (or similar)
46	0	Connector, SMA, Straight		Johnson	142–0701–201	J1, J2, J3, J4, J5, J6, J7, J8, J10, J11, J12, J13, J14J15, J16, J17, J18, J19, J20, J21, J22, J23, J24, J25, J26, J27, J28, J29, J30, J31, J32, J33, J34, J35, J36, J37, J38, J39, J40, J41, J42, J48, J49, J50, J51, J52
1		J43			CON DSUB09- RAMP-788796	J43 (Optional – Not Supplied)
0	42	Res, Chip, 0 Ω, 0603, 1/16 W, 5%	0			R1, R3, R5, R7, R9, R11, R13, R15, R17, R19, R21, R23, R25, R27, R29, R31, R33, R35, R37, R39, R41, R43, R45, R47, R49, R51, R53, R55, R57, R59, R61, R63, R65, R67, R69, R71, R73, R75, R77, R79, R81, R83
0	1	0–50 K POTENTIOMETER, TOP ADJUST	0–50 kΩ	BOURNS	3269W-1-503	R85

Board Lamination Stackup:

Dielectric is FR4 (interlayer between 1–2, 2–3, 3–4, 4–5, 5–6). Layers #1 (Topside) and #6 (Bottomside) are signal path copper (trace width 0.014").

Layer	Layer	Copper	Dielectric	Layer	Trace		
Number	Name	Thickness	Thickness	Material	Width		
1	TOP	1/2 OZ.			0.014		
	[]]]]]		0.008	See Note 1	$\langle D \rangle$		
2	GND	1 OZ.			N/A		
	/////	///////////////////////////////////////	0.005	See Note 1			
3	PWR1	1 OZ.			N/A		
		///////	Adjust	See Note 1			
4	PWR2	1 OZ.			N/A		
		///////	0,005	See Note 1			
5	GND	1 OZ.			N/A		
			0,008	See Note 1			
6	BTN	1/2 OZ.			0.014		
FINISHED	PCB THICK	NESS TO BE:	0.100 ±10%	,			

Board Fabrication Notes:

(Unless otherwise specified)

- 1. ARTWORK: Fabricate using ADC artwork No. AZ10035 Rev A. Drill locations determined by ADC file AZ10035NC.DRL
- 2. MATERIAL: High temp FR4 – 170°C Tg
- BOARD THICKNESS: Refer to stacking diagram for finished board thickness.
- TWIST AND WARP: Board twist shall not exceed 0.5% (0.005 in.) per linear inch.
- 5. PLATING:

Copper thickness for internal and external layers is specified in the stacking diagram. Finished PCB to be electrodeposited hard gold plate, type 1 (99.7% min gold), grade C (knoop hardness 130–200), class X, 3–10 micro inches thick, over entire board surface.

Selective plating is not required.

Hole Plating:

0.011 minimum barrel avg. / 0.009 absolute minimum. Absolute maximum to be determined by PCB vendor based on the required finished hole diameter. Hole diameters are after plating unless otherwise specified.

5.1 – Surface pads in this area to be free from any irregularities or defects that might hinder proper performance of the pad.

6. ANNULAR RING:

Annular ring to be 0.005 minimum with top to bottom registration to be within 0.003.

7. SOLDERMASK:

Apply soldermask, color: green, type: LP1, per artwork provided. If VIA plugs are required, plug pattern will be supplied with artwork.

8. SILKSCREEN:

To be white, non-conductive ink per artwork. No ink is to be on plated thru hole or surface mount pads. Silkscreen lines and text width are to be 0.006 minimum.

9. SOLDERABILITY:

Plated holes shall not be rough or irregular so as to prevent proper solder wicking.

10. DRILL CHART:

Hole sizes specified are finished hole sizes, unless otherwise specified: Standard plated hole tolerance is ± 0.003 Standard non-plated hole tolerance is ± 0.002

- 11. IMPEDANCE: Impedance controlled layers: 1, 6.
- 12. APPROVAL:

100% continuity and isolation test required for each fabricated PCB. Final test data must be cross referenced to the IPC–D–356 file provided. A verification stamp is required on each PCB. A TDR report shall be provided for each impedance controlled layer at the time of shipment. Final acceptance shall be determined by these layers having a characteristic impedance of 50 ohms $\pm 10\%$. Vendor can make line width adjustments on impedance controlled conductor widths of 0.0005. All other artwork deviations must have prior approval from R&D ADC. onsemi, ONSEMi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries. onsemi owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of onsemi's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. Onsemi is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

The evaluation board/kit (research and development board/kit) (hereinafter the "board") is not a finished product and is not available for sale to consumers. The board is only intended for research, development, development, development, and evaluation purposes and will only be used in laboratory/development areas by persons with an engineering/technical training and familiar with the risks associated with handling electrical/mechanical components, systems and subsystems. This person assumes full responsibility/liability for proper and safe handling. Any other use, resale or redistribution for any other purpose is strictly prohibited.

THE BOARD IS PROVIDED BY ONSEMI TO YOU "AS IS" AND WITHOUT ANY REPRESENTATIONS OR WARRANTIES WHATSOEVER. WITHOUT LIMITING THE FOREGOING, ONSEMI (AND ITS LICENSORS/SUPPLIERS) HEREBY DISCLAIMS ANY AND ALL REPRESENTATIONS AND WARRANTIES IN RELATION TO THE BOARD, ANY MODIFICATIONS, OR THIS AGREEMENT, WHETHER EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING WITHOUT LIMITATION ANY AND ALL REPRESENTATIONS AND WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, NON-INFRINGEMENT, AND THOSE ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE CUSTOM OR TRADE PRACTICE.

onsemi reserves the right to make changes without further notice to any board.

You are responsible for determining whether the board will be suitable for your intended use or application or will achieve your intended results. Prior to using or distributing any systems that have been evaluated, designed or tested using the board, you agree to test and validate your design to confirm the functionality for your application. Any technical, applications or design information or advice, quality characterization, reliability data or other services provided by **onsemi** shall not constitute any representation or warranty by **onsemi**, and no additional obligations or liabilities shall arise from **onsemi** having provided such information or services.

onsemi products including the boards are not designed, intended, or authorized for use in life support systems, or any FDA Class 3 medical devices or medical devices with a similar or equivalent classification in a foreign jurisdiction, or any devices intended for implantation in the human body. You agree to indemnify, defend and hold harmless onsemi, its directors, officers, employees, representatives, agents, subsidiaries, affiliates, distributors, and assigns, against any and all liabilities, losses, costs, damages, judgments, and expenses, arising out of any claim, demand, investigation, lawsuit, regulatory action or cause of action arising out of or associated with any unauthorized use, even if such claim alleges that onsemi was negligent regarding the design or manufacture of any products and/or the board.

This evaluation board/kit does not fall within the scope of the European Union directives regarding electromagnetic compatibility, restricted substances (RoHS), recycling (WEEE), FCC, CE or UL, and may not meet the technical requirements of these or other related directives.

FCC WARNING – This evaluation board/kit is intended for use for engineering development, demonstration, or evaluation purposes only and is not considered by **onsemi** to be a finished end product fit for general consumer use. It may generate, use, or radiate radio frequency energy and has not been tested for compliance with the limits of computing devices pursuant to part 15 of FCC rules, which are designed to provide reasonable protection against radio frequency interference. Operation of this equipment may cause interference with radio communications, in which case the user shall be responsible, at its expense, to take whatever measures may be required to correct this interference.

onsemi does not convey any license under its patent rights nor the rights of others.

LIMITATIONS OF LIABILITY: **onsemi** shall not be liable for any special, consequential, incidental, indirect or punitive damages, including, but not limited to the costs of requalification, delay, loss of profits or goodwill, arising out of or in connection with the board, even if **onsemi** is advised of the possibility of such damages. In no event shall **onsemi**'s aggregate liability from any obligation arising out of or in connection with the board, under any theory of liability, exceed the purchase price paid for the board, if any.

The board is provided to you subject to the license and other terms per **onsemi**'s standard terms and conditions of sale. For more information and documentation, please visit www.onsemi.com.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS: Technical Library: www.onsemi.com/design/resources/technical-documentation onsemi Website: www.onsemi.com ONLINE SUPPORT: <u>www.onsemi.com/support</u> For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales