
semi



DATE 26 APR 2004

NOTES:

- DIRENSIONS AND TOLERANCING PER ASME Y14.5M, 1994.
 CONTROLLING DIMENSIONS: MILLIMETER.
 DIMENSION & APPLIES TO PLATED

- LIMENSION D APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM TERMINAL COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS. 4.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.80	1.00	
A1	0.00	0.05	
A3	0.20 REF		
b	0.18	0.30	
D	7.00 BSC		
D2	5.50	5.70	
E	7.00 BSC		
E2	5.50	5.70	
е	0.50 BSC		
L	0.30	0.50	
k	0.20		

GENERIC **MARKING DIAGRAM***



*This information is generic. Please refer to device data sheet for actual part marking.

Pb-Free indicator, "G" or microdot " .", may or may not be present.

DOCUMENT NUMBER:	98AON15253D	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	QFN40, 7*7*0.9 0.5 P		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.