






UDFN10 2.5x2, 0.5P CASE 517CJ ISSUE O


**DATE 31 JUL 2012** 



<b>↓</b>	⊢ L	┌ L
L1		







- NOTES:
  1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
- CONTROLLING DIMENSION: MILLIMETERS. DIMENSIONS 6 APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.30 MM FROM TERMINAL TIP. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS			
DIM	MIN	MAX		
Α	0.45	0.55		
A1	0.00	0.05		
A3	0.13 REF			
b	0.15	0.25		
D	2.50 BSC			
Е	2.00 BSC			
е	0.50 BSC			
L	0.70	0.90		
L1	0.05	0.15		

## **GENERIC MARKING DIAGRAM\***



XX = Specific Device Code


M = Date Code

= Pb-Free Package

(Note: Microdot may be in either location)

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ■", may or may not be present.

## **RECOMMENDED MOUNTING FOOTPRINT**



DOCUMENT NUMBER:	98AON82417E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	UDFN10 2.5X2, 0.5P		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves brisefin and of 160 m are trademarks of defined values of services and of the confined values and of the values of the confined values and of the values of the confined values of the confined values and of the values special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.