
semi



WLCSP4, 0.96x0.96 CASE 567AW ISSUE O

DATE 26 JUL 2010




NOTES:

DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
CONTROLLING DIMENSION: MILLIMETERS.
COPLANARITY APPLIES TO SPHERICAL OPDIMINA OF COLDER DALL OF CONTROLLING OF COLDER DALLING

ALLS.

CROWNS OF SOLDER BA					
	MILLIMETERS				
DIM	MIN	MAX			
Α	0.56	0.72			
A1	0.21	0.27			
A2	0.42 REF				
b	0.29	0.35			
D	0.96 BSC				
Е	0.96 BSC				
е	0.50	BSC			

RECOMMENDED **SOLDERING FOOTPRINT***



DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON49806E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	WLCSP4, 0.96X0.96		PAGE 1 OF 1

onsemi and ONSEMi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make charges without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products herein. special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.