

PIN A1 REFERENCE

0.05 C

0.05

0.05 C

5x ∅ b

CAB

С 0.03

0.05

NOTE 3

С 0.05

E

TOP VIEW

SIDE VIEW

BOTTOM VIEW

A B

C SEATING PLANE

еD



WLCSP5, 1.41x0.94 CASE 567LT ISSUE O

DATE 05 JUN 2015

NOTES:

- 1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994. 2. CONTROLLING DIMENSION: MILLIMETERS. 3. COPLANARITY APPLIES TO SPHERICAL
- CROWNS OF SOLDER BALLS.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.40	0.50	
A1	0.21	0.27	
A2	0.23 REF		
b	0.29	0.35	
D	1.41 BSC		
E	0.94 BSC		
eD	0.435 BSC		
еE	0.25 BSC		

GENERIC MARKING DIAGRAM*




= Specific Device Code Х

Μ = Month Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot " ■", may or may not be present.

RECOMMENDED SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON98954F	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	WLCSP5, 1.41X0.94		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves brisefin and of 160 m are trademarked to demonstrate the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.