

PIN ONE REFERENCE

0.05 0.05 С

> 0.05 С

0.05 C

 $|\triangle|$ 

NOTE 3

**TOP VIEW** 

Α1

SIDE VIEW

**BOTTOM VIEW** 

C SEATING

CAB

NOTE 3

0.07 M

<u>√</u> 4X L



## X3DFN4 0.525x0.925, 0.3P CASE 714AA **ISSUE B**

**DATE 08 DEC 2014** 

- NOTES:
  1. DIMENSIONING AND TOLERANCING PER
- ASME Y14.5M, 1994.

  2. CONTROLLING DIMENSION: MILLIMETERS.

  3. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

	MILLIMETERS		
DIM	MIN	MAX	
Α	0.24	0.32	
A1	0.00	0.05	
b	0.12	0.18	
D	0.525 BSC		
Е	0.925 BSC		
е	0.30 BSC		
L	0.173	0.233	
L2	0.42	0.48	

## **GENERIC MARKING DIAGRAM\***




= Specific Device Code Χ

M = Date Code

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G", may or not be present.

## **RECOMMENDED SOLDER FOOTPRINT\***



\*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	98AON89145F	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	X3DFN4 0.525X0.925, 0.3P		PAGE 1 OF 1

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves brisefin and of 160 m are trademarked so defined values of services and of the confined values and of the values of the confined values and of the values of the confined values and of the values of the special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.