

## Final Product/Process Change Notification Document #: FPCN20889XE Issue Date: 13 July 2016

Title of Change	Wafer Level Pag	ckage (M/LD) fab site cl	ange from Gunma Jana	an to Niigata Is	ากวก		
Title of Change:	Wafer Level Package (WLP) fab site change from Gunma, Japan to Niigata, Japan.						
Proposed first ship date:	28 November 2016						
Contact information:	Contact your local ON Semiconductor Sales Office or <u>Tsutomu.Shimazaki@onsemi.com</u>						
Samples:	Contact your local ON Semiconductor Sales Office or <u>Tsutomu.Shimazaki@onsemi.com</u>						
Additional Reliability Data:	Contact your lo	Contact your local ON Semiconductor Sales Office or <u>Satoru.Fujinuma@onsemi.com</u>					
Type of notification:	This is a Final Product/Process Change Notification (FPCN) sent to customers. FPCNs are issued 90 days prior to implementation of the change.  ON Semiconductor will consider this change accepted, unless an inquiry is made in writing within 30 days of delivery of this notice. To do so, contact <pcn.support@onsemi.com>.</pcn.support@onsemi.com>						
Change Part Identification:	Products manufactured at Niigata will be printed Date Code from <b>1648</b> on shipping MPN label.						
Change category:	☐ Wafer Fab Change ☐ Assembly Change ☐ Test Change ☐ Other						
Manufacturing Site Change/Addition  Manufacturing Process Change  Sites Affected:		Datasheet/Product Doc change Shipping/Packaging/Marking Other:  DN Semiconductor site(s):  External Foundry/Subcon site(s)					
Description and Purpose:  To continuously supply products Gunma, Japan to Niigata, Japan. ISO/TS16949 certified.  Reliability Data Summary:  QV DEVICE NAME LV5216CS PACKAGE WLCSP36 2.97x2.97r	All equipment a						
	11111						
i cot opcon	ication		Condition		Interval	Results	
HTOL JESD2	ication 2-A108	Timax	Condition . 100 % max rated Vcc		Interval	Results 0/231	
	2-A108	Tjmax	, 100 % max rated Vcc		1008 hrs	0/231	
HTSL JESD2:							
HTSL JESD2:	2-A108 2-A103	Та	, 100 % max rated Vcc Ta= 150°C		1008 hrs 1008 hrs	0/231 0/231	
HTSL JESD2: TC JESD2: THB JESD2:	2-A108 2-A103 2-A104	Ta 8	, 100 % max rated Vcc Ta= 150°C = -40°C to +125°C		1008 hrs 1008 hrs 500 cyc	0/231 0/231 0/231	
HTSL JESD2: TC JESD2: THB JESD2:	2-A108 2-A103 2-A104 2-A101 JESD-A113 nary: al performance. Da	Ta 8	, 100 % max rated Vcc Ta= 150°C = -40°C to +125°C 5°C, 85% RH, bias MSL 1 @ 260 °C		1008 hrs 1008 hrs 500 cyc	0/231 0/231 0/231	
HTSL JESD2: TC JESD2: THB JESD2: PC J-STD-020  Electrical Characteristic Summ There is no change in the electric  List of Affected Standard Part	2-A108 2-A103 2-A104 2-A101 JESD-A113 nary: al performance. Da	Ta 8	, 100 % max rated Vcc Ta= 150°C = -40°C to +125°C 5°C, 85% RH, bias MSL 1 @ 260 °C	Qualification	1008 hrs 1008 hrs 500 cyc 1008 hrs	0/231 0/231 0/231	

TEM001092 Rev. H Page 1 of 1