BC556B, BC557A, B, C, BC558B

Amplifier Transistors

PNP Silicon

ON Semiconductor®

http://onsemi.com

Features

- Pb−Free Packages are Available*



MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector - Emitter Voltage BC556 BC557 BC558	V_{CEO}	 −65 −45 −30	Vdc
Collector - Base Voltage BC556 BC557 BC558	V_{CBO}	 −80 −50 −30	Vdc
Emitter - Base Voltage	V_{EBO}	−5.0	Vdc
Collector Current − Continuous − Peak	I_C I_{CM}	−100 −200	mAdc
Base Current − Peak	I_{BM}	−200	mAdc
Total Device Dissipation @ T_A = 25°C Derate above 25°C	P_D	625 5.0	mW mW/°C
Total Device Dissipation @ T_C = 25°C Derate above 25°C	P_D	1.5 12	W mW/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	−55 to +150	°C

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	200	°C/W
Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	83.3	°C/W

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

TO−92
CASE 29
STYLE 17



STRAIGHT LEAD
BULK PACK



BENT LEAD
TAPE & REEL
AMMO PACK

MARKING DIAGRAM



xx	= 6B, 7A, 7B, 7C, or 8B
A	= Assembly Location
Y	= Year
WW	= Work Week
▪	= Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

© Semiconductor Components Industries, LLC, 2007

March, 2007 − Rev. 3

Publication Order Number:
BC556B/D

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector−Emitter Breakdown Voltage		$V_{(BR)CEO}$				V
(I_C = −2.0 mAdc, I_B = 0)	BC556		−65	−	−	
	BC557		−45	−	−	
	BC558		−30	−	−	
Collector−Base Breakdown Voltage		$V_{(BR)CBO}$				V
(I_C = −100 μAdc)	BC556		−80	−	−	
	BC557		−50	−	−	
	BC558		−30	−	−	
Emitter−Base Breakdown Voltage		$V_{(BR)EBO}$				V
(I_E = −100 μAdc, I_C = 0)	BC556		−5.0	−	−	
	BC557		−5.0	−	−	
	BC558		−5.0	−	−	
Collector−Emitter Leakage Current		I_{CES}				
(V_{CES} = −40 V)	BC556		−	−2.0	−100	nA
(V_{CES} = −20 V)	BC557		−	−2.0	−100	
	BC558		−	−2.0	−100	
(V_{CES} = −20 V, T_A = 125°C)	BC556		−	−	−4.0	μA
	BC557		−	−	−4.0	
	BC558		−	−	−4.0	
ON CHARACTERISTICS						
DC Current Gain		h_{FE}				−
(I_C = −10 μAdc, V_{CE} = −5.0 V)	A Series Device		−	90	−	
	B Series Devices		−	150	−	
	C Series Devices		−	270	−	
(I_C = −2.0 mAdc, V_{CE} = −5.0 V)	BC557		120	−	800	
	A Series Device		120	170	220	
	B Series Devices		180	290	460	
	C Series Devices		420	500	800	
(I_C = −100 mAdc, V_{CE} = −5.0 V)	A Series Device		−	120	−	
	B Series Devices		−	180	−	
	C Series Devices		−	300	−	
Collector−Emitter Saturation Voltage		$V_{CE(sat)}$				V
(I_C = −10 mAdc, I_B = −0.5 mAdc)			−	−0.075	−0.3	
(I_C = −10 mAdc, I_B = see Note 1)			−	−0.3	−0.6	
(I_C = −100 mAdc, I_B = −5.0 mAdc)			−	−0.25	−0.65	
Base−Emitter Saturation Voltage		$V_{BE(sat)}$				V
(I_C = −10 mAdc, I_B = −0.5 mAdc)			−	−0.7	−	
(I_C = −100 mAdc, I_B = −5.0 mAdc)			−	−1.0	−	
Base−Emitter On Voltage		$V_{BE(on)}$				V
(I_C = −2.0 mAdc, V_{CE} = −5.0 Vdc)			−0.55	−0.62	−0.7	
(I_C = −10 mAdc, V_{CE} = −5.0 Vdc)			−	−0.7	−0.82	
SMALL−SIGNAL CHARACTERISTICS						
Current−Gain − Bandwidth Product		f_T				MHz
(I_C = −10 mA, V_{CE} = −5.0 V, f = 100 MHz)	BC556		−	280	−	
	BC557		−	320	−	
	BC558		−	360	−	
Output Capacitance		C_{ob}	−	3.0	6.0	pF
(V_{CB} = −10 V, I_C = 0, f = 1.0 MHz)						
Noise Figure		NF				dB
(I_C = −0.2 mAdc, V_{CE} = −5.0 V,	BC556		−	2.0	10	
R_S = 2.0 kΩ, f = 1.0 kHz, Δf = 200 Hz)	BC557		−	2.0	10	
	BC558		−	2.0	10	
Small−Signal Current Gain		h_{fe}				−
(I_C = −2.0 mAdc, V_{CE} = 5.0 V, f = 1.0 kHz)	BC557		125	−	900	
	A Series Device		125	−	260	
	B Series Devices		240	−	500	
	C Series Devices		450	−	900	

1. I_C = −10 mAdc on the constant base current characteristics, which yields the point I_C = −11 mAdc, V_{CE} = −1.0 V.

BC557/BC558



Figure 1. Normalized DC Current Gain



Figure 2. “Saturation” and “On” Voltages



Figure 3. Collector Saturation Region



Figure 4. Base−Emitter Temperature Coefficient



Figure 5. Capacitances



Figure 6. Current−Gain − Bandwidth Product

BC556



Figure 7. DC Current Gain



Figure 8. “On” Voltage



Figure 9. Collector Saturation Region



Figure 10. Base−Emitter Temperature Coefficient



Figure 11. Capacitance



Figure 12. Current−Gain − Bandwidth Product



Figure 13. Thermal Response



Figure 14. Active Region − Safe Operating Area

The safe operating area curves indicate I_C−V_{CE} limits of the transistor that must be observed for reliable operation. Collector load lines for specific circuits must fall below the limits indicated by the applicable curve.

The data of Figure 14 is based upon $T_{J(pk)}$ = 150°C; T_C or T_A is variable depending upon conditions. Pulse curves are valid for duty cycles to 10% provided $T_{J(pk)} \leq$ 150°C. $T_{J(pk)}$ may be calculated from the data in Figure 13. At high case or ambient temperatures, thermal limitations will reduce the power than can be handled to values less than the limitations imposed by second breakdown.

ORDERING INFORMATION

Device	Package	Shipping†
BC556BG	TO−92 (Pb−Free)	5000 Units / Bulk
BC556BZL1G	TO−92 (Pb−Free)	2000 / Ammo Box
BC557AZL1G	TO−92 (Pb−Free)	2000 / Ammo Box
BC557BG	TO−92 (Pb−Free)	5000 Units / Bulk
BC557BRL1	TO−92	2000 / Tape & Reel
BC557BRL1G	TO−92 (Pb−Free)	2000 / Tape & Reel
BC557BZL1G	TO−92 (Pb−Free)	2000 / Ammo Box
BC557CG	TO−92 (Pb−Free)	5000 Units / Bulk
BC557CZL1G	TO−92 (Pb−Free)	2000 / Ammo Box
BC558BRLG	TO−92 (Pb−Free)	2000 / Tape & Reel
BC558BRL1G	TO−92 (Pb−Free)	2000 / Tape & Reel
BC558BZL1G	TO−92 (Pb−Free)	2000 / Ammo Box

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

SCALE 1:1



STRAIGHT LEAD
BULK PACK

BENT LEAD
TAPE & REEL
AMMO PACK

TO−92 (TO−226)
CASE 29−11
ISSUE AM

DATE 09 MAR 2007



STRAIGHT LEAD
BULK PACK



SECTION X−X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.175	0.205	4.45	5.20
B	0.170	0.210	4.32	5.33
C	0.125	0.165	3.18	4.19
D	0.016	0.021	0.407	0.533
G	0.045	0.055	1.15	1.39
H	0.095	0.105	2.42	2.66
J	0.015	0.020	0.39	0.50
K	0.500	---	12.70	---
L	0.250	---	6.35	---
N	0.080	0.105	2.04	2.66
P	---	0.100	---	2.54
R	0.115	---	2.93	---
V	0.135	---	3.43	---



BENT LEAD
TAPE & REEL
AMMO PACK



SECTION X−X

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. CONTOUR OF PACKAGE BEYOND DIMENSION R IS UNCONTROLLED.
4. LEAD DIMENSION IS UNCONTROLLED IN P AND BEYOND DIMENSION K MINIMUM.

	MILLIMETERS	
DIM	MIN	MAX
A	4.45	5.20
B	4.32	5.33
C	3.18	4.19
D	0.40	0.54
G	2.40	2.80
J	0.39	0.50
K	12.70	---
N	2.04	2.66
P	1.50	4.00
R	2.93	---
V	3.43	---

STYLES ON PAGE 2

DOCUMENT NUMBER:	**98ASB42022B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**TO−92 (TO−226)**	**PAGE 1 OF 2**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

TO−92 (TO−226)
CASE 29−11
ISSUE AM

DATE 09 MAR 2007

STYLE 1:
PIN 1. EMITTER
2. BASE
3. COLLECTOR

STYLE 2:
PIN 1. BASE
2. EMITTER
3. COLLECTOR

STYLE 3:
PIN 1. ANODE
2. ANODE
3. CATHODE

STYLE 4:
PIN 1. CATHODE
2. CATHODE
3. ANODE

STYLE 5:
PIN 1. DRAIN
2. SOURCE
3. GATE

STYLE 6:
PIN 1. GATE
2. SOURCE & SUBSTRATE
3. DRAIN

STYLE 7:
PIN 1. SOURCE
2. DRAIN
3. GATE

STYLE 8:
PIN 1. DRAIN
2. GATE
3. SOURCE & SUBSTRATE

STYLE 9:
PIN 1. BASE 1
2. EMITTER
3. BASE 2

STYLE 10:
PIN 1. CATHODE
2. GATE
3. ANODE

STYLE 11:
PIN 1. ANODE
2. CATHODE & ANODE
3. CATHODE

STYLE 12:
PIN 1. MAIN TERMINAL 1
2. GATE
3. MAIN TERMINAL 2

STYLE 13:
PIN 1. ANODE 1
2. GATE
3. CATHODE 2

STYLE 14:
PIN 1. EMITTER
2. COLLECTOR
3. BASE

STYLE 15:
PIN 1. ANODE 1
2. CATHODE
3. ANODE 2

STYLE 16:
PIN 1. ANODE
2. GATE
3. CATHODE

STYLE 17:
PIN 1. COLLECTOR
2. BASE
3. EMITTER

STYLE 18:
PIN 1. ANODE
2. CATHODE
3. NOT CONNECTED

STYLE 19:
PIN 1. GATE
2. ANODE
3. CATHODE

STYLE 20:
PIN 1. NOT CONNECTED
2. CATHODE
3. ANODE

STYLE 21:
PIN 1. COLLECTOR
2. EMITTER
3. BASE

STYLE 22:
PIN 1. SOURCE
2. GATE
3. DRAIN

STYLE 23:
PIN 1. GATE
2. SOURCE
3. DRAIN

STYLE 24:
PIN 1. EMITTER
2. COLLECTOR/ANODE
3. CATHODE

STYLE 25:
PIN 1. MT 1
2. GATE
3. MT 2

STYLE 26:
PIN 1. V_{CC}
2. GROUND 2
3. OUTPUT

STYLE 27:
PIN 1. MT
2. SUBSTRATE
3. MT

STYLE 28:
PIN 1. CATHODE
2. ANODE
3. GATE

STYLE 29:
PIN 1. NOT CONNECTED
2. ANODE
3. CATHODE

STYLE 30:
PIN 1. DRAIN
2. GATE
3. SOURCE

STYLE 31:
PIN 1. GATE
2. DRAIN
3. SOURCE

STYLE 32:
PIN 1. BASE
2. COLLECTOR
3. EMITTER

STYLE 33:
PIN 1. RETURN
2. INPUT
3. OUTPUT

STYLE 34:
PIN 1. INPUT
2. GROUND
3. LOGIC

STYLE 35:
PIN 1. GATE
2. COLLECTOR
3. EMITTER

DOCUMENT NUMBER:	98ASB42022B	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO−92 (TO−226)	PAGE 2 OF 2

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales