

# NCP1596A

## 1.5 A, 1.5 MHz Current Mode PWM Buck Down Converter

The NCP1596A is a current mode PWM buck converter with integrated power switch. It can provide up to 1.5 A output current with high conversion efficiency. High frequency PWM control scheme can provide a low output ripple noise. Thus, it allows the usage of small size passive components to reduce the board space. In a low load condition, the controller will automatically change to PFM mode which provides a higher efficiency at low load. Additionally, the device includes soft-start, thermal shutdown with hysteresis, cycle-by-cycle current limit, and short circuit protection. This device is available in a compact 3x3 DFN package.

### Features

- High Efficiency up to 90%, 1 A @ 3.3 V, 75% @ 1.2 V
- Fully Internal Compensation
- Low Output Voltage Ripple, 20 mV Typical
- $\pm 1.5\%$  Reference Voltage
- High PWM Switching Frequency, 1.5 MHz
- Automatic PWM / PFM Switchover at Light Load
- Built-in 1 ms Digital Soft Start
- Cycle-by-cycle Current Limit
- Thermal Shutdown with Hysteresis
- Internal UVLO Protection
- Ext. Adjustable Output Voltage
- Low Profile and Minimum External Components
- Designed for use with Ceramic Capacitor
- Compact 3x3 DFN Package
- These are Pb-Free Devices

### Typical Applications

- Hard Disk Drives
- USB Power Device
- Wireless and DSL Modems



**ON Semiconductor®**


<http://onsemi.com>



1

**6 PIN DFN 3x3  
MN SUFFIX  
CASE 506AH**

### MARKING DIAGRAM



1596A = Specific Device Code

A = Assembly Location


L = Wafer Lot

Y = Year

W = Work Week

■ = Pb-Free Package

### PIN CONNECTIONS



### ORDERING INFORMATION

Device	Package	Shipping†
NCP1596AMNTWG	DFN6 (Pb-Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

## NCP1596A




Figure 1. Typical Operating Circuit

### ABSOLUTE MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Power Supply (Pins 4, 5)	$V_{IN}$	6.0 -0.3 (DC) -1.0 (100 ns)	V
Input / Output Pins Pins 1, 3, 6	$V_{IO}$	6.0 -0.3 (DC) -1.0 (100 ns)	V
Thermal Characteristics 3x3 DFN Plastic Package Maximum Power Dissipation @ $T_A = 25^\circ\text{C}$ Thermal Resistance Junction-to-Ambient 0 lfpm	$P_D$ $R_{\theta JA}$	1450 68.5	mW $^\circ\text{C/W}$
Operating Junction Temperature Range (Note 4)	$T_J$	-40 to +150	$^\circ\text{C}$
Operating Ambient Temperature Range	$T_A$	-40 to +85	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	-55 to +150	$^\circ\text{C}$
Lead Temperature Soldering (10 sec)		230	$^\circ\text{C}$
Moisture Sensitivity Level (Note 3)	MSL	1	-

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

NOTE: ESD data available upon request.

- This device series contains ESD protection and exceeds the following tests:  
Human Body Model (HBM) 2.0 kV per JEDEC standard: JESD22-A114.  
Machine Model (MM) 200 V per JEDEC standard: JESD22-A115.
- Latch-up Current Maximum Rating: 150 mA per JEDEC standard: JESD78.
- Moisture Sensitivity Level (MSL): 1 per IPC/JEDEC standard: J-STD-020A.
- The maximum package power dissipation limit must not be exceeded.

$$P_D = \frac{T_{J(max)} - T_A}{R_{\theta JA}}$$

# NCP1596A

## ELECTRICAL CHARACTERISTICS

( $V_{IN} = 5.0\text{ V}$ ,  $V_{OUT} = 1.2\text{ V}$ ,  $T_A = 25^\circ\text{C}$  for typical value,  $-40^\circ\text{C} \leq T_A \leq 85^\circ\text{C}$  for min/max values unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
Operating Voltage	$V_{IN}$	4.0	–	5.5	V
Under Voltage Lockout Threshold	$V_{UVLO}$	3.2	3.5	3.8	V
Under Voltage Lockout hysteresis	$V_{UVLO\_HYS}$	–	180	–	mV
PFET Leakage Current (Pins 5, 4) $T_A = 25^\circ\text{C}$ $T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$	$I_{LEAK-P}$	– –	1.0 –	10 15	$\mu\text{A}$

## FEEDBACK VOLTAGE

FB Input Threshold ( $T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$ )	$V_{FB}$	0.788	0.800	0.812	V
FB Input Current	$I_{FB}$	–	10	100	nA

## THERMAL SHUTDOWN

Thermal Shutdown Threshold (Note 5)	$T_{SHDN}$	–	160	–	$^\circ\text{C}$
Hysteresis (Note 5)	$T_{SDHYS}$	–	30	–	$^\circ\text{C}$

## PWM SMPS MODE

Switching Frequency ( $T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$ )	$F_{OSC}$	1.27	1.5	1.725	MHz
Internal PFET ON-Resistance ( $I_{LX} = 100\text{ mA}$ , $V_{IN} = 5.0\text{ V}$ , $T_A = 25^\circ\text{C}$ ) (Note 5)	$R_{DS(on)_P}$	–	0.2	0.3	Ohm
Minimum Duty Cycle	$D_{MIN}$	–	0	–	%
Maximum Duty Cycle	$D_{MAX}$	–	100	–	%
Soft-Start Time ( $V_{IN} = 5.0\text{ V}$ , $V_O = 1.2\text{ V}$ , $I_{LOAD} = 0\text{ mA}$ , $T_A = 25^\circ\text{C}$ )	$T_{SS}$	0.8	1.0	1.2	ms
Main PFET Switch Current Limit (Note 5)	$I_{LIM}$	2.0	2.5	–	A

## ENABLE

Enable Threshold High	$V_{EN\_H}$	1.8	–	–	V
Enable Threshold Low	$V_{EN\_L}$	–	–	0.4	V
Enable bias current ( $EN = 0\text{ V}$ )	$I_{EN}$	–	500	–	nA

## EFFICIENCY

Output Load Current 10 mA @ 1.2 V (Note 5)	$\eta$	–	50	–	%
Output Load Current 100 mA to 1.2 A @ 1.2 V (Note 5)	$\eta$	–	70	–	%

## TOTAL DEVICE

Quiescent Current Into $V_{CCP}$ ( $V_{IN} = 5\text{ V}$ , $V_{FB} = 1.0\text{ V}$ , $T_A = 25^\circ\text{C}$ )	$I_{CCP}$	–	10	–	$\mu\text{A}$
Quiescent Current Into $V_{CC}$ ( $V_{IN} = 5\text{ V}$ , $V_{FB} = 1.0\text{ V}$ , $T_A = 25^\circ\text{C}$ )	$I_{CC}$	–	500	–	$\mu\text{A}$
Shutdown Quiescent Current into $V_{CC}$ and $V_{CCP}$ ( $EN = 0$ , $V_{IN} = 5\text{ V}$ , $V_{FB} = 1.0\text{ V}$ , $T_A = 25^\circ\text{C}$ )	$I_{CC\_SD}$	–	1.0	3.0	$\mu\text{A}$

5. Values are design guaranteed.

# NCP1596A

## PIN FUNCTION DESCRIPTIONS

Pin #	Symbol	Pin Description
1	FB	Feedback pin. Part is internally compensated. Only necessary to place a voltage divider or connect the output directly to this pin.
2	GND	Ground
3	LX	Pin connected internally to power switch. Connect externally to inductor.
4	VCCP	Power connection to the power switch.
5	VCC	IC power connection.
6	EN	Device Enable pin. This pin has an internal current source pull up. No connect is enable the device. With this pin pulled down below 0.8 V, the device is disabled and enters the shutdown mode.




Figure 2. Detail Block Diagram

## EXTERNAL COMPONENT REFERENCE DATA

V <sub>OUT</sub>	Inductor Model	Inductor (L1)	Diode (D1)	C <sub>IN</sub> (C1)	C <sub>OUT</sub> (C2)	R1	R2
3.3 V	CDC5D23 3R3 (1 A) CDRH6D38 3R3 (1.5 A)	3.3 $\mu$ H	MBRA210LT3G	22 $\mu$ F 22 $\mu$ F x 2	22 $\mu$ F 22 $\mu$ F x 2	31 k	10 k
2.5 V	CDC5D23 3R3 (1 A) CDRH6D38 3R3 (1.5 A)	3.3 $\mu$ H	MBRA210LT3G	22 $\mu$ F 22 $\mu$ F x 2	22 $\mu$ F 22 $\mu$ F x 2	21 k	10 k
1.5 V	CDC5D23 3R3 (1 A) CDRH6D38 3R3 (1.5 A)	3.3 $\mu$ H	MBRA210LT3G	22 $\mu$ F 22 $\mu$ F x 2	22 $\mu$ F 22 $\mu$ F x 2	8 k	10 k
1.2 V	CDC5D23 3R3 (1 A) CDRH6D38 3R3 (1.5 A)	3.3 $\mu$ H	MBRA210LT3G	22 $\mu$ F 22 $\mu$ F x 2	22 $\mu$ F 22 $\mu$ F x 2	5 k	10 k

# NCP1596A




Figure 3. Timing Diagram




Figure 4. State Diagram

TYPICAL OPERATING CHARACTERISTICS




Figure 5. Switch ON Resistance vs. Temperature




Figure 6. Feedback Input Threshold vs. Temperature




Figure 7. Switching Frequency vs. Temperature




Figure 8. Main P-FET Current Limit vs. Temperature




Figure 9. Quiescent Current Into V<sub>CC</sub> vs. Temperature




Figure 10. Shutdown Quiescent Current vs. Temperature




Figure 11. Output Voltage Change vs. Output Current




Figure 12. Efficiency vs. Output Current




Figure 13. Output Voltage Change vs. Output Current




Figure 14. Efficiency vs. Output Current




Figure 16. Output Voltage Change vs. Output Current






Figure 15. Efficiency vs. Output Current




( $V_{IN} = 5\text{ V}$ ,  $I_{LOAD} = 10\text{ mA}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 20\text{ }\mu\text{F}$ )  
 Upper Trace: Output Ripple Voltage, 20 mV/div  
 Middle Trace:  $L_X$  Pin Switching Waveform, 5 V/div  
 Lower Trace: Inductor Current Waveform, 500 mA/div  
 Time Base: 500 ns/div

**Figure 17. DCM Switching Waveform for  $V_{OUT} = 3.3\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $I_{LOAD} = 500\text{ mA}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 20\text{ }\mu\text{F}$ )  
 Upper Trace: Output Ripple Voltage, 20 mV/div  
 Middle Trace:  $L_X$  Pin Switching Waveform, 5 V/div  
 Lower Trace: Inductor Current Waveform, 500 mA/div  
 Time Base: 200 ns/div

**Figure 18. CCM Switching Waveform for  $V_{OUT} = 3.3\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $I_{LOAD} = 10\text{ mA}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 20\text{ }\mu\text{F}$ )  
 Upper Trace: Output Ripple Voltage, 20 mV/div  
 Middle Trace:  $L_X$  Pin Switching Waveform, 5 V/div  
 Lower Trace: Inductor Current Waveform, 500 mA/div  
 Time Base: 2  $\mu\text{s}$ /div

**Figure 19. DCM Switching Waveform for  $V_{OUT} = 1.2\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $I_{LOAD} = 500\text{ mA}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 20\text{ }\mu\text{F}$ )  
 Upper Trace: Output Ripple Voltage, 20 mV/div  
 Middle Trace:  $L_X$  Pin Switching Waveform, 5 V/div  
 Lower Trace: Inductor Current Waveform, 500 mA/div  
 Time Base: 200 ns/div

**Figure 20. CCM Switching Waveform for  $V_{OUT} = 1.2\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $I_{LOAD} = 10\text{ mA}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 20\text{ }\mu\text{F} \times 2$ )  
 Upper Trace: Input Voltage, 1 V/div  
 Lower Trace: Output Voltage, 1 V/div  
 Time Base: 500  $\mu\text{s}$ /div

**Figure 21. Soft-Start Waveforms for  $V_{OUT} = 3.3\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $I_{LOAD} = 10\text{ mA}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 20\text{ }\mu\text{F} \times 2$ )  
 Upper Trace: Input Voltage, 1 V/div  
 Lower Trace: Output Voltage, 500 mV/div  
 Time Base: 500  $\mu\text{s}$ /div

**Figure 22. Soft-Start Waveforms for  $V_{OUT} = 1.2\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 10\text{ }\mu\text{F} \times 2$ )  
 Upper Trace: Output Dynamic Voltage, 100 mV/div  
 Lower Trace: Output Current, 200 mA/div  
 Time Base: 20 ns/div

**Figure 23. Load Regulation for  $V_{OUT} = 3.3\text{ V}$**




( $V_{IN} = 5\text{ V}$ ,  $L = 3.3\text{ }\mu\text{H}$ ,  $C_{OUT} = 10\text{ }\mu\text{F} \times 2$ )  
 Upper Trace: Output Dynamic Voltage, 100 mV/div  
 Lower Trace: Output Current, 200 mA/div  
 Time Base: 20 ns/div

**Figure 24. Load Regulation for  $V_{OUT} = 3.3\text{ V}$**



( $V_{IN} = 5\text{ V}$ ,  $L = 3.3\text{ H}$ ,  $C_{OUT} = 10\text{ }\mu\text{F} \times 2$ )  
 Upper Trace: Output Dynamic Voltage, 50 mV/div  
 Lower Trace: Output Current, 200 mA/div  
 Time Base: 10 ns/div

**Figure 25. Load Regulation for  $V_{OUT} = 1.2\text{ V}$**



( $V_{IN} = 5\text{ V}$ ,  $L = 3.3\text{ H}$ ,  $C_{OUT} = 10\text{ }\mu\text{F} \times 2$ )  
 Upper Trace: Output Dynamic Voltage, 50 mV/div  
 Lower Trace: Output Current, 200 mA/div  
 Time Base: 10 ns/div

**Figure 26. Load Regulation for  $V_{OUT} = 1.2\text{ V}$**

## DETAILED OPERATING DESCRIPTION

**Introduction**

The NCP1596A is a current-mode buck converter with switching frequency at 1.5 MHz. High operation frequency can reduce the capacitor value and PCB area. Also, more features are built in this converter.

1. Internal 1 ms soft-start to avoid inrush current at startup.
2. Internal cycle by cycle current limit provides an output short circuit protection.
3. Internal compensation. No external compensation components are necessary.
4. Thermal shutdown protects the devices from over heat.
5. 100% duty cycle allowed. Speed up transient load response.

The upper feature can provide more cost effective solutions to applications. A simple function block diagram and timing diagram are shown in Figure 1 and Figure 2.

**Soft-Start and Current Limit**

A soft start circuit is internally implemented to reduce the in-rush current during startup. This helps to reduce the output voltage over-shoot.

The current limit is set to allow peak switch current in excess of 2 A. The intended output current of the system is 1.5 A. The ripple current is calculated to be approximately 350 mA with a 3.3  $\mu$ H inductor. Therefore, the peak current at 1.5 A output will be approximately 1.7 Amps. A 2.5 Amp set point will allow for transient currents during load step. The current limit circuit is implemented as a cycle-by-cycle current limit. Each on-cycle is treated as a separate situation. Current limiting is implemented by monitoring the P-channel switch current buildup during conduction with a current limit comparator. The output of the current limit comparator resets the PWM latch, immediately terminating the current cycle. When output loading is short circuit, device will auto restart with soft-start.

**Error Amplifier and Slope Compensation**

A fully internal compensated error amplifier is provided inside NCP1596A. No external circuitry is needed to stabilize the device. The error amplifier provides an error signal to the PWM comparator by comparing the feedback voltage (800 mV) with internal voltage reference of 1.2 V.

Current mode converter can exhibit instability at duty cycles over 50%. A slope compensation circuit is provided

inside NCP1596A to overcome the potential instability. Slope compensation consists of a ramp signal generated by the synchronization block and adding this to the inductor current signal. The summed signal is then applied to the PWM comparator.

**Thermal Shutdown**

Internal Thermal Shutdown circuitry is provided to protect the integrated circuit in the event when maximum junction temperature is exceeded. When activated, typically at 180°C, the shutdown signal will disable the P-channel switch. The thermal shutdown circuit is designed with 30°C of hysteresis. This means that the switching will not start until the die temperature drops by this amount. This feature is provided to prevent catastrophic failures from accidental device overheating. **It is not intended as a substitute for proper heat sinking.** NCP1596A is contained in the thermally enhanced QFN package.

**Under Voltage Lockout (UVLO)**

UVLO function is used to ensure the logic level correctly when input voltage is very low. In NCP1596A, the UVLO level is set to 3.5 V. If the input voltage is less than 3.5 V, the converter will shutdown itself automatically.

**Low Power Shutdown Mode (EN)**

NCP1596A can be disabled whenever the EN pin is tied to ground. During the shutdown mode, the internal reference, oscillator and driver control circuits will be turn off, the device only consume 1  $\mu$ A typically and output voltage will be discharge to zero by the external resistor divider. EN pin has an internal pull-up current source, which typical value is 500 nA.

**Power Saving Pulse-Frequency-Modulation (PFM) Control Scheme**

While the converter loading decreases, the converter enters the Discontinuous-conduction-mode (DCM) operation. In DCM operation, the on-time ( $T_{on}$ ) of the integrated switch for each switching cycle will decrease when the output current decreases. In order to maintain a high converter efficiency at light load condition. A minimum  $T_{on}$  is set to 70 ns. It can make sure a minimum fixed power send to output. To avoid a higher switch loss occurs when without loading apply. This control scheme can reduce the switching loss at light load and improve the conversion efficiency.

## APPLICATION INFORMATION

**Output Voltage Selection**

The output voltage is programmed through an external resistor divider connect from  $V_{OUT}$  to FB then to GND.

For internal compensation and noise immunity, the resistor from FB to GND should be in 10 k to 20 k ranges. The relationship between the output voltage and feedback resistor is given by:

$$V_{OUT} = V_{FB} \times \left(1 + \frac{R1}{R2}\right) \quad (\text{eq. 1})$$

$V_{OUT}$ : Output voltage

$V_{FB}$ : Feedback Voltage

R1: Feedback resistor from  $V_{OUT}$  to FB.

R2: Feedback resistor from FB to GND.

**Input Capacitor Selection**

In the PWM buck converter, the input current is pulsating current with switching noise. Therefore, a bypass input capacitor must choose for reduce the peak current drawn from the power supply. For NCP1596A, low ESR ceramic capacitor of 10  $\mu\text{F}$  should be used for most of cases. Also, the input capacitor should be placed as close as possible to the  $V_{CCA}$  pin for effective bypass the supply noise.

**Inductor Selection**

The inductor parameters are including three items, which are DC resistance, inductor value and saturation current. Inductor DC resistance will effect the convector overall efficiency, low DC resistor value can provide a higher efficiency. Thus, inductor value are depend on the inductor

ripple current, input voltage, output voltage, output current and operation frequency, the inductor value is given by:

$$\Delta I_L = \frac{V_{OUT}}{L \times F_{SW}} \times \left(1 - \frac{V_{OUT}}{V_{IN}}\right) \quad (\text{eq. 2})$$

$\Delta I_L$  : peak to peak inductor ripple current

L: inductor value

$F_{SW}$ : switching frequency

After selected a suitable value of the inductor, it should be check out the inductor saturation current. The saturation current of the inductor should be higher than the maximum load plus the ripple current.

$$\Delta I_{L(MAX)} = \Delta I_{OUT(MAX)} + \frac{\Delta I_L}{2} \quad (\text{eq. 3})$$

$\Delta I_{L(MAX)}$  : Maximum inductor current

$\Delta I_{OUT(MAX)}$  : Maximum output current

**Output Capacitor Selection**

Output capacitor value is based on the target output ripple voltage. For NCP1596A, the output capacitor is required a ceramic capacitors with low ESR value. Assume buck converter duty cycle is 50%. The output ripple voltage in PWM mode is given by:

$$\Delta V_{OUT} \approx \Delta I_L \times \left(\frac{1}{4 \times F_{SW} \times C_{OUT}} + \text{ESR}\right) \quad (\text{eq. 4})$$

In general, value of ceramic capacitor using 20  $\mu\text{F}$  should be a good choice.





1  
SCALE 2:1

**DFN6 3\*3 MM, 0.95 PITCH**

CASE 506AH  
ISSUE O

DATE 17 NOV 2004


**SOLDERING FOOTPRINT\***

NOTES:

1. DIMENSIONS AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

DIM	MILLIMETERS		
	MIN	NOM	MAX
A	0.80	0.90	1.00
A1	0.00	0.03	0.05
A3	0.20 REF		
b	0.35	0.40	0.45
D	3.00 BSC		
D2	2.40	2.50	2.60
E	3.00 BSC		
E2	1.50	1.60	1.70
e	0.95 BSC		
K	0.21	MINIMUM	
L	0.30	0.40	0.50

### GENERIC MARKING DIAGRAM\*



- xxxxx = Specific Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
▪ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

\*For additional information on our Pb-Free strategy and soldering details, please download the **onsemi** Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

<b>DOCUMENT NUMBER:</b>	<b>98AON19891D</b>	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
<b>DESCRIPTION:</b>	<b>DFN6 3*3 MM, 0.95 PITCH, SINGLE FLAG</b>	<b>PAGE 1 OF 1</b>

**onsemi** and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)