

# MOSFET – Power, Dual, N-Channel, Power Trench, Power Clip, Asymmetric 25 V



## NTMFD1D4N02P1E

ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)

### Features

- Small Footprint (5x6mm) for Compact Design
- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Low  $Q_G$  and Capacitance to Minimize Driver Losses
- These are Pb-free, Halogen Free / BFR Free and are RoHS Compliant

### Typical Applications

- DC-DC Converters
- System Voltage Rails

### MAXIMUM RATINGS ( $T_J = 25^\circ\text{C}$ unless otherwise stated)

Parameter			Symbol	Q1	Q2	Unit
Drain-to-Source Voltage			$V_{DSS}$	25	25	V
Gate-to-Source Voltage			$V_{GS}$	+16V -12V	+16V -12V	V
Continuous Drain Current $R_{\theta JC}$ (Note 3)	Steady State	$T_C = 25^\circ\text{C}$	$I_D$	74	155	A
		$T_C = 85^\circ\text{C}$		53	112	
Power Dissipation $R_{\theta JC}$ (Note 3)		$T_A = 25^\circ\text{C}$	$P_D$	25	41	W
Continuous Drain Current $R_{\theta JA}$ (Notes 1, 3)	Steady State	$T_A = 25^\circ\text{C}$	$I_D$	20	36	A
		$T_A = 85^\circ\text{C}$		14	26	
Power Dissipation $R_{\theta JA}$ (Notes 1, 3)		$T_A = 25^\circ\text{C}$	$P_D$	2.1	2.3	W
Continuous Drain Current $R_{\theta JA}$ (Notes 2, 3)	Steady State	$T_A = 25^\circ\text{C}$	$I_D$	13	24	A
		$T_A = 85^\circ\text{C}$		10	17	
Power Dissipation $R_{\theta JA}$ (Notes 2, 3)		$T_A = 25^\circ\text{C}$	$P_D$	0.96	1.0	W
Pulsed Drain Current	$T_A = 25^\circ\text{C}$ , $t_p = 10 \mu\text{s}$		$I_{DM}$	325	552	A
Single Pulse Drain-to-Source Avalanche Energy Q1: $I_L = 9.4 A_{pk}$ , $L = 3 \text{ mH}$ (Note 4) Q2: $I_L = 20.1 A_{pk}$ , $L = 3 \text{ mH}$ (Note 4)			$E_{AS}$	134	604	mJ
Operating Junction and Storage Temperature Range			$T_J$ , $T_{stg}$	-55 to 150		$^\circ\text{C}$
Lead Temperature Soldering Reflow for Soldering Purposes (1/8" from case for 10 s)			$T_L$	260		$^\circ\text{C}$


Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

FET	$V_{(BR)DSS}$	$R_{DS(on)}$ MAX	$I_D$ MAX
Q1	25 V	3.3 $\text{m}\Omega$ @ 10 V	74 A
		4.2 $\text{m}\Omega$ @ 4.5 V	
Q2	25 V	1.1 $\text{m}\Omega$ @ 10 V	155 A
		1.33 $\text{m}\Omega$ @ 4.5 V	




PQFN8  
POWER CLIP  
CASE 483AR

### MARKING DIAGRAM



2EKN = Specific Device Code  
A = Assembly Location  
Y = Year  
WW = Work Week  
ZZ = Assembly Lot Code

### ELECTRICAL CONNECTION



### ORDERING INFORMATION

Device	Package	Shipping†
NTMFD1D4N02P1E	PQFN8 (Pb-Free)	3000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

# NTMFD1D4N02P1E

**Table 1. THERMAL RESISTANCE RATINGS**

Parameter	Symbol	Q1 Max	Q2 Max	Units
Junction-to-Case – Steady State (Note 1, 3)	$R_{\theta JC}$	4.4	2.9	°C/W
Junction-to-Ambient – Steady State (Note 1, 3)	$R_{\theta JA}$	60	55	
Junction-to-Ambient – Steady State (Note 2, 3)	$R_{\theta JA}$	130	120	

- Surface-mounted on FR4 board using 1 in<sup>2</sup> pad size, 2 oz Cu pad.
- Surface-mounted on FR4 board using minimum pad size, 2 oz Cu pad.
- The entire application environment impacts the thermal resistance values shown. They are not constants and are only valid for the particular conditions noted. Actual continuous current will be limited by thermal & electro-mechanical application board design.  $R_{\theta CA}$  is determined by the user's board design.
- Q1 100% UIS tested at L = 0.1 mH,  $I_{AS} = 16.5$  A.  
Q2 100% UIS tested at L = 0.1 mH,  $I_{AS} = 36$  A.

**Table 2. ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise stated)

Parameter	Symbol	Test Condition	FET	Min	Typ	Max	Unit
<b>OFF CHARACTERISTICS</b>							
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0$ V, $I_D = 250$ $\mu$ A	Q1	25			V
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS} = 0$ V, $I_D = 1$ mA	Q2	25			V
Drain-to-Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS} / T_J$	$I_D = 250$ $\mu$ A, ref to $25^\circ\text{C}$	Q1		16		mV/°C
		$I_D = 1$ mA, ref to $25^\circ\text{C}$	Q2		19		
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{GS} = 0$ V, $V_{DS} = 20$ V	$T_J = 25^\circ\text{C}$	Q1		10	$\mu$ A
				Q2		10	
Gate-to-Source Leakage Current	$I_{GSS}$	$V_{DS} = 0$ V, $V_{GS} = +16$ V / $-12$ V	Q1			$\pm 100$	nA
			Q2			$\pm 100$	

**ON CHARACTERISTICS** (Note 5)

Gate Threshold Voltage	$V_{GS(TH)}$	$V_{GS} = V_{DS}$ , $I_D = 250$ $\mu$ A	Q1	1.2	1.54	2.0	V
		$V_{GS} = V_{DS}$ , $I_D = 800$ $\mu$ A	Q2	1.2	1.55	2.0	
Threshold Temperature Coefficient	$V_{GS(TH)} / T_J$	$I_D = 250$ $\mu$ A, ref to $25^\circ\text{C}$	Q1		-4.3		mV/°C
		$I_D = 800$ $\mu$ A, ref to $25^\circ\text{C}$	Q2		-4.4		
Drain-to-Source On Resistance	$R_{DS(on)}$	$V_{GS} = 10$ V, $I_D = 20$ A	Q1		2.6	3.3	m $\Omega$
		$V_{GS} = 4.5$ V, $I_D = 18$ A			3.4	4.2	
		$V_{GS} = 10$ V, $I_D = 37$ A	Q2		0.81	1.1	
		$V_{GS} = 4.5$ V, $I_D = 33$ A			1.04	1.33	
Forward Transconductance	$g_{FS}$	$V_{DS} = 5$ V, $I_D = 20$ A	Q1		125		
		$V_{DS} = 5$ V, $I_D = 37$ A	Q2		285		
Gate Resistance	$R_G$	$T_A = 25^\circ\text{C}$	Q1		0.44		$\Omega$
			Q2		0.6		

**CHARGES & CAPACITANCES**

Input Capacitance	$C_{ISS}$	$V_{GS} = 0$ V, $V_{DS} = 13$ V, $f = 1$ MHz	Q1		1180		pF
			Q2		3603		
Output Capacitance	$C_{OSS}$		Q1		320		pF
			Q2		940		
Reverse Capacitance	$C_{RSS}$		Q1		22		pF
			Q2		64		

- Pulse Test: pulse width  $\leq 300$   $\mu$ s, duty cycle  $\leq 2\%$
- Switching characteristics are independent of operating junction temperatures

# NTMFD1D4N02P1E

**Table 2. ELECTRICAL CHARACTERISTICS** ( $T_J = 25^\circ\text{C}$  unless otherwise stated)

Parameter	Symbol	Test Condition	FET	Min	Typ	Max	Unit
<b>CHARGES &amp; CAPACITANCES</b>							
Total Gate Charge	$Q_{G(TOT)}$	Q1: $V_{GS} = 4.5\text{V}$ , $V_{DS} = 13\text{V}$ , $I_D = 20\text{A}$ Q2: $V_{GS} = 4.5\text{V}$ , $V_{DS} = 13\text{V}$ , $I_D = 37\text{A}$	Q1		7.2		nC
			Q2		21.5		
Gate-to-Drain Charge	$Q_{GD}$		Q1		1.35		nC
			Q2		3.9		
Gate-to-Source Charge	$Q_{GS}$		Q1		3.15		nC
			Q2		9.1		
Total Gate Charge	$Q_{G(TOT)}$	$V_{GS} = 10\text{V}$ , $V_{DS} = 13\text{V}$ , $I_D = 20\text{A}$	Q1		16.4		nC
		$V_{GS} = 10\text{V}$ , $V_{DS} = 13\text{V}$ , $I_D = 37\text{A}$	Q2		48.6		

**SWITCHING CHARACTERISTICS,  $V_{GS} = 4.5\text{V}$**  (Note 6)

Turn-On Delay Time	$t_{d(ON)}$	$V_{GS} = 4.5\text{V}$ Q1: $I_D = 20\text{A}$ , $V_{DD} = 13\text{V}$ , $R_G = 6\Omega$ Q2: $I_D = 37\text{A}$ , $V_{DD} = 13\text{V}$ , $R_G = 6\Omega$	Q1		11.6		ns
			Q2		21.4		
Rise Time	$t_r(ON)$		Q1		2.7		ns
			Q2		8.7		
Turn-Off Delay Time	$t_{d(OFF)}$		Q1		15.6		ns
			Q2		30.7		
Fall Time	$t_f$	Q1		3.2		ns	
		Q2		8.5			

**SWITCHING CHARACTERISTICS,  $V_{GS} = 10\text{V}$**  (Note 6)

Turn-On Delay Time	$t_{d(ON)}$	$V_{GS} = 10\text{V}$ Q1: $I_D = 20\text{A}$ , $V_{DD} = 13\text{V}$ , $R_G = 6\Omega$ Q2: $I_D = 37\text{A}$ , $V_{DD} = 13\text{V}$ , $R_G = 6\Omega$	Q1		7.9		ns
			Q2		10.2		
Rise Time	$t_r(ON)$		Q1		1.1		ns
			Q2		3.3		
Turn-Off Delay Time	$t_{d(OFF)}$		Q1		21.3		ns
			Q2		48.9		
Fall Time	$t_f$	Q1		2.2		ns	
		Q2		7.4			

**SOURCE-TO-DRAIN DIODE CHARACTERISTICS**

Forward Diode Voltage	$V_{SD}$	$V_{GS} = 0\text{V}$ , $I_S = 20\text{A}$	$T_J = 25^\circ\text{C}$	Q1		0.8	1.2	V
			$T_J = 125^\circ\text{C}$			0.7		
		$V_{GS} = 0\text{V}$ , $I_S = 37\text{A}$	$T_J = 25^\circ\text{C}$	Q2		0.8	1.2	
			$T_J = 125^\circ\text{C}$			0.65		
Reverse Recovery Time	$t_{RR}$	$V_{GS} = 0\text{V}$ , Q1: $I_S = 20\text{A}$ , $dI/dt = 100\text{A}/\mu\text{s}$ Q2: $I_S = 37\text{A}$ , $dI/dt = 300\text{A}/\mu\text{s}$	Q1		21.4		ns	
			Q2		36.5			
Reverse Recovery Charge	$Q_{RR}$		Q1		8.3		nC	
			Q2		21.9			

5. Pulse Test: pulse width  $\leq 300\ \mu\text{s}$ , duty cycle  $\leq 2\%$

6. Switching characteristics are independent of operating junction temperatures

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

# NTMFD1D4N02P1E

## TYPICAL CHARACTERISTICS FOR Q1




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature






Figure 6. Drain-to-Source Leakage Current vs. Voltage

# NTMFD1D4N02P1E


## TYPICAL CHARACTERISTICS FOR Q1 (continued)




**Figure 7. Capacitance Variation**




**Figure 8. Gate-to-Source vs. Total Charge**




**Figure 9. Resistive Switching Time Variation vs. Gate Resistance**



**Figure 10. Diode Forward Voltage vs. Current**



**Figure 11. Maximum Rated Forward Biased Safe Operating Area**



**Figure 12. Maximum Drain Current vs. Time in Avalanche**

# NTMFD1D4N02P1E

## TYPICAL CHARACTERISTICS FOR Q1 (continued)




Figure 13. Thermal Response

# NTMFD1D4N02P1E

## TYPICAL CHARACTERISTICS FOR Q2




Figure 14. On-Region Characteristics




Figure 15. Transfer Characteristics




Figure 16. On-Resistance vs. Gate-to-Source Voltage




Figure 17. On-Resistance vs. Drain Current and Gate Voltage




Figure 18. On-Resistance Variation with Temperature




Figure 19. Drain-to-Source Leakage Current vs. Voltage

# NTMFD1D4N02P1E

## TYPICAL CHARACTERISTICS FOR Q2 (continued)




Figure 20. Capacitance Variation




Figure 21. Gate-to-Source vs. Total Charge




Figure 22. Resistive Switching Time Variation vs. Gate Resistance




Figure 23. Diode Forward Voltage vs. Current




Figure 24. Maximum Rated Forward Biased Safe Operating Area




Figure 25. Maximum Drain Current vs. Time in Avalanche



# NTMFD1D4N02P1E

## TYPICAL CHARACTERISTICS FOR Q2 (continued)






Figure 26. Thermal Response

# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS



**PQFN8 5.00x6.00x0.75, 1.27P**  
CASE 483AR  
ISSUE D

DATE 06 NOV 2023



NOTES: UNLESS OTHERWISE SPECIFIED

- A) DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MO-229, DATED 11/2001.
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
- D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.70	0.75	0.80
A1	0.00	-	0.05
A3	0.20 REF		
b	0.51 BSC		
D	4.90	5.00	5.10
D2	3.05	3.15	3.25
D3	4.12	4.22	4.32
D4	3.80	3.90	4.00
E	5.90	6.00	6.10
E2	2.36	2.46	2.56
E3	0.81	0.91	1.01
E4	1.27	1.37	1.47
E5	0.59 REF		
e	1.27 BSC		
e/2	0.635 BSC		
e1	3.81 BSC		
k	0.52 REF		
L	0.38	0.48	0.58
L4	1.47	1.57	1.67
z	0.55 REF		
z1	0.39 REF		

**RECOMMENDED LAND PATTERN**  
\*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERM/D.

<b>DOCUMENT NUMBER:</b>	<b>98AON13666G</b>	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
<b>DESCRIPTION:</b>	<b>PQFN8 5.00x6.00x0.75, 1.27P</b>	<b>PAGE 1 OF 1</b>

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)