

ON Semiconductor

Is Now

onsemi™

To learn more about onsemi™, please visit our website at
www.onsemi.com

onsemi and **onsemi** and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner. Other names and brands may be claimed as the property of others.

PCRKA20065F8M1

650 V, 200 A Extremefast Diode with Solderable Top Metal



ON Semiconductor®


www.onsemi.com

Features

- AEC-Q101 Qualified
- Maximum Junction Temperature 175°C
- Extremefast Technology with Soft Recovery
- Low Forward Voltage ($V_F = 1.35$ V (Typ.) @ $I_F = 200$ A)
- Cathode Pad covered with Solderable Metal Layer

Applications

- Automotive Traction Modules
- General Power Modules



ORDERING INFORMATION

Part Number	PCRKA20065F8M1	
Packing	Wafer (sawn on foil)	
	mils	μm
Die Size	197 × 394	5,000 × 10,000
Anode Area	183 × 381	4,668 × 9,668
Die Thickness	3	78
Top Metal	6 μm AlCu + 1.15 μm Ti/NiV/Ag (STM)	
Back Metal	0.65 μm NiV/Ag	
Topside Passivation	Silicon Nitride plus Polyimide	
Wafer Diameter	200 mm	
Max Possible Die Per Wafer	487	

PCRKA20065F8M1

ABSOLUTE MAXIMUM RATINGS (T_{VJ} = 25°C unless otherwise noted)

Parameter	Symbol	Ratings	Units
Repetitive Peak Reverse Voltage	V _{RRM}	650	V
DC Forward Current, limited by T _J max	I _F	(Note 1)	A
Pulsed Forward Current, t _p limited by T _J max (Note 2)	I _{FM}	900	A
Operating Junction Temperature	T _J	-40 to +175	°C
Storage Temperature Range	T _{stg}	+17 to +25	°C

1. Depends on the thermal properties of assembly
2. Not subject to production test – verified by design/characterization

ELECTRICAL CHARACTERISTICS OF THE DIODE (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Units
-----------	--------	----------------	------	------	------	-------

Static Characteristics (Tested on wafers)

Breakdown Voltage	V _{BR}	I _R = 1 mA	650	–	–	V
Reverse Leakage Current	I _R	V _R = 650 V	–	–	30	μA
Forward Voltage	V _F	I _F = 100 A	–	1.15	1.7	V

Electrical Characteristics (Not subject to production test – verified by design / characterization)

Forward Voltage	V _F	I _F = 200 A	T _J = 25°C	–	1.35	1.9	V
			T _J = 175°C	–	1.3	–	V
Reverse Recovery Charge	Q _{rr}	I _F = 200 A, V _R = 400 V dI _F /dt = 1000 A/μs, T _J = 25°C	–	3.2	–	μC	
Reverse Recovery Current	I _{rr}		–	55	–	A	
Reverse Recovery Time	T _{rr}		–	117	–	ns	
Reverse Recovery Charge	Q _{rr}	I _F = 200 A, V _R = 400 V dI _F /dt = 1000 A/μs, T _J = 175°C	–	15.1	–	μC	
Reverse Recovery Current	I _{rr}		–	122	–	A	
Reverse Recovery Time	T _{rr}		–	247	–	nS	

3. For ordering, technique and other information on Onsemi automotive bare die products, please contact automotivebaredie@onsemi.com

PCRKA20065F8M1





Figure 1. Dimensional Outline and Pad Layout

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910

ON Semiconductor Website: www.onsemi.com

Order Literature: <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative