

Product Overview

LM324: Operational Amplifier, Single Supply, Quad

For complete documentation, see the data sheet.

The LM324 series are low-cost, quad op-amps with true differential inputs. They have several distinct advantages over standard operational amplifier types in single supply applications. The quad amplifier can operate at supply voltages as low as 3.0 V or as high as 32 V with quiescent currents about one-fifth of those associated with the MC1741 (on a per amplifier basis). The common mode input range includes the negative supply, thereby eliminating the necessity for external biasing components in many applications. The output voltage range also includes the negative power supply voltage.

Features

- Short Circuited Protected Outputs
- True Differential Input Stage
- Single Supply Operation: 3.0 V to 32 V (LM224, LM324, LM324A)
- Low Input Bias Currents: 100 nA Maximum (LM324A)
- Four Amplifiers Per Package
- Internally Compensated
- Common Mode Range Extends to Negative Supply
- Industry Standard Pinouts
- ESD Clamps on the Inputs Increase Ruggedness without Affecting Device Operation
- Pb-Free Packages are Available*

For more features, see the data sheet

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Rail to Rail	Channels	V _S Min (V)	V _S Max (V)	I _q Typ (mA)	V _{OS} Max (mV)	GBW Typ (MHz)	SR Typ (V/μs)	I _O Typ (mA)	ΔV _{OS} /ΔT (μV/C)	e _N (nV/√Hz)	I _{bias} Typ (pA)	CMRR Typ (dB)	Architecture	Temperature Range (°C)	Package Type
LM324DR2G	0.0816	Pb-free Halide free	Active	No	4	3	32	0.35	7	1	0.6	40	7	-	-90000	70	Bipolar	0 to 70	SOIC-14
LM324DTBR2G	0.1245	Pb-free Halide free	Active	No	4	3	32	0.35	7	1	0.6	40	7	-	-90000	70	Bipolar	0 to 70	TSSOP-14
LM324EDR2G	0.084	Pb-free Halide free	Active	No	4	3	32	0.35	3	1	0.6	40	7	-	-45000	70	Bipolar	0 to 70	SOIC-14

For more information please contact your local sales support at www.onsemi.com.

Created on: 7/9/2020