

Product Overview

NB7V585M: Input Mux - 2:1 Differential, 1.8 V / 2.5 V, Clock / Data Fanout Buffer - 1:6 CML

For complete documentation, see the data sheet.



The NB7V585M is a differential 1-to-6 CML clock/data distribution chip featuring a 2:1 Clock/Data input multiplexer with an input select pin. The INx/INxb inputs incorporate internal 50-ohm termination resistors and will accept LVPECL, CML, or LVDS logic levels. The NB7V585M produces six identical output copies of clock or data operating up to 7GHz or 10.7Gb/s, respectively. As such, NB7V585M is ideal for SONET, GigE, Fiber Channel, Backplane and other clock/data distribution applications. The 16mA differential CML output structure provides matching internal 50-ohm source terminations, 400mV output swings when externally terminated with a 50-ohm resistor to VCC and is optimized for low skew and minimal jitter. The NB7V585M is powered with either 1.8V or 2.5V supply and is offered in a low profile 5x5mm 32-pin QFN package.

Features

- Maximum Input Data Rate > 10 Gb/s Typical
- Data Dependent Jitter < 10 ps
- Maximum Input Clock Frequency > 6 GHz Typical
- Random Clock Jitter < 0.8 ps RMS, Max
- Low Skew 1:6 CML Outputs, 30 ps Max
- 2:1 MultiLevel Mux Inputs
- 175 ps Typical Propagation Delay
- 50 ps Typical Rise and Fall Times
- Operating Range: VCC = 1.71 V to 1.89 V
- Internal 50-ohm Input Termination Resistors

For more features, see the data sheet

Applications

- Clock Distribution: SONET/SDH, Fibre Channel, Gigabit Ethernet

End Products

- Routers, Servers

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Input/Output Ratio	Channels	Input Level	Output Level	V _{CC} Typ (V)	f _{Max} Typ (MHz)	t _{jitter} Typ (ps)	t _{skew(00) Max} (ps)	t _{pd} Typ (ns)	Package Type
NB7V585MMNR4G		Pb-free	Active	2:1	1	LVDS	CML	1.8	7000	0.2	30	175	QFN-32
		Halide free				CML		2.5					
						ECL							

For more information please contact your local sales support at www.onsemi.com.

Created on: 7/5/2020