

Product Overview

MM3Z4V7: 300 mW 4.7 V \pm 5% Zener Diode Voltage Regulator

For complete documentation, see the data sheet.

This Zener Diode Voltage Regulator is packaged in a SOD323 surface mount package, which has a power dissipation of 300 milliwatts. It is designed to provide voltage regulation protection and is especially attractive in situations where space is at a premium. It is well suited for applications such as cellular phones, hand held portables and high density PC boards.

Features

- Standard Zener Breakdown Voltage Range - 2.4 V to 75 V
- Steady State Power Rating of 300 mW
- Small Body Outline Dimensions: 0.067" X 0.049" (1.7 mm X 1.25 mm)
- Low Body Height: 0.035" (0.9 mm)
- Package Weight: 4.507 mg/unit
- ESD Rating of Class 3 (>16 KV) per Human Body Model
- CASE: Void-free, transfer-molded plastic
- FINISH: All external surfaces are corrosion resistant
- MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES: 260°C for 10 Seconds
- LEADS: Plated with Pb/Sn or Sb only (Pb-Free)

For more features, see the data sheet

Applications

- Zener voltage regulation

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	V _Z Typ (V)	P Max (W)	Package Type
MM3Z4V7T1G	0.0152	Pb-free Halide free	Active	4.7	0.3	SOD-323
SZMM3Z4V7T1G	0.0293	AEC Qualified PPAP Capable Pb-free Halide free	Active	4.7	0.3	SOD-323

For more information please contact your local sales support at www.onsemi.com.

Created on: 7/11/2020