



Product Overview

NVTFS5826NL: Power MOSFET 60V, 20A, 24 mOhm, Single N-Channel, u8FL, Logic Level.

For complete documentation, see the data sheet.



Automotive Power MOSFET in a 3x3mm flat lead package designed for compact and efficient designs and including high thermal performance. Wettable Flank Option available for Enhanced Optical Inspection. AEC-Q101 Qualified MOSFET and PPAP capable suitable for automotive applications.

Features

- Low on resistance
- High current capability
- 100% avalanche tested
- AEC-Q101 Qualified
- Solenoid driver

Benefits

- Minimal conduction losses
- Robust load performance
- Safeguard against voltage overstress failures
- Suitable for automotive applications

Applications

- Motor driver
- Solenoid Driver
- Lamp Driver

End Products

- Automotive engine controllers
- Automotive body controllers

Part Electrical Specifications

Product	Pricing (\$/Unit)	Compliance	Status	Channel Polarity	Configuration	$V_{DS(BR)}$ Min (V)	V_{GS} Max (V)	$V_{GS(th)}$ Max (V)	I_D Max (A)	P_D Max (W)	$R_{DS(on)}$ Max @ $V_{GS} = 2.5V$ (mΩ)	$R_{DS(on)}$ Max @ $V_{GS} = 4.5V$ (mΩ)	$R_{DS(on)}$ Max @ $V_{GS} = 10V$ (mΩ)	Q_g Typ @ $V_{GS} = 4.5V$ (nC)	Q_g Typ @ $V_{GS} = 10V$ (nC)	C_{iss} Typ (pF)	Package Type
NVTFS5826NLTAG		AEC Qualified PPAP Capable Pb-free Halide free	Active	N-Channel	Single	60	20	2.5	20	22		32	24	8.3	16	850	WDF N-8 / u8FL
NVTFS5826NLTWG		AEC Qualified PPAP Capable Pb-free Halide free	Active	N-Channel	Single	60	20	2.5	20	22		32	24	8.3	16	850	WDF N-8 / u8FL
NVTFS5826NLWFTAG		AEC Qualified PPAP Capable Pb-free Halide free	Active	N-Channel	Single	60	20	2.5	20	22		32	24	8.3	16	850	WDF N-8 / u8FL
NVTFS5826NLWFTWG		AEC Qualified PPAP Capable Pb-free Halide free	Active	N-Channel	Single	60	20	2.5	20	22		32	24	8.3	16	850	WDF N-8 / u8FL

For more information please contact your local sales support at www.onsemi.com.

Created on: 8/11/2020