

Product Overview

FUSB302B: Programmable USB Type-C Controller with PD (Default SNK)

For complete documentation, see the data sheet.

The FUSB302B targets system designers looking to implement a DRP/SRC/SNK USB Type-C connector with low amount of programmability. The FUSB302B enables the USB Type-C detection including attach, and orientation. The FUSB302B integrates the physical layer of the USB BMC Power Delivery protocol to allow up to 100 W of power and role swap. The BMC PD block enables full support for alternative interfaces of the Type-C specification. Reference code is available for the FUSB302B for easy implementation of Type-C and USB BMC Power Delivery protocol across several embedded controller platforms. Click on the Software link below.

Features

- Dual-Role Functionality with Autonomous DRP Toggle
- Ability to connect as either a host or a device based on what has been attached.
- Software configurable either as a dedicated host, dedicated device, or dual role.
- Dedicated devices can operate both on a Type-C receptacle or a Type-C plug with a fixed CC and VCONN channel.
- Full Type-C 1.2 Support. Integrates the following functionality of the CC pin
- Attach/Detach Detection as Host
- Current Capability Indication as Host
- Current Capability Detection as Device
- Audio Adapter Accessory Mode
- Debug Accessory Mode

For more features, see the data sheet

Applications

- This product is general usage and suitable for many different applications.

Part Electrical Specifications							
Product	Pricing (\$/Unit)	Compliance	Status	Mode Support	Power Delivery Communication Support	IC Features	Package Type
FUSB302B01MPX	0.44	Pb-free Halide free non AEC-Q and PPAP	Active	DFP (Source) DRP UFP (Sink)	Yes	Debug Accessory Support	WQFN-14
FUSB302B10MPX	0.44	Pb-free Halide free non AEC-Q and PPAP	Active	DFP (Source) DRP UFP (Sink)	Yes	Debug Accessory Support	WQFN-14
FUSB302B11MPX	0.44	Pb-free Halide free non AEC-Q and PPAP	Active	DFP (Source) DRP UFP (Sink)	Yes	Debug Accessory Support	WQFN-14
FUSB302BMPX	0.44	Pb-free Halide free non AEC-Q and PPAP	Active	DFP (Source) DRP UFP (Sink)	Yes	Debug Accessory Support	WQFN-14
FUSB302BUCX	0.3333	Pb-free Halide free non AEC-Q and PPAP	Active	DFP (Source) DRP UFP (Sink)	Yes	Debug Accessory Support	WLCSP-9
FUSB302BVMPX	0.572	AEC Qualified PPAP Capable Pb-free Halide free	Active	DRP	Yes	Automotive	WQFN-14

For more information please contact your local sales support at www.onsemi.com.

Created on: 10/29/2020