

Product Overview

FOD8332: Input LED Drive, 2.5 A Output Current, IGBT Drive Optocoupler with Desaturation Detection, Isolated Fault Sensing, and Active Miller Clamp

For complete documentation, see the data sheet.

The FOD8332 is an advanced 2.5 A output current IGBT drive optocoupler capable of driving medium power IGBTs with ratings up to 1,200 V and 150 A. It is suited for fast-switching driving of power IGBTs and MOSFETs used in motor control inverter applications and high-performance power systems. The FOD8332 offers critical protection features necessary for preventing fault conditions that lead to destructive thermal runaway of IGBTs. The device utilizes Fairchild's proprietary Optoplanar® coplanar packaging technology and optimized IC design to achieve reliable high isolation voltage and high noise immunity, characterized by high common-mode rejection and power supply rejection specifications. The device is housed in a wide-body 16-pin small-outline plastic package. The gate-driver channel consists of an aluminum gallium arsenide (AlGaAs) light-emitting diode (LED) optically coupled to an integrated high-speed driver circuit with a low-RDS(ON) MOSFET output stage. The fault-sense channel consists of an aluminium gallium arsenide (AlGaAs) LED optically coupled to an integrated high-speed feedback circuit for fault sensing.

Features

- Input LED Drive Facilitates Receiving Digitally Encoded Signals from PWM Output
- Optically Isolated Fault-Sensing Feedback
- Active Miller Clamp to Shut Off IGBT During High dv/dt without Negative Supply Voltage
- High Noise Immunity Characterized by Common Mode Rejection – 35 kV/μs Minimum, VCM = 1500 VPEAK
- 2.5 A Peak Output Current Driving Capability for Medium Power IGBT
- P-Channel MOSFETs at Output Stage Enable Output Voltage Swing Close to Supply Rail (Rail-to-Rail Output)
- Wide Supply Voltage Range: 15 V to 30 V
- Integrated IGBT Protection
- Desaturation Detection
- “Soft” IGBT Turn-Off

For more features, see the data sheet

Applications

- Automation
- Consumer Appliances
- Energy Generation & Distribution
- Industrial Motor
- Motion Control - Industrial Motor

Part Electrical Specifications

Product	Compliance	Status	I_{FLH} (Max) (mA)	I_{DDL}, I_{DDH} (Max) (mA)	I_{OL}, I_{OH} (Min) (A)	t_{PHL}, t_{PLH} (Max) (ns)	PWD (Max) (ns)	V_{UVLO} (Typ) (V)	V_{UVLO-} (Typ) (V)	CMR (Min) (kV/μs)	V_{ISO} (Min) (V)	T_{OPR} (Min) (°C)	T_{OPR} (Max) (°C)	Package Type
FOD8332	Pb-free	Active	7	5	2.5	250	100	11.7	10.7	35	4243	-40	100	SOIC16 W
FOD8332R2	Pb-free	Active	7	5	2.5	250	100	11.7	10.7	35	4243	-40	100	SOIC16 W
FOD8332R2V	Pb-free	Active	7	5	2.5	250	100	11.7	10.7	35	4243	-40	100	SOIC16 W
FOD8332V	Pb-free	Active	7	5	2.5	250	100	11.7	10.7	35	4243	-40	100	SOIC16 W

For more information please contact your local sales support at www.onsemi.com.

Created on: 10/18/2019